

39° 20' 00"

Latitude

80° 15' 00"

Longitude

Topo Location

7.5' Loc.	<u>1.565</u>	15' Loc.	<u>1.565</u>
	<u>1.44W</u>	(calc.)	<u>1.44W</u>

Company Aramelli Chemical Company

Farm M. R. Lodge 5

15' Quad Clarkburg (SE)
(sec.)

7.5' Quad Clarkburg

District Simpson

WELL LOCATION PLAT

County 033 Permit 70513

dry hole

M. R. Lodge Well No. 5 (G 103)

Simpson District, Harrison County, on Simpson Creek about two miles north of Bridgeport; completed in 1924 or 1925; authority, Grasselli Chemical Company; elevation, _____.

	Top. Feet.	Bottom. Feet.
Conductor.....	---	16
Slate.....	16	100
Lime.....	100	360
Big Dunkard.....	360	400
Slate.....	400	485
Gas Sand.....	485	540
Slate-Shells.....	540	585
1st. Salt Sand.....	585	685
Slate.....	685	710
2nd. Salt Sand.....	710	905
Red Rock.....	905	1190
Slate-Lime.....	1190	1270
Little Lime.....	1270	1280
Pencil Cave.....	1280	1300
Big Lime.....	1300	1378
Big Injun.....	1378	1470
Broken Lime.....	1470	1845
Fifty Foot.....	1845	1940
Slate.....	1940	1945
Thirty Foot.....	1945	2040
Red Rock.....	2040	2230
Gordon Sand.....	2230	2255
Slate-Shells.....	2255	2280
4th. Sand.....	2280	2295
Slate.....	2295	2362
5th Sand (S.Lime).....	2362	2394
Total Depth.....	---	2405

After drilling through the 5th. Sand there was not enough gas to get an open flow test.

This well was shot in the 5th Sand. After shot, cleaned out and tubed with 2" Tubing, same showed 2 tenth inches water through a 3/3" Orifice Plate which represents about 4,150 cu. ft. for 24 hours.