



*Abandoned Aug. 48*

*3.90-S  
3.92-S  
2.05-W  
2.01-W*

New Location  X  
 Drill Deeper   
 Abandonment

LOCATION 0.9 M. SOUTH MT. TELL

Company COLUMBIAN CARBON CO.  
 Address BOX 1240 - CHARLESTON - W. VA.  
 Farm E. F. FISHER ET AL  
 Tract C-1547-1548-1549 Acres 368 1/4 Lease No. 1550-1552  
 Well (Farm) No. TWO Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 886.2  
 Quadrangle KENNA S.E. C-5  
 County JACKSON District RIPLEY  
 Engineer J. Miller  
 Engineer's Registration No. 772  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date 7-21-41 Scale 1" = 1320'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. JAC-189

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500. latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Jac-189	Columbian Carbon Co.	Gas Well		
Company	Box 1240, Charleston, W. Va.	Casing & Tubing	16"	41'0" 41'0"
Address	E. F. Fisher, et al Acres 368 $\frac{1}{2}$	10-3/4"	937'6"	Pulled
Farm	Duddons Fork	8 5/8"	2117'6"	2117'6"
Location	2 (GW-608) Elev. 900.6 DF	7"	5158'11"	5158'11"
Well No.	Ripley Jackson County	2 3/8"	5311'6"	5311'6"
District	S. J. Slater, et ux			
Surface	R. F. D. #1, Kenna, W. Va.			
Mineral	Same			
Commenced	8-6-41			
Completed	10-26-41			
Volume	4,500 MCF			
Rock Pressure	860 Lbs., 3 days			
Fresh water	490-540 1-13" Blr. per Hr.			
Salt water	1565 Show; 1615 Hole Full; 1620 2-10" Blrs. per Hr.			

Yellow Clay	0	15	Black Slate	1325	1515
Blue Sand	15	30	Grey Slate	1515	1550
Blue Slate	30	41	1st Salt Sand	1550	1640
Grey Sand	41	108	Slate	1640	1650
White Slate	108	118	2nd Salt Sand	1650	1807
Red Rock	118	150	Black Slate	1807	1816
Blue Slate	150	175	Sand	1816	1827
Red Rock	175	210	Black Slate	1827	1830
White Slate	210	255	Maxon Sand	1830	1870
Red Rock	255	280	Big Lime	1870	1996
Blue Slate	280	310	Sandy Lime	1996	2035
Red Rock	310	345	Big Injun Sand	2035	2062
Grey Slate	345	367	Black Lime	2062	2078
Blue Slate	367	425	Blue Slate	2078	2090
Red Rock	425	435	Sand - squaw?	2090	2105
Blue Slate	435	450	Blue Slate	2105	2115
Red Rock	450	461	Slate & Lime Shells	2115	2240
Slate	460	490	Slate	2240	2480
Sand	490	540	Lime Shells	2480	2775
Red Rock	540	555	Slate & Shells	2775	2900
Slate	555	563	Grey Shale	2900	3250
Red Rock	563	593	Dark Slate	3250	3400
Slate	593	610	Slate & Shells	3400	3730 Gas 3630 Show
Red Rock	610	690	Brown Shale	3730	3780
Blue Slate	690	710	Slate & Shells	3780	4073
Red Rock	710	785	Dark Shale	4073	4135
Blue Lime	785	810	White Slate	4135	4170
White Slate	810	825	Brown Shale	4170	4348
Red Rock	825	835	White Slate	4348	4434
White Slate	835	877	Brown Shale	4434	4560
Black Slate	877	896	White Slate	4560	4609
Sand	896	908	Brown Shale	4609	4630
Blue Slate	908	927	Grey Slate	4630	4815
Lime Shell	927	945	Brown Shale	4815	5108 SLM
Sand	945	1005	Corniferous Lime - 463	5108 S.M	5217 SLM
Grey Slate	1005	1065	Oriskany Sand	5217 SLM	5275
Sand	1065	1085	Lime	5275	5286 PAY: 5222-5231
White Slate	1085	1128	Oriskany Sand	5286	5297
Black Slate	1128	1152	Lime	5297	5300
Sand	1152	1200	Oriskany Sand	5300	5302 DLM
Blue Slate	1200	1273		5302' DLM =	5295' SLM
Sand	1273	1295	TOTAL DEPTH		5295' SLM
White Slate	1295	1325			

CEMENT RECORD:

9- 6-41 ---Cemented 8 5/8" casing.  
Ran 100 sacks Superior cement mixed with 1 sack Aquagol,  
13' cement in pipe.

10-14-41 ---Cemented 7" casing.  
Ran 11 sacks Alpha cement with dump bailer.  
40' cement in pipe.

485