



Abandoned Feb. 48

1.62 S
0.25 W
0.24 W

New Location X
Drill Deeper
Abandonment

Company United Carbon Co.
 Address Charleston, W. Va.
 Farm O. M. Lewis
 Tract _____ Acres 36 Lease No. 2466
 Well (Farm) No. 1 Serial No. 1047
 Elevation (Spirit Level) 877.3
 Quadrangle Kenna WC
 County Jackson District Ripley
 Engineer E.G. Withrow
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date Dec. 19, 1941 Scale 1" = 330'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. J2C-275

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500. latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

6-6 192

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. JAC-275

Company United Carbon Company
 Address United Carbon Bldg., Chas., W.Va.
 Farm O.M. Lewis Acres 36
 Location Left Fork Pocah.
 Well No. 1 Elev. 377.3
 District Ripley Jackson County
 Surface O.M. Lewis, Sissonville, W.Va.
 Mineral Same
 Commenced 2-17-42
 Completed 5-30-42
 Shot 5-30-42 5141-5171 with 60 qts. Glys.
 Flow 13/10ths Merc. in 7"-24#
 Volume 5,628,000 C.F.
 Rock Pressure 1350 lbs. 12 hrs.
 Salt Water 1665 H.F.

Gas Well

Casing & Tubing
 13 3/8 472' 00
 10 3/4 912' 00
 8 5/8 2130 2130
 7 5048 5048
 2 3/8 5177
 Casing cemented 8 5/8" 522'
 4-12-42
 7" 212' 5-19-42

Clay	0	16
Red Rock	16	75
Sand	75	90
Red Rock	90	140
Slate	140	180
Red Rock	180	360
Slate	360	385
Red Rock	385	440
Slate	440	475
Sl. & Sh.	475	525
Sand	525	535
Sl. & Sh.	535	598
Red Rock	598	645
Lime	645	680
Red Rock	680	765
Sl. & Sh.	765	825
Sand	825	910
Lime	910	920
Sand	920	950
Sl. & Sh.	950	975
Sand	975	1043
Slate	1043	1085
Sand	1085	1190
Sl. & Sh.	1190	1345
Sand	1345	1435
Slate	1435	1445
Lime	1445	1490
Slate	1490	1535
Lime	1535	1605
Salt Sand	1605	1975
Big Lime	1975	2035
Injun Sand	2035	2079
Lime Bk.	2079	2085
Sl. & Sh.	2085	2300
Slate-Wh.	2300	2505
Broa Sand	2505	2528
Sl. & Sh.	2528	3045
Wh. Slate	3045	3725
Br. Shale - 441	3725	3775
Slate	3775	4015
Br. Shale	4015	4305
Sl. & Sh.	4305	4440
Br. Shale	4440	4460
Wh. Slate	4460	4735
Br. Shale	4735	4951
Bk. Shale	4951	5031 - MARCELLUS
Cornif. Lime - 413	5031	5133
Oris. Sand	5133	5174
Lime - Held	5174	
Total Depth		5183

Gas Show

485