



New Location
 Drill Deeper
 Abandonment

Company GODFREY L. CABOT INC.
 Address 900 UNION BLDG. CHARLESTON W.VA
 Farm The Putnam Co.
 Tract _____ Acres _____ Lease No. 3-464
 Well (Farm) No. 32 Serial No. 1036
 Elevation (Spirit Level) 765.11
 Quadrangle KENNA
 County JACKSON District Ripley
 Engineer Ray Booton
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date 2-23-42 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. JAC-301

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

66 192

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Jac 301

Company
Address
Farm
Location
Well No.
District
Surface
Commenced
Completed
Shot
Volume
Rock Pressure
Salt Water

Godfrey L. Cabot, Inc.
Charleston, W. Va.
The Putnam Co.
32 Ser 1036 Elev. 765.11
Riploy Jackson County
March 16, 1942
June 1, 1942
6-1-42 5040 to 5060, 40 qts.
4720 MCF. A.S. 20 Min. ; 520 M. B.S.
1575 lbs. 40 hrs. Oriskany
Back Pressure 1-1/4 #.
1510 one blr.; 1590 Hole Full
Tubed and shut in 6-23-42

Gas Well
CASING & TUBING

1 3/8	65	65
10 1/2	873	873
8 5/8	2050	-
7"	4951	4951
2 3/8	5107	5107

8 5/8x10 1/2x16" Spang B.H.
Packer
7" x 8 5/8" x 15" Spec.
Orisk. B.H. Packer; 53
bags aquagol;
4 fibertex.
Line pipe used as tubing.
bottom joint welded.
Port. top bot
5046 5054
5099 5105

Yellow Clay	0	10	Sandy Lime	1477	1492
Red Rock	10	60	Sand <i>sil sand</i>	1492	1865
Blue Shale	60	90	Big Lime <i>3340</i>	1865	1945
Lime	90	100	White Slate	1945	1948
Blue Slate	100	110	Injun Sand	1948	1968
Red Rock	110	120	Slate	1968	1970
Lime	120	125	Sand	1970	1975
Red Rock	125	155	Sandy Lime	1975	2008
Gray Shale	155	180	Slate	2008	2015
Red Rock	180	220	Sandy Lime	2015	2045
White Slate	220	255	Lime	2045	2055
Red Rock	255	345	Slate	2055	2140
Sand	345	375	Lime	2140	2155
White Slate	375	420	Shale	2155	2165
Sand	420	425	Lime	2165	2175
White Slate	425	430	Shale	2175	2410
Red Rock	430	440	Dark Shale <i>upper</i>	2410	2428
White Slate	440	485	Berea Grit	2428	2440
Lime Rotten	485	510	White Slate & Shells	2440	2850
Lime	510	530	White Slate	2850	3140
White Slate	530	535	Dark Slate	3140	3280
Red Rock	535	540	Slate & Shells	3280	3310
White Slate	540	575	Dark Slate	3310	3660
Red Rock	575	580	Brown Shale <i>44</i>	3660	3725
White Slate	580	590	White Slate & Shells	3725	3900
Lime	590	600	Dark Slate	3900	4020
Red Rock	600	622	Brown Shale	4020	4080
Lime	622	630	White Slate	4080	4110
Red Rock	630	640	Dark Shale	4110	4190
Lime	640	647	Brown Shale	4190	4250
Pink Rock	647	687	White Slate	4250	4645
White Slate	687	697	Dark Slate	4645	4670
Lime	697	715	Brown Shale	4670	4931
White Slate	715	730	Corniferous Lime <i>402</i>	4931	5040
Lime	730	760	Oriskany	5040	5085
Sand	760	780	Lime	5085	5096
Pink Rock	780	790	Sand <i>Held</i>	5096	5113
Gray Shale	790	835	Lime	5113	5120
Lime	835	845	Show oil 1230; Show gas 2428 no test		
White Slate	845	855	TOTAL DEPTH <i>485</i>		5113 SLM
Black Slate	855	865	5120-5113 SLM 7' correction not made.		
White Slate	865	874	GAUGES IN ORISKANY B.S.		
Lime	874	900	5040-41 133M		
White Slate	900	945	Shut down testing casing & pulling 8"		
Sand	945	1035	5042 424 M A.S. GAUGES IN ORISKANY		
White Slate	1035	1050	5043 948 M Gauge B.S. 520 M		
Sand	1050	1075	5044 1724 M 5 Mins A.S. 5130 M		
White Slate	1075	1120	5048 1889 M 10 Mins A.S. 4927 M		
Black Slate	1120	1220	5050 1724 M 15 Mins A.S. 4720 M		
Sand	1220	1330	5055 1390 M 20 Mins. A.S. 4720 M		
Black Slate	1330	1340	5065-75 771 M		
Sand	1340	1390	5085-5113 545 M		
Sandy Shale	1390	1410			
Sand	1410	1447			
Black Slate	1447	1477			