



New Location ✕
 Drill Deeper
 Abandonment

0.95 W.
 3.73 S.

Company GODFREY L. CARPENT. INC.
 Address 600 Union Bldg CHARLESTON WVA
 Farm J.L. McLean Hrs - (Helms 14 days et al)
 Tract _____ Acres 9.84 Lease No. 3-463
 Well (Farm) No. 3 Serial No. 933
 Elevation (Spirit Level) 684.04
 Quadrangle Kenna
 County Kanawha District Poca
 Engineer W.E. Fisher
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date June 12 1940 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-721

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan-721
Kenna Quad.

Gas Well

Company Godfrey L. Cabot, Inc.
Address Charleston, W. Va.
Farm J. L. McLean (Helen M. Hoge) ACRES @
Well No. 3 - Serial 939 - ELEV. 684.04
District Poca - Kanawha County
Surface & Mineral -
Commenced July 13, 1940
Completed Oct. 9, 1940
Shot 10/10/40 - depth 4807-4814 - 15 qts.
4830-4837 - 15 qts.
Open Flow 9/10ths - 7" (17#)
Volume 4,989,000 c.f.
Rock Pressure 1150 lbs. 22 hrs.
Water Fresh W. - hole full
Salt W. 1235 - water stand 200 ft.
from top of hole.

CASING & TUBING

13	59	59
10-3/4	410	410
	10-3/4 casing shoe	
8-5/8	1832	
	Casing shoe - 15 sacks	
	Aquagel	
7 OD	4730	4730
	Lead deep hole packer	
	7" O.D. - 50 sacks	
	Aquagel - 250# Fibrotex	
2	4859	4859

Gravel	0	12	Slate & Shells	2230	3441	
Blue Slate	12	16	Brown Shale	3441	3500	
Red Rock	16	21	White Slate	3500	3510	
Sand	21	35	Lime	3510	3570	
Red Rock	35	52	Slate & Shells	3570	3698	
Blue Slate	52	59	Brown Shale	3698	3995	
Red Rock	59	90	Slate	3995	4435	
Slate	90	100	Brown Shale	4435	4660	
Red Rock	100	110	- Black Shale	4660	4709	
Slate	110	120	- Corniferous	4709	4806	S.L. 4806
Sand	120	140	HFV - fresh			Gas 4807
Red Rock	140	155	- Oriskany Sand	4806	4848	S.L. 4808
Slate	155	165	- Lime	4848	4859	S.L. 4859
Red Rock	165	190	Total Depth		4859	
Slate	190	197				
Lime	197	200				
Sand	200	225				
Red Rock	225	239				
Slate	239	285				
Red Rock	285	300				
Slate	300	328				
Sand	328	335				
Slate	335	358				
Sand	358	370				
Red Rock	370	385				
Slate & Shells	385	417				
Sand	417	483				
Slate & Shells	483	505				
Sand	505	572				
Slate	572	745				
Sand	745	793				
Slate & Shells	793	862				
- Coal	862	867				
Slate & Shells	867	1080				
Sand	1080	1113				
Slate	1113	1157				
- Salt Sand	1157	1557	SW 1235			
Slate	1557	1558				
- Lime	1558	1585				
- Slate	1585	1595				
- Big Lime	1595	1756				
- Injun Sand	1756	1798				
Black Slate	1798	1801				
Black Lime	1801	1845				
Slate & Shells	1845	2210				
- Brown Shale	2210	2215				
- Berea Sand	2215	2230				

GAUGES IN ORISKANY SAND:

4808	367 M
4813	1400 M
4828	1075 M
4834	2252 M
4835	2300 M
4836	2400 M
4839	2252 M
4841	2015 M
4846	1963 M
4847	1963 M
4853	1912 M
4858	1858 M