



New Location
 Drill Deeper
 Abandonment

LOC. 19 M. N.E. OF BLUNDON

Company COLUMBIAN CARBON CO.
 Address BOX 1240 - CHARLESTON - W. VA.
 Farm E. L. TAYLOR ET AL
 Tract _____ Acres 83 Lease No. CT-72
 Well (Farm) No. ONE Serial No. _____
 Elevation (Spirit Level) 809.1
 Quadrangle KENNA S.E. -7-
 County KANAWHA District POCA
 Engineer James R. Sell
 Engineer's Registration No. 772
 File No. _____ Drawing No. 366
 Date SEPT. 6, 1941 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-855

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

Deep well ✓

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Kan-355		Gas Well
Company	Columbian Carbon Co.	CASING & TUBING
Address	Box 1240, Charleston, W.Va.	16 26 26
Farm	E.L. Taylor et al Acres 83	13 3/8 513'7 Pulled
Location	Goose Creek	8 5/8 1822' 1822'
Well No	1 (GW-612) Elev. 814.4DF	7 5051'5 5051'5
District	Poca Kanawha County	2 3/8 5222'11 5222'11
Surface	E.L. Taylor, Elkview, W.Va.	3 1/2 87'3 87'3
Mineral	Same	
Commenced	11-12-41	
Completed	2-17-42	
Shot	2-18-42 Depth 5128SLM to 200# Gelatin 5158' SLM	
Volume	2499MCF	
Rock Pressure	1270 lbs. 6 days	
Oil	1163' show 1253' show	
Fresh Water	175' 1-16" blrs.; 363' 1-16"blr. pr. hr.; 720' 1-13" blr. pr. hr. 1240-65 Hole Full	

Surface	0	12	CEMENT RECORD:
Red Rock	12	20	11-19-41 Aquagelled 13 3/8"
Blue Slate	20	60	casing. Ran 12 sacks aquagel
Sand	60	90	6% and 1 sack Fibrotex.
Red Rock	90	160	
White Slate	160	200	12-20-41 Cemented 8 5/8" casing
Red Rock	200	250	Ran 126 sacks Alpha cement
White Slate	250	300	mixed with 2 sacks Aquagel.
Red Rock	300	345	Ran plug on top cement. 11'
White Slate	345	350	cement in hole.
Sand	350	368	
Slate	368	380	2-3-42 Cemented 7" casing.
Red Rock	380	400	Ran 10 sacks Alpha cement in
White Slate	400	475	dump bailer. 45' cement in
Red Rock	475	495	pipe.
Slate & Shells	495	508	
Sand	508	660	
Slate	660	661	
Sand	661	700	
Slate	700	720	
Sand	720	730	
Slate Shells	730	840	
Sand	840	940	
Slate Shells	940	1020	
Sand	1020	1030	
Slate & Shells	1030	1098	
Sand	1098	1120	
Slate	1120	1135	
Salt Sand	1135	1205	Oil 1163 small show
Slate	1205	1215	Show gas 1312
Salt Sand	1215	1418	
Slate	1418	1440	Oil Show 1253
Sand - <i>maister</i>	1440	1560	
L Lime	1560	1590	
Slate - <i>P. cave</i>	1590	1600	
Big Limo	1600	1758	Gas 1655 blow out
Big Injun Sand	1758	1780	
Slate & Shells	1780	3680	
Brown Shale	3680	3730	Gas 3710 Small show
White Slate	3730	3900	
Brown Shale	3900	4020	
White Slate	4020	4550	
Brown Shale	4550	4860	
White Slate	4860	4895	
Brown Shale	4895	4962	DLM (4962'DLM- 5008SLM)
Corniferous Lime	SLM 5008	5118	SLM
Oriskany Sand	SLM 5118	5159	
Lime	5159	5165	
Oriskany Sand	5165	5203	
Lime	5203	5209	SLM
TOTAL DEPTH		5209	SLM Pay 5151-52