



4
1
3
2
8
2
11

New Location +
 Drill Deeper
 Abandonment

Company GODFREY L CABOT INC
 Address 900 UNION BLDG CHARLESTON WVA
 Farm THE PUTNAM CO
pt of 22,000 AC
 Tract _____ Acres _____ Lease No. 3-464
 Well (Farm) No. 26 Serial No. 998
 Elevation (Spirit Level) 990.86 818.75-75 to 80
 Quadrangle KENNA SW
 County KANAWHA District POCA
 Engineer _____
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date Sept. 4 1940 Scale 1"=1320

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-857

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

Deep Well

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Not same well as on map? Perhaps

Permit No. Kan 857
Company
Address
Farm
Location
District
Well No.
Surface
Commenced
Completed
Shot
Volume
Rock Pressure
Salt Water

Godfrey L. Cabot, Inc.
Charleston, W.Va.
DeHolmes Morton Acres--
Poca Kanawha County
9 Ser 998 Elev. 818.75
March 28, 1942
June 22, 1942
6-24-42 Depth 5013-5033, 40 qts.
1279 MCF A.S.; (1 hr. A.S.) B.S. 484 M
1575 lbs. 16 hrs. Oriskany
1426; Hole Full 1452'

Gas Well
CASING & TUBING
10 1/2 892 892
8 5/8 2017 2017
7" 4940 4940
2 3/8 5079 5079
10 1/2 half collar shoe
28 bags aquagel
1-8 5/8 #10 1/2 B.H. Spang
Packer #20138
7" B.H. Spang Packer
#20476; 40 bags
aquagel, 4 fibertex.
2 3/8 bottom joint
welded. Tubed under line
pressure.

Tubed and shut in 7-7-42
Perf. top bottom
5022 5030
5073 5079

Red Rock	0	10	Lime Shells	2671	2707
Lime	10	42	Lime	2707	2738
No Record	42	70	Shale	2738	2775
Shale	70	156	Slate & Lime Shells	2775	2924
Lime	156	178	Shale	2924	2951
Shale	178	200	Slate & Shells	2951	3160
Lime	200	278	Shale	3160	3185
Shale	278	285	Slate & Shells	3185	3228
Red Rock	285	320	Shale	3228	3267
White Slate	320	335	Slate & Shells	3267	3391
Red Rock	335	360	Shells	3391	3428
Lime	360	372	Slate & Lime Shells	3428	3558
Red Rock	372	388	Shale	3558	3585
Shale	388	392	Slate & Shells	3585	3636
Red Rock	392	410	Shale	3636	3643
Lime	410	430	Gritty Lime, Black	3643	3675
White Slate	430	440	Brown Shale & Shells	3675	3705
Lime	440	528	Shale & Slate, Dark	3705	3755
Shale, Gray	528	550	Shale & Shells, Wh	3755	3770
Lime, White	550	575	Lime	3770	3779
Slate	575	581	Shale & Shells Wh	3779	3871
Lime	581	625	Shale, dark	3871	3938
Shale, Gray	625	640	Shale & Shells Wh	3938	3974
Lime, Gray	640	656	Shale Dark Brown	3974	4212
Red Rock	656	670	Shale, white	4212	4626
Slate, White	670	707	Shale, brown	4626	4795
Lime	707	728	Shale, White	4795	4845
Shale	728	740	Shale, Brown	4845	4899
Lime	740	759	Slate, black	4899	4919
Sand	759	795	Lime - <i>See above</i>	4919	5012
Shale	795	815	Sand	5012	5053
Gritty Lime	815	870	Lime	5053	5063
Slate & Shells	870	954	Sand	5063	5085
Shale, gray	954	960	Lime	5085	5087 SL
Lime, blue	960	985	TOTAL DEPTH		5087
Slate, Black	985	996	Show oil 1285-90 ; gas 3065-70; Gas		
Gritty Lime	996	1060	3646, shale gas 95 M		A.S.
Slate, Black	1060	1095	GAUGES IN ORISKANY B.S. Gauges Orisk.		
Slate & Lime, Gray	1095	1137	5014 show	Gauge B.S.	484 M
Sand	1137	1203	5018 189 M	5 Mins. A.S.	1767 M
Slate	1203	1280	5022 280 M	10 " "	1590 M
Sand, White	1280	1357	5024 327 M	15 " "	1443 M
Slate, Black	1357	1375	5026 270 M	20 " "	1390 M
Sand, White	1375	1795	5027 310 M	60 " "	1279 M
Big Lime, White	1795	1978	5028 315 M		
Sand, white	1978	1980	5032-40 561 M		
Black Shale	1980	1983	5045-50 553 M		
Sand, white	1983	2004	5059 520 M		
Shale	2004	2020	5080-87 465 M		
Lime	2020	2046			
Slate & Shells	2046	2425			
Sand	2425	2450			
Shale	2450	2484			
Shale & Shell	2484	2610			
Shale	2610	2671			