



New Location +
Drill Deeper
Abandonment

0.415
3.070

Company GODFREY, L. CABOT, INC.
 Address 900 UNION BLDG. CHARLESTON WVA
 Farm POCA COAL LAND CO.
PT. OF 4850 AC.
 Tract _____ Acres _____ Lease No. 3-466
 Well Farm No. 7 Serial No. 1024
 Elevation (Spirit Level) 867.52
 Quadrangle KENNA
 County KANAWHA District POCA
 Engineer Roy Boston
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date 1-21-41 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-896

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

✓

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

| | | |
|--------------------|-----------------------------------|----------------------------|
| Permit No. Kan 896 | | Gas Well |
| Company | Godfrey L. Cabot, Inc. | CASING & TUBING |
| Address | Charleston, W. Va. | 1 3/8 407 407 |
| Farm | Poca Coal Land Co. Acres --- | 10 1/2 848 848 |
| Location | --- | 8 5/8 2075 -- |
| Well No | 7 Scr. 1024 Elev. 867.52 | 7 4947 4947 |
| District | Poca Kanawha County | 2 3/8 5094 5094 |
| Surface | --- | |
| Mineral | --- | (13 3/8) 1/2 coupling shoe |
| Commenced | Jan 31, 1942 | 1/2 coupling shoe |
| Completed | May 5, 1942 | B. H. Packer, 25 sacks |
| Shot | 5020-5043, 40 qts., on 5-6-42 | aquagel. |
| Volume | 5130 MCF A.S. (20 Min) B.S. 862 M | 7" O.D. Spec. Oriskany |
| Rock Pressure | 1550 lbs. 54 hrs. Oriskany | Packer; 40 sacks |
| Fresh Water | 896 1/2 blrs. pr. hr. | aquagel; 4 sacks |
| Salt Water | 1155 1 blr. pr. hr; 1555 H.F. | fibertex |
| | Level 325' | Bottom joint welded. |
| | | Line pipe as tubing |
| | | Perf. top Bot |
| | | 5028 5032 |
| | Tubed and shut in 5-14-42 | 5038 5092 |

| | | | | |
|----------------|-----------|-----------------------------------|-------|---------|
| Surface | 10 | Sand | 1230 | 1260 |
| Red Rock | 10 40 | Slate & Shells | 1260 | 1420 |
| Slate | 40 60 | Sand | 1420 | 1445 |
| Red Rock | 60 90 | Slate | 1445 | 1470 |
| Slate | 90 110 | Salt Sand | 1470 | 1815 |
| Red Rock | 110 130 | Little Lime | 1815 | 1830 |
| Slate | 130 145 | Slate | 1830 | 1835 |
| Red Rock | 145 180 | Big Lime | 1835 | 2007 |
| Lime | 180 200 | Big Injun | 2007 | 2025 |
| Slate | 200 210 | Slate | 2025 | 2029 |
| Red Rock | 210 235 | Sand | 2029 | 2044 |
| Slate | 235 265 | Slate & Shells | 2044 | 2479 |
| Red Rock | 265 308 | Dorea | 2479 | 2497 |
| Sand | 308 338 | Slate & Shells | 2497 | 3710 |
| Red Rock | 338 385 | Shale | 3710 | 3750 |
| Slate | 385 395 | Slate & Shells | 3750 | 3970 |
| Lime | 395 409 | Brown Shale | 3970 | 4020 |
| Red Rock | 409 414 | Slate & Shells | 4020 | 4123 |
| Black Sand | 414 420 | Brown Shale | 4123 | 4265 |
| Slate | 420 430 | White Slate | 4265 | 4685 |
| Red Rock | 430 468 | Brown Shale | 4685 | 4926 |
| Lime | 468 480 | Corniferous | 4926 | 5014 |
| Slate | 480 490 | Oriskany | 5014 | 5052 SL |
| Red Rock | 490 510 | Lime | 5052 | 5062 |
| Slate | 510 525 | Sand | 5062 | 5082 |
| Red Rock | 525 553 | Lime | 5082 | 5105 SL |
| Sand | 553 578 | Best gauge natural Oriskany | 5022- | |
| Slate & Shells | 578 722 | 5026, init. prod. 2929 MCF; 5031- | | |
| Red Rock | 722 730 | 5032; 5041 to 5043 | | |
| Slate & Shells | 730 742 | Show gas 2490; gas 5012-14 2929M | | |
| Pink Rock | 742 752 | GAUGES IN ORISKANY SAND | | |
| Lime | 752 766 | 5022-24 2929M | | |
| Slate | 766 777 | Shut down to test casing. | | |
| Lime | 777 783 | 5024 1220 M | | |
| Pink Rock | 783 806 | 5025 1336 M | | |
| Slate | 806 840 | 5026 1543 M | | |
| Sand | 840 920 | 5026 1443 M | | |
| Slate | 920 970 | 5029 1090 M | | |
| Sand | 970 988 | 5031 945 M | | |
| Slate | 988 996 | 5032 1220 M | | |
| Sand | 996 1015 | 5035-5041 1220 M | | |
| Slate | 1015 1030 | 5043 1543 M | | |
| Sand | 1030 1050 | 5045 1443 M | | |
| Slate | 1050 1070 | 5049 1336 M | | |
| Sand | 1070 1137 | 5064 1220 M | | |
| Slate | 1137 1144 | 5070 1157 M | | |
| Sand | 1144 1175 | 5080 1090 M | | |
| Slate | 1175 1185 | 5093-5105 1090 M | | |
| Sand | 1185 1210 | GAUGES IN ORISKANY AFTER SHOT | | |
| Slate | 1210 1230 | Gauge B.S. 862 M 10 M.A.S. 5130M | | |
| | | 5 Mins A.S. 5692 M 15 " " 5130M | | |
| | | 20 " " 5130 M | | |