



Poca District, Kanawha County, W. Va.  
 By Poca Fork Oil & Gas Co., Clendenin, W. Va.  
 @bandoned under permit Kan-.....-A?

On.....acres.

Elevation.....' L.

Drilling completed in 1927.

7" O. D. casing, 1805'.

Gas well. Record to Dept. of Mines stamped May 8, 1948.

Record to RCT from Mrs. Griffith June 18, 1948. Old File No. 1282.

	Top.	Bottom.
Clay	0	9
Sand	9	69
Blue mud	69	100
Red rock	100	140
Black slate	140	175
Sand	175	200
Red rock	200	275
Slate	275	300
Red rock	300	370
Sand	370	400
Red rock	400	430
Lime	430	450
Slate	450	490
Sand	490	550
Slate	550	580
Sand	580	800
Black lime	800	860
Slate	860	930
Sand	930	1015
Slate	1015	1025
Lime	1025	1050
Slate	1050	1055
Sand	1055	1080
Slate	1080	1220
Gas Sand	1220	1280
Slate	1280	1300
Salt Sand	1300	1555
Slate	1555	1585
Lime	1585	1620
Sand	1620	1660
Slate	1660	1675
Lime	1675	1705
Maxton Sand	1705	1747
Little Lime	1747	1759
Slate	1759	1761
Lime and shell	1761	1766
Slate	1766	1768
Big Lime (gas pays, 1813-1815, 1842-1848, and 1877')	1768	....
Total depth		1878



*Completed no inspection  
made information 6-4-48*

1252

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. KAN - 502-A

Oil or Gas Well \_\_\_\_\_  
(KIND)

Company Poca Fork Oil & Gas Company  
Address Glendenin, W. Va.  
Farm J. A. Dodd Acres \_\_\_\_\_  
Location (waters) \_\_\_\_\_  
Well No. 1 Elev. \_\_\_\_\_  
District Poca County Kanawha  
The surface of tract is owned in fee by \_\_\_\_\_  
Address \_\_\_\_\_  
Mineral rights are owned by \_\_\_\_\_  
Address \_\_\_\_\_  
Drilling commenced \_\_\_\_\_  
Drilling completed 1927  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10			Size of
8 1/4			
6 5/8 7" OD		1805	Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom


CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

\_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Clay			0	9			
Sand			9	69			
Blue Mud			69	100			
Red Rock			100	140			
Black Slate			140	175			
Sand			175	200			
Red Rock			200	275			
Slate			275	300			
Red Rock			300	370			
Sand			370	400			
Red Rock			400	430			
Lime			430	450			
Slate			450	490			
Sand			490	550			
Slate			550	580			
Sand			580	800			
Black Lime			800	860			
Slate			860	930			
Sand			930	1015			
Slate			1015	1025			
Lime			1025	1050			
Slate			1050	1055			
Sand			1055	1080			
Slate			1080	1220			
Gas Sand			1220	1280			
Slate			1280	1300			
Salt Sand			1300	1555			
Slate			1555	1585			
Lime			1585	1620			
Sand			1620	1660			
Slate			1660	1675			
Lime			1675	1705			
Maxon Sand			1705	1747			
Little Lime			1747	1759			
Slate			1759	1761			
Lime & shell			1761	1766			
Slate			1766	1768			
Big Lime			1768				
Total Depth				1878			



Gas pays 1815-1815-1842-1848  
1877

(Over)

JUN 18 1948