



Company The Pure Oil Co.  
 Address Newark, Ohio  
 Farm Williams Coal Co.  
 Tract Acres 12000 Lease No. 5012  
 Well (Farm) No. 126 Serial No. 268  
 Elevation (Spirit Level) 1027  
 Quadrangle Montgomery **WC**  
 County Kanawha District Cabin Creek  
 Engineer J. B. Hunter  
 Engineer's Registration No. Ohio-2912  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date 9-14-48 Scale 1" = 200'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. KAN-557-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

6-5 247

WILLIAMS COAL CO. NO. 126 WELL.

557A

Cabin Creek District, Kanawha County, W. Va.  
 By The Pure Oil Co., Box 551, Newark, Ohio.  
 Abandoned under permit Kan-.....-A?  
 On 12,000 acres, on Cabin Creek.  
 Elevation, 1027' L.  
 Surface and minerals owned by Shonk Land Co., %D.C.Shonk, Dawes, W. Va.  
 Drilling commenced Oct. 15, 1918; completed Feb. 28, 1919.  
 Shot March 11, 1919, at 2680-2693', with 40 qts.  
 Oil, 6 bbls., 1st 24 hrs.  
 Fresh water at 75'.  
 Salt water at 1200'.  
 10" casing, 90' (99'); 8", 1360'; 6½", 2037' 8" (2047'?) + 2" tubing, 2720';  
 all left in.  
 Coal was encountered at 250-254, 334-340, and 390-394'.  
 Oil well. Abandonment reported to Dept. of Mines Nov. 3, 1948.  
 Record to RCT from Mrs. Griffith July 10, 1949. Old File No. 1395.

	Top.	Bottom.
Conductor	0	16
Sand, white (water, 75', 1 blr. per hr.)	16	115
Slate, black	115	250
Coal, black	250	254
Slate, black	254	280
Sand, white	280	334
Coal, black	334	340
Slate, black	340	350
Sand, white	350	390
Coal, black	390	394
Slate and lime, black	394	490
Sand, white	490	560
Slate, black	560	640
Sand, white	640	720
Slate, black	720	740
Sand, white	740	780
Lime, black	780	800
Sand, white	800	910
Big Dunkard Sand, dark	910	1010
Slate, black	1010	1080
Salt Sand, white (water, 1200', hole filled up 700')	1080	1355
Slate and lime, gray	1355	1527
Red rock	1527	1546
Sand, white	1546	1575
Red rock	1575	1590
Slate and lime, black	1590	1800
Maxton Sand, white	1800	1890
Slate and lime, black	1890	2005
Pencil, black	2005	2010
Big Lime, white (show of gas at 2160')	2010	2230
Big Injun Sand, red	2230	2260
Slate and lime, black	2260	2653
Shale, brown	2653	2661
Berea Sand, white (oil and gas pay, 2682-2694')	2661	2694
Total depth		2697



*Completed no inspection*

1395

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. 557-A

Oil or Gas Well Oil  
(KIND)

Company The Pure Oil Company  
Address Box 551 - Newark, Ohio  
Farm Williams Coal Company Acres 12,000  
Location (waters) Cabin Creek  
Well No. 126 Elev. 1027  
District Cabin Creek County Kanawha  
The surface of tract is owned in fee by Shonk Land Co.,  
Att: D.C. Shonk Address Dawes, W.Va.  
Mineral rights are owned by Shonk Land Co.,  
Att: D.C. Shonk Address Dawes, W.Va.

Drilling commenced 10-15-18  
Drilling completed 2-28-19  
Date Shot 3-11-19 From 2680 To 2693  
With 40 Qts.

Open Flow /10ths Water in \_\_\_\_\_ Inch  
/10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil 6 \_\_\_\_\_ bbls., 1st 24 hrs.  
Fresh water 75 \_\_\_\_\_ feet \_\_\_\_\_ feet  
Salt water 1200 \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	90'	95'	Size of
8 1/2	1360'	1360'	
6 5/8	2037' 8"	2047'	Depth set
5 3/16			
3			Perf. top
2		2720'	Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT 250 FEET 48 INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES 334 FEET 72 INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES 390 FEET 48 INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Conductor			0	16			
Sand	white		16	115	Water	75	1 bailer pr.hr.
Slate	black		115	250			
Coal	black		250	254			
Slate	black		254	280			
Sand	white		280	334			
Coal	black		334	340			
Slate	black		340	350			
Sand	white		350	390			
Coal	black		390	394			
Slate & Lime	black		394	490			
Sand	white		490	560			
Slate	black		560	640			
Sand	white		640	720			
Slate	black		720	740			
Sand	white		740	780			
Lime	black		780	800			
Sand	white		800	910			
BIG DUNKARD	dark		910	1010			
Slate	black		1010	1080			
SALT SAND	white		1080	1355	Water	1200	H.F. up 700'
Slate & Lime	gray		1355	1527			
Red Rock	red		1527	1546			
Sand	white		1546	1575			
Red Rock	red		1575	1590			
Slate & Lime	black		1590	1800			
MAXON SAND	white		1800	1890			
Slate & Lime	black		1890	2005			
Pencil	black		2005	2010			
BIG LIME	white		2010	2230			
BIG INJUN	red		2230	2260			
Slate & Lime	black		2260	2653			
Shale	brown		2653	2661			
BEREA SAND	white		2661	2694			
PAY SAND				2697	TOTAL DEPTH		
2682 - 2694	Oil and Gas-1st Pay						
Show of gas at 2160							



