



New Location...
 Drill Deeper.....
 Abandonment.....

MAY 19 1953
 Stake which bears
 N57°W-15' from
 Stone.

Company PRESTON OIL CO.
 Address CHARLESTON W.VA.
 Farm PORTER & CRAWFORD
 Tract _____ Acres 1 1/2 + 1 1/2 Lease No. 27188
 Well (Farm) No. 1 Serial No. 3329
 Elevation (Spirit Level) 709.6'
 Quadrangle MONTGOMERY
 County KANAWHA District CABIN CREEK
 Engineer Seybert Shull
 Engineer's Registration No. 2529
 File No. 70-43 Drawing No. _____
 Date 5-1-53 Scale 1" = 100'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. KAN-1002-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

PORTER & CRAWFORD NO. 1 (3329) - PRESTON OIL CO. - KAN-1002-A

70070
O.F. Man-1014.

PORTER & CRAWFORD NO. 1 (S18) WELL.

now 1002-A

Cabin Creek District, Kanawha County, W. Va.
 By The Ohio Fuel Oil Co. (Virginian Gasoline & Oil Co.)
 On lease No. 1932P1935; 4 acres.
 Drilling contractor, G. L. Titus, Huntington, W. Va.
 Cost per foot, \$1.60.
 Commenced Jan. 1, 1917; completed March 17, 1917.
 12 $\frac{1}{2}$ " casing, 38'; 10", 505'; 8", 1151' (263' left in); 6", 1812'.
 Shot March 22, 1917, with 90 qts.
 Oil, pumped 25 bbls., 1st 24 hrs.

	Top.	Bottom.	Thickness..
Conductor	0	- 16	16
Sand (12 $\frac{1}{2}$ " casing, 38') (hole full water)	38	- 58	20
Coal	58	- 63	5
Sand	63	- 100	37
Slate	100	- 135	35
Sand	135	- 145	10
Slate	145	- 175	30
Sandy lime	175	- 195	20
Slate	195	- 210	15
Lime	210	- 220	10
Slate	220	- 230	10
Sandy lime	230	- 260	30
Slate	260	- 355	95
Sand	335	- 365	10
Slate	365	- 375	10
Lime	375	- 430	55
Slate	430	- 435	5
Lime	435	- 450	15
Slate	450	- 465	15
Lime	465	- 485	20
Slate	485	- 500	15
Sandy lime	500	- 650	150
Gramphis Sand	650	- 760	100
Slate	750	- 810	60
Salt Sand (hole full water, 875')	810	- 1100	290
Slate	1100	- 1140	30
Lime	1140	- 1200	60
Slate	1200	- 1210	10
Lime	1210	- 1240	30
Slate	1240	- 1255	15
Red rock	1255	- 1265	15
Shells	1265	- 1290	25
Red rock	1290	- 1315	25
Shells	1315	- 1325	10
Red rock	1325	- 1370	45
Shells	1370	- 1560	190
Maxton Sand (1 bailer water at hour at 1610')	1560	- 1660	100
Lime	1660	- 1700	40
Slate	1700	- 1715	15
Little Lime	1715	- 1750	35
Pencil Clay	1750	- 1755	5
Big Lime (gas at 1920')	1755	- 1970	215
Big Injun Sand	1970	- 2010	40
Shells	2010	- 2240	230
Slate	2240	- 2355	115
Shells	2355	- 2414	29
Berea Grit (oil at 2435')	2414	- 2441	30
Total depth		2447	