



I, the undersigned, hereby certify that this map is correct to the best of my knowledge and belief and shows all the information required by paragraph 6 of the rules and regulations of the oil and gas section of the mining laws of West Virginia.

Sybert A. Jewell

- New Location
- Drill Deeper
- Abandonment

Company THE PRESTON OIL CO.
 Address CHARLESTON, W. VA.
 Farm IMPERIAL COAL CO.
 Tract _____ Acres 5400 Lease No. 2975
 Well (Farm) No. _____ Serial No. 1032
 Elevation (Spirit Level) 1283.27'
 Quadrangle MONTGOMERY - NW
 County KANAWHA District CABIN CRK
 Engineer Sybert A. Jewell
 Engineer's Registration No. 2529
 File No. 72-45 Drawing No. _____
 Date SEPT. 30, 1964 Scale 1" = 800

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION
CHARLESTON

WELL LOCATION MAP
FILE NO. KAN-1355-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

6-0 240

1355A

Cabin Creek District, Kanawha County, W. Va.
 By United Fuel Gas Co.
 Drilling contractor, Drilling Dept.
 Commenced Dec. 6, 1918; completed Mar. 31, 1919.
 Drillers: C. E. Murray, C. M. Woodwill.
 10" casing, 565'; 8 $\frac{1}{4}$ " , 1719' (pulled); 6 $\frac{5}{8}$ " , 2356'.
 Shot April 17, 1919, with 60 qts.
 Steel-line measurements at 1705, 2333, 2986, and 3023'.
 Oil well.

	Top.	Bottom.	Thickness.
Slate	0	- 177	177
Coal	177	- 183	6
Sand	183	- 220	27
Slate	220	- 260	40
Sand	260	- 335	75
Slate	335	- 420	85
Lime	420	- 445	25
Coal	445	- 447	2
Slate	447	- 477	30
Sand	477	- 516	39
Coal	516	- 520	4
Sand	520	- 560	40
Slate	560	- 800	240
Sand	800	- 860	60
Slate and shells	860	- 1230	370
Grampus Sand (hole full water, 1345')	1230	- 1370	140
Slate and shells	1370	- 1400	30
Salt Sand ←	1400	- 1565	165
Slate	1565	- 1585	20
Salt Sand	1585	- 1680	95
Slate	1680	- 1705	25
Lime	1705	- 1725	20
Slate and shells	1725	- 1881	156
Red rock	1881	- 1905	24
Lime	1905	- 1930	25
Red rock	1930	- 2040	110
Sand	2040	- 2060	20
Red rock	2060	- 2080	20
Lime shells and slate	2080	- 2160	80
Maxton Sand	2160	- 2232	72
Black lime	2232	- 2265	33
Slate	2265	- 2305	40
Little Lime	2305	- 2322	17
Pencil Cave	2322	- 2327	5
Big Lime	2327	- 2532	205
Big Injun Sand	2532	- 2580	48
Slate	2580	- 2690	110
Weir Sand	2690	- 2725	35
Slate and shells	2725	- 2986	261
Berea Sand	2986	- 3021	35
Total depth		3023	
Revised record:			
Top Big Lime	2327		
Berea Sand (oil pay sand, 3006-3021')	2986	- 3021	35
Total depth		3023	

KAN-1355-A

WELL RECORD

996

UNITED FUEL GAS

COMPANY

SERIAL WELL NO. 1032

MAP SQUARE

NAME Imperial Coal Company

WELL NO. 1032-27 LEASE NO. _____ ACRES _____

TOWNSHIP OR DISTRICT Cabin Creek

COUNTY Kanawha

FIELD _____

STATE W. Va.

RIG _____ Building Cost _____

Contractor _____

Commenced _____ 19____, Completed _____ 19____

DRILLING Cost per Ft. _____

Contractor Drilling Dept.

Address _____

Commenced Dec. 6 19 18 Completed Mar. 31 1919

DRILLERS TOOL DRESSERS

C. E. Murray _____

C. M. Goodwill _____

CASING AND TUBING		
SIZE	USED IN DRILLING	LEFT IN WELL
16		
13		
10	565	565
8 1/4	1719	None
6 5/8	2356	2356
5 3/16		
4 7/8		
4		
3		
2		

WELL TUBED

Date _____

_____ in. Tubing or Casing

Size of Packer _____

Kind of Packer _____

1st Perf. Set _____ from _____

2nd Perf. Set _____ from _____

TEST BEFORE SHOT

_____ of Water in _____ inch

10ths. _____ of Merc. in _____ inch

10ths. Volume _____ Cu. Ft.

TEST AFTER SHOT

_____ of Water in _____ inch

10ths. _____ of Merc. in _____ inch

10ths. Volume _____ Cu. Ft.

Rock Pressure _____

Date Shot 4-17-19

Size of Torpedo 60 Qts.

Oil Flowed _____ bbls. 1st 24 hours

Oil Pumped _____ bbls. 1st 24 hours

Well Abandoned and Plugged _____ 19____

DRILLER'S RECORD

FORMATION	TOP	BOTTOM	THICKNESS	REMARKS
Slate		177	.177	Slate & Shells 2725 2986 261
Coal	177	182	6	Berea Sand 2986 3021 35
Sand	183	220	27	
Slate	220	260	40	Total Depth 3023
Sand	260	335	75	
Slate	335	420	85	
Lime	420	445	25	Revised Record
Coal	445	447	2	
Slate	447	477	30	
Sand	477	516	39	Top Big Lime 2327
Coal	516	520	4	Berea Sand 2986 3021 - 35
Sand	520	560	40	Oil Pay Sand 3006 3021 - 15
Slate	560	800	240	Total Depth 3023
Sand	800	860	60	
Slate & Shells	860	1230	370	
Crampus	1230	1370	140	
Slate & Shells	1370	1400	30	Hole full water 1345
Salt Sand	1400	1565	165	
Slate	1565	1585	20	
Salt Sand	1585	1680	95	Steel Line Measurements
Slate	1680	1705	25	1705 2333 2986 3023
Lime	1705	1725	20	
Slate & Shells	1725	1881	156	
Red Rock	1881	1905	24	
Lime	1905	1930	25	
Red Rock 3	1930	2040	110	
Sand	2040	2060	20	
Red Rock	2060	2080	20	
Lime Shells & Slate	2080	2160	80	
Maxon Sand	2160	2232	72	
Black Lime	2232	2265	33	
Slate	2265	2305	40	
Little Lime	2305	2322	17	
Pencil Cave	2322	2327	5	
Big Lime	2327	2532	205	
Injun Sand	2532	2580	48	
Slate	2580	2690	110	
Weir Sand	2690	2725	35	