

38° 10' 00"

LATITUDE

81° 25' 00"

LONGITUDE

1.1 n S  
1.38 W

LONGITUDE

Taken from  
Equitable Resource's  
Property Map  
of 1929

T'S OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
\_\_\_\_\_ (calc.) \_\_\_\_\_

Company United Fuel Gas Co  
Farm Imperial Coal Co #2 (193)  
SECTION N2P  
Quad Cedar Grove  
County Kanawha  
District Cabin Creek

WELL LOCATION MAP  
File No. 039-70043

still producing 10-5-66

IMPERIAL COAL CO. NO. 2 (763) WELL.

70043  
O.F. - Kan-973...  
OLD FILE -  
not a part of  
~~Kan-1560~~

Cabin Creek District, Kanawha County, W. Va.  
By United Fuel Gas Co., Charleston, W. Va.  
Drilling contractor: W. B. Heeter.  
Commenced May 29, 1916. Completed Sept. 20, 1916.  
Drillers: Red Heeter, Ferd Hall.  
10" casing, 744'; 8 1/2", 1784' 4"; 6 3/8", 2431' 6"; all left in.  
Shot Sept. 22, 1916, with 110 qts.

	Top.	Bottom.	Thickness.	
Sand	0	100	100	
Slate	100	140	40	
Coal	140	146	6	
Slate	146	186	40	
Sand	186	206	20	
Slate and lime	206	255	49	
Coal	255	265	10	
Slate	265	345	80	
Sand	345	418	73	
Slate	418	430	12	
Coal	430	435	5	
Sand	435	470	35	
Slate	470	500	30	
Sand	500	550	50	
Slate	550	589	39	
Coal	589	594	5	
Slate	594	630	36	
Lime and sand	630	660	30	
Slate	660	691	31	
Coal	691	695	4	
Sand	695	730	35	
Slate and lime	730	954	224	
Sand	954	1030	76	
Slate and shells	1030	1070	40	
Sand	1070	1230	160	
Slate	1230	1265	35	?
Sand	1265	1375	110	?
Slate	1375	1450	75	
Salt Sand (water at 1510') (hole full water at 1605')	1450	1643	193	
Slate	1643	1672	29	
Sand	1672	1742	70	
Slate and shells	1742	1770	28	
Sand	1770	1781	11	
Red rock and lime	1781	2085	304	
Lime shells	2085	2208	123	
Maxton Sand (water at 2250')	2208	2278	70	
Little Lime	2278	2389	111	
Pencil Cave	2389	2390	1	
Big Lime	2390	2619	229	
Red rock	2619	2662	43	
Lime shells	2662	3009	347	
Berea Sand (show of oil, 3030-3040')	3009	3042	33	
Black lime	3042	3054	12	
Total depth		3054		

## IMPERIAL COAL CO. NO. 2 (763) WELL.

Cabin Creek District, Kanawha County, W. Va.

By United Fuel Gas Co., Charleston, W. Va.

Drilling contractor: W. B. Heeter.

Commenced May 29, 1916. Completed Sept. 20, 1916.

Drillers: Red Heeter, Ferd Hall.

10" casing, # 744'; 8<sup>1</sup>/<sub>2</sub>" 1784' 4"; 6<sup>5</sup>/<sub>8</sub>" 2431' 6"; all left in.

Shot Sept. 22, 1916, with 110 qts.

	Top.	Bottom.	Thickness.	
Sand	0	- 100	100	
Slate	100	- 140	40	
Coal	140	- 146	6	
Slate	146	- 186	40	
Sand	186	- 206	20	
Slate and lime	206	- 255	49	
Coal	255	- 265	10	
Slate	265	- 345	80	
Sand	345	- 418	73	
Slate	418	- 430	12	
Coal	430	- 435	5	
Sand	435	- 470	35	
Slate	470	- 500	30	
Sand	500	- 550	50	
Slate	550	- 589	39	
Coal	589	- 594	5	
Slate	594	- 630	36	
Lime and sand	630	- 660	30	
Slate	660	- 691	31	
Coal	691	- 695	4	
Sand	695	- 730	35	
Slate and lime	730	- 954	224	
Sand	954	- 1030	76	
Slate and shells	1030	- 1070	40	
Sand	1070	- 1230	160	
Slate	1230	- 1265	35	?
Sand	1265	- 1375	110	?
Slate	1375	- 1450	75	
Salt Sand (water at 1510') (hole full water at 1605')	1450	- 1643	193	
Slate	1643	- 1672	29	
Sand	1672	- 1742	70	
Slate and shells	1742	- 1770	28	
Sand	1770	- 1781	11	
Red rock and lime	1781	- 2085	304	
Lime shells	2085	- 2208	123	
Maxton Sand (water at 2250')	2208	- 2278	70	
Little Lime	2278	- 2389	111	
Pencil Cave	2389	- 2390	1	
Big Lime	2390	- 2619	229	
Red rock	2619	- 2662	43	
Lime shells	2662	- 3009	347	
Berea Sand (show of oil, 3030-3040')	3009	- 3042	33	
Black lime	3042	- 3054	12	
Total depth		3054		