LATITUDE 38°25' 6,245 224W

7'5 OG15 topo location
7.5' loc _____ 15' loc _____ (calc.)

Company Oconnell Opall Co
Farm Goshorn 19

Quad Clendenin 15'
County Kamanha

District Big Sandy

WELL LOCATION MAP

File No. 40706 70734

737 1914 WUGES

Kanawha County

Report

Goshorn No. 20 Well Record (712).

Located in Elk district on divide between waters of Falling Rock Creek and Laurel Fork of Blue Creek, 2.3 miles east of Carpenter's station. Completed June 7, 1913. Authority, O'Connell Oil Company. Elevation 1230'.

	Thickness.	Total
	Feet.	Feet.
Unrecorded	480	480
Coal, Stockton-Lewiston	5	485
Unrecorded	745	1230
Salt sand	430	1660
Red rock	140	1800
Little Lime	35	1835
Pencil Cave	5	1840
Lime	15	1855
Pencil Cave	5	1860
Big Lime	160	2020
Slate	7	2027
Red rock	38	2065
Sand, Big Injun	35	2100
Sand and breaks of slate	110	2210
White sand, "Weir," oil	35	2245
Slate to bottom		2248
10" casing, 20 feet; 8" casing, 160 feet; 6%" (
first oil at 2231 feet; gas at 2237 feet; second oil a oil well."	at 2237-2241	feet;
· · · · · · · · · · · · · · · · ·		

Goshorn No. 19 Well Record (737).

Located in Elk district on divide between waters of Falling Rock Creek and Laurel Fork of Blue Creek, 3 miles northeast of Carpenter station. Completed May 19, 1913. Authority, O'Connell Oil Company. Elevation, 1130' B.

- •	Fhickness	Total
	Feet.	Feet.
Soil, black shale, and shells		1080
Salt sand		1325
Slate	15	1340
Lime	10	1350
Slate	10	1360
Hard, gritty lime	20	1380
Sand	100	1480
Lime	20	1500
Red rock	5	1505
Lime	60	1565
Slate	10	1575
Lime		1580
Red rock		1625
Slate and lime shells	50	1675
Hard sandy lime		1685
Slate and shells		1720
Little Lime	30	1750
Pencil Cave		1755
Lime		1785

	Thickness Feet.	Total Feet.
Pencil Cave	5	1790
Pencil Cave	155	1945
Big Lime	30	1975
Red rock and slate	55	2030
Red sand	5	2035
Red sand	30	2065
Hard white sand	45	2110
Sand and lime shells	65	2175
Sand. "Weir," oil	••••	

"10" casing, 17 feet; 8" casing, 800 feet; 65%" casing, 1789½ feet; half enough water to drill with at 100 feet; hole filled up with water in a rush at 1200 feet; gas at 1820 feet; first oil, 2148 feet; second oil, 2162 feet and 2165 feet."

Goshorn No. 17 Well Record (714).

Located in Elk district, on divide between waters of Falling Rock Creek and Laurel Fork of Blue Creek, 3 miles northeast of Carpenter station. Completed March, 1913. Elevation, 1070' B.

Thickness Total

Thickness	Totai
Feet.	Feet.
Unrecorded	18
- 18Z	200
Sand	270
Coal, Stockton	275
Sand 5	280
Coal, Stockton 5	285
Sand	305
Coal, Coalburg	310
Shells	500
Shells	580
White sand	700
Slate	725
Sand	1080
Shells	1500
Sair sand	1510
Slate	1570
ded rock	1625
lame shells	1645
Sand Maxion	1660
SIRLE	1685
THE TAILED TAILED AND A STATE OF THE PARTY O	1690
Pencil Cave	1865
Big Lime	1875
Slate 10	
Red rock	1910
Sand 90	2000
Slate 40	2040
Sand, "Weir," oil 40	2080
Slate to bottom 5	2085
"10" cosing 18 feet: 8" casing 720 feet: 65%" casing 170	feet:

ıI

85 20 50

55

"10" casing, 18 feet; 8" casing, 720 feet; 6%" casing, 1705 feet; water at 1150 feet and 1400 feet; "break" of 2 feet in Big Lime at 1700 feet; gas at 1850 feet; first oil, 2075 feet; gas at 2076 feet; sec ond oil, 2076-2080 feet; oil well."