

## Black Band Coal &amp; Coke Co. No. 1954 Well.

Loudon District, Kanawha County, W. Va.

By United Fuel Gas Co.

Kan-B on map.

Elevation, 921.29' L.

29 M. cu. ft. gas show, after shot (abandoned).

Located 0.38 mi. S. of 38° 15' and 0.65 mi. W. of 81° 35'—NC—Peytona

Quadrangle.

On southwestern branch of Rush Creek, (near head).

1.5 mi. W. of Marmet.

	Top.	Bottom.	Thickness.	Elevation (top)
Big Lime	1260	1468	208	— 339
Big Injun Sand	1468	1512	44	— 547
Berea Sand	1900±	1930±	30±	— 979±
Corniferous Lime	4588	4681±	93	—3667
Oriskany Sand	4681±	4689±	8	—3760

Thickness, Devonian Shales, 2658± feet. Total depth, 5225'. (Salina)

Thickness, Devonian Shales, 2658± feet. Total depth, 5225'. (Salina)

Remarks: Completed May 25, 1929. Shot at 4680-90', 4675-4685'.

Water, 865' (hole full). Water and show gas, 1189'. Gas and show

of oil, 1326'. Oil show, 1350'. Water, 1375' and 1443'. Gas show,

3800'.

Oriskany gas, 4681-89'.

Gas show, 5223'. Water, 5225'.

670831

## DEEP WELL

BLACK BAND COAL &amp; COKE CO. NO. 1954.

Kanawha Bl.

By United Fuel Gas Co. Completed, May 25, 1929.

Elevation, 921.29 (SPCCo.) Kanawha County, W. Va., Loudon Dist.

90831

	Top.	Bottom.
Surface	0	35
Sand	35	115
Slate and shells	115	170
Sand	170	220
Slate	220	255
Sand	255	360
Slate and shells	360	485
Sand	505	
Slate and shells	570	
Sand, First Salt	690	
Slate and shells	830	
Second Salt Sand	925	
(Water, 865'; hole full)		
Slate and shells	970	
Red rock	975	
Slate and shells	994	
Lime shells	1002	
Slate	1015	
Sand, Maxton	1080	
Red rock	1088	
Lime shells	1100	
Slate and shells	1182	
Slate	1187	
Little Lime	1240	
(Water, 1189'; 1 bailer per hr.; also show of gas)		
Pencil Cave	1240	1260
Big Lime	1260	1468
(Gas and show of oil, 1326; 16/10 W. in 2", 186 M.) (oil show, 1350'; water, 1375 and 1443'; 5 bailers per hr.)		
Big Injun Sand	1512	
Slate	1531	
Lime, broken	1600	
Slate and shells	1900	
Lime shells, gray	2200	
Slate and shells, gray	3420	
Slate, black	3430	
Shale, black	3690	
Lime, hard	3710	
Lime, broken (gas show, 3800')	3800	
Slate, gray	3900	
Lime, black	3920	
Slate, caved	3990	
Lime	4040	
Slate and lime, broken, caved	4115	
Slate, brown	4120	
Lime, broken, gray	4325	
Shale	4340	
Lime shells	4345	
Slate and shale, brown	4420	
Lime, black	4425	

1260  
921  
339Berea 1930 (+)1930  
921  
1009

## BLACK BAND COAL &amp; COKE COMPANY NO. 1954 (Continued).

	Top.	Bottom.
Shale, white . . . . .	4475	
Slate and lime, broken, black . . . . .	4480	
Slate and lime, broken . . . . .	4510	
Lime . . . . .	4520	
Shale . . . . .	4555	
Shale, brown, soft . . . . .	4588	(4558?)
Lime, Corniferous, gray . . . . .	4558	4720 (4588?)
Hard (gas, 4681-4689'; 8/10 W. in 1")		
Lime, Corniferous, dark . . . . .	4720	4754
" " gray . . . . .	4754	4820
" " dark . . . . .		4860
" " gray . . . . .		4890
" " black . . . . .		5010
" " gray . . . . .		5135
" " black, broken . . . . .		5140
" " hard . . . . .		5150
" " broken . . . . .		5155
" " hard . . . . .		5223
(gas show, 5223' - no test; water, 5225')		
Total depth . . . . .	5225	(Salina)
String of small tools left in.		
1st shot, 4680-4690' - 10 qts.		
2nd shot, 4675-4685' - 20 qts.		
Test before shot, 3/10 W. in 1".		
Test after shot, 6/10 W. in 1".		
Abandoned, 6/1/29.		

4588  
 193-  
 ✓628  
 3-  
 2658

4588  
 7-1  
 3667