



Company HOMER QUEEN DBA. QUEEN GAS COMPANY

Address BUCKHANNON, WVA.

Farm SOBISCA S. HALL

Tract LOT #5 Acres 29.78 Lease No. ONE

Well (Farm) No. THREE Serial No. \_\_\_\_\_

Elevation (Spirit Level) 1435'

Quadrangle WESTON - SC

County LEWIS District SKIN CREEK

Engineer PAUL G. DEAN

Engineer's Registration No. 1856

File No. 136-1-18 Drawing No. 62-16

Date 5-11-62 Scale 1"=500'

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION  
CHARLESTON

WELL LOCATION MAP  
FILE NO. Lew-1004

- + Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
- Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION 21

Quadrangle Weston

Permit No. LEW-1004

WELL RECORD

Oil or Gas Well Gas  
(REND)

Company Queen Gas Company  
Address P. O. Box 506, Buckhannon, W. Va.  
Farm Shirley J. & Eva Jane Craig Acres 29.78  
Location (waters) Stone Coal Creek  
Well No. Three (Hall # 3) Elev. 1435'  
District Skin Creek County Lewis  
The surface of tract is owned in fee by Shirley J. & Eva Jane Craig  
Address \_\_\_\_\_  
Mineral rights are owned by Sobiesca S. Hall, M. D.,  
132 S. 4th Street, Address Clarksburg, W. Va.  
Drilling commenced June 7, 1962  
Drilling completed October 14, 1962  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow 36/10ths Water in 5/3 Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume 13,371 Cu. Ft.  
Rock Pressure 1910 lbs. 20 (after frac.) hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED \_\_\_\_\_

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13	16'	00	gas anchor
10	400'	00	Size of <u>7x3 1/2</u>
8 1/4	1600'	00	
6 1/4	2775'	2775'	Depth set <u>2768</u>
5 3/16			
3			Perf. top <u>2751</u>
2			Perf. bottom <u>2771</u>
Liners Used			Perf. top _____
<u>4 1/2</u>	4761	4761	Perf. bottom _____

CASING CEMENTED 5 5/8 SIZE 2775 No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
55 sks. cement, 4 1/2 500' GARATON  
COAL WAS ENCOUNTERED AT 264 FEET \_\_\_\_\_ INCHES  
3 FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

WELL FRACTURED Dowell Company

RESULT AFTER TREATMENT 6,750,000 cu. ft.

ROCK PRESSURE AFTER TREATMENT 1910 #

Fresh Water none Feet \_\_\_\_\_ Salt Water none Feet \_\_\_\_\_

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Red Rock			0	30			
Grey Slate			30	41			
Red Rock			41	60			
Lime			60	120			
Slate & Shells			120	264			
Coal			264	267			
Lime			267	351			
Sand			351	380			
Slate & Shells			380	400			
Red Rock			400	460			
Shale			460	472			
Red Rock			472	525			
Sand		Hard	525	540			
Red Rock			540	618			
Sand		Hard	618	630			
Slate & Shells			630	645			
Red Rock			645	730			
Slate & Shells			730	800			
Lime			800	872			
Sand			872	970			
Sand & Lime		Hard	970	1117			
Sand	Brown		1117	1160			
Limey Sand			1160	1209			
Sand		Hard	1209	1331			
Shale	Dark		1331	1530			
Sand & Lalin		Hard	1530	1596			
Limey Sand		Hard	1596	1648			
Sand			1648	1690			
Red Rock			1690	1873			
Sand		Hard	1873	1973			



Formation	Color	Hard or Soft	Top <u>21</u>	Bottom	Oil, Gas or Water	Depth Found	Remarks
Little Lime			1973	1987			
Pencil Cave			1987	1990			
Lime			1990	2080	Gas	2073'	Showing
Sand			2080	2095			
Slate Break			2095	2099			
Sand			2099	2165			
Sand & Shale			2165	2240			
Sand			2240	2302			
Slate & Shells			2302	2319			
Sand <u>6 1/2</u>			2319	2404	Oil & Salt Water	2335'	2 bailers p. hr.
Slate & Shells			2404	2433		2343'	1 bailer p. hr.
Sand <u>3/4</u>		Hard	2433	2475			
Red Rock & Shells			2475	2542			
Sand <u>Gr. 05 1/2</u>			2542	2573			
Red Rock, Sand & Shells			2573	2614			
Sand <u>Gr. 2</u>			2614	2649			
Slate & Shells			2649	2682			
Sand <u>4 1/2</u>			2682	2697			
Slate & Shells			2697	2772			
Sand <u>5 1/2</u>			2772	2784	Gas	2774'	70/10 water 2"
Shale			2784	2900	Gas	2784'	plate.
Sand & Shells			2900	3250			60/10 water 2"
Limy Sand			3250	3290			plate.
Slate & Shells			3290	3335			
Sand			3335	3360			
Slate & Shells			3360	3608	Gas	3608'	4/10-3/8 water
Sand & Lime			3608	3940			
Slate & Shells			3940	4014			
Sand			4014	4031			
Slate & Shells			4031	4486			
Limy Sand			4486	4560	Show of Gas		
Slate & Shells			4560	4699	Gas Tests	4694'	10/10-5/8 plate
Sand, Broken			4699	4728	Gas		
Sand		Hard	4728	4735	Gas		
Sand s		Soft	4735	4744	Gas		80/10-5/8 plate
Sand, Broken			4744	4761			
			Total depth	4761			

Date Oct. 23, 1923  
 Hall #3 Well, Queen Gas Co.  
 APPROVED Harmon Gura, Owner  
 By \_\_\_\_\_ (Title)