


LATITUDE 39° 00' 00"

LONGITUDE 80° 35' 00"



7'5 OGIS topo location

7.5' loc 2.52S 15' loc _____
 0.37W (calc.) _____

Company HNG Co

Farm Collins Heirs 4035

Quad PETERSON 7 1/2'

County LEWIS

District COURT HOUSE

WELL LOCATION MAP

File No. 041-5A

**AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**
(REQUIRED BY SECTION 2, CHAPTER 26, ACTS 1929)
WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION

W. J. Riddle

COAL OPERATOR _____ NAME OF WELL OPERATOR _____
 ADDRESS _____ COMPLETE ADDRESS _____
 COAL OPERATOR _____ WELL AND LOCATION _____ 19 _____
 ADDRESS _____ COURTS HOUSE _____ District _____
 COAL OPERATOR _____ Well No. 4635 _____ County _____
 ADDRESS _____ Farm _____

AFFIDAVIT TO BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES

AFFIDAVIT

STATE OF WEST VIRGINIA,)
 COUNTY OF Lewis) ss:
Ross E. Menold and Lace J. Riddle
 being first duly sworn according to law depose and say that they are experienced in the work of plugging
 and filling oil and gas wells and were employed by Hope Natural Gas Company, well operator,
 and participated in the work of plugging and filling the above well, that said work was commenced on the
24th day of October, 1929, and that the well was plugged and filled in
 the following manner:

Manner in which sand was plugged:
 Filled hole solid with clay to 2225 feet. Drove 6 5/8
 M. & F. wood plug at 2225 feet. Filled solid with clay to 2175 feet.
 Bridged hole at 2175 feet and drove 6 5/8 lead plug wh' h shut off all gas.

*off file
2-11-3*

Manner in which coal was plugged:
 Was unable to pull 6 5/8 casing. Filled solid with
 clay from 2175 to 740 feet. Split holes in 6 5/8 casing at intervals of
 4 feet from 740 to ~~680~~ 680 feet. Filled from 740 feet to 672 feet solid
 with cement. Filled from 672 to top of hole solid with clay.

Description of monument:
 Concrete block 5 feet long, 8" square, with 3" hole
 extending through the center from end to end. Erected monument December 16,
 1929. Extends 30" below and 30" above surface. Inscription: "H.N.G. Co. No. 4034"
(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 12, OIL AND GAS ACT OF 1929.)
 and that the work of plugging and filling said well was completed on the 16th day of December,

1929
 And further deponents saith not.

Ross E. Menold