

LATITUDE 39° 05' 00"

LONGITUDE 80° 17' 30"



T'S OGIS topo location

7.5' 10c	<u>1.61 S</u>	15' 10c	_____
	<u>1.47 W</u>	(calc.)	_____

Company HNG Co

Form T.A. Law 6239

Quad BERLIN 7 1/2'

County LEWIS

District HACKERS CREEK

WELL LOCATION MAP

File No. 041-19A

**AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 8, CHAPTER 26, ACTS 1922)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION**

No Coal	COAL OPERATOR	Hope Natural Gas Company	NAME OF WELL OPERATOR
	ADDRESS	445 West Main St. Clarksburg, W. Va.	COMPLETE ADDRESS
	COAL OPERATOR	December 6, 1930.	19
	ADDRESS	Hackers Creek	District
	COAL OPERATOR	Lewis	County
	ADDRESS	Well No 6839	
		T. A. Law	Farm

Level 19A

AFFIDAVIT TO BE MADE IN TRIPLICATE, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES

AFFIDAVIT

STATE OF WEST VIRGINIA.

COUNTY OF Harrison

vs:

William R. Ellis

and

William E. Wallace

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by Hope Natural Gas Co., well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

11 day of November, 1930 and that the well was plugged and filled in the following manner:

Manner in which sand was plugged. Clay to 4545- Being 20' above Beacon Sand and set Cement Plug. Bridge 2225 Being 20' below Nail-town sand Clay to 3025 Being 20' above Speechley Sand and set Cement Plug. Bridge 2225 Being 20' below Hayward sand Clay to 2225 being 20' above Fifth sand and set Cement Plug. Clay to 2227 being 20' above Gordon sand and set Cement Plug. Clay to 2220 and set Lead Plug. Clay to 2220 being 20' above Gordon Street sand and set cement Plug. Bridge 2224 Being 20' below 20' sand clay to 2225 and set Cement Plug. Clay to 1220 being 10' below where 6 3/8" Casing is set and have Lead Plug at 1220. Clay to 1220 being 20' above Big Injun Sand and set Cement Plug. Bridge 1220- Being 20' below Hanna sand Clay to 720- Clay to 620 being 20' above Second Salt sand and set Cement Plug. Clay to 720 being 20' above First Salt sand and set Cement Plug. Clay to 520-Being in the big Buckhead sand and set Cement Plug. Bridge 224 being 10' below where 10" Casing is set and Set Cement Plug. Clay to Surface.

No. Coal.

Description of monument: Regular monument installed.

(8" x 8" 30' above surface)

THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, OIL AND GAS ACT OF 1922.
and that the work of plugging and filling said well was completed on the 6th day of December

1930

And further deponents saith not

William R. Ellis

*6839
26
\$1113*