



Law-59-A

I, the undersigned, hereby certify that this map is correct, and shows all the information to the best of my knowledge and belief required by the oil and gas section of the mining laws of West Va.
M. S. S. S. S.

*Plot showing
GAS WELL TO BE PLUGGED
 on lot owned by
G. W. WILSON*

*Located in the City of
 Westar, in Court House
 District, Lewis County.*

PLUGGING AND FILLING WELL
(REQUIRED BY SECTION 4, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

*is equal to our
knowledge*
COAL OPERATOR OR OWNER
ADDRESS

Tracy M. Caine
NAME OF WELL OPERATOR
Weston W. Va.
COMPLETE ADDRESS

COAL OPERATOR OR OWNER

March 29th 1934
WELL AND LOCATION

ADDRESS

Court House District

COAL OPERATOR OR OWNER

Lewis County

ADDRESS

Well No. One

G. M. Wilson Farm

TO BE MADE IN TRIPPLICATE ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE OBTAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

OF WEST VIRGINIA, Ohio }
~~Washington~~ }
Washington }
OF }
SS:

Leroy Cassidy and William Cassidy
I, Leroy Cassidy and William Cassidy, both duly sworn according to law depose and say that they are experienced in the work of plugging oil and gas wells and were employed by Tracy M. Caine, well operator, participated in the work of plugging and filling the above well, that said work was commenced on the day of March 34, 1934, and that the well was plugged and filled in the following manner:

anner in which sand was plugged: Shot tubing at 2255, drove wood plug from 2255 to 2252, cement 2252 to 2242 to 2159. Drive wood plug 2159' to 2156'. Fill with red clay from 2156' to 2060'. Drive wood plug from 2060' to 2057'. Cement from 2057' to 2047'. Set a cement bridge at 1683'. Fill with red clay from 1583' to 1682'. Drive wood plug from 1682' to 1679'. Cement 1679' to 1669'. Fill with clay from 1669' to 1655'. All were tamped to 1669. Set a permanent cement at 1042. Fill with clay from 1042 to 1032. Drive wood plug from 1032 to 1029. Cut pipe at 1022 and fill with cement from 1029 to 840. Drive wood plug from 840 to 837. Cement 837 to 592. Drive wood plug from 595 to 592. Fill with clay from 827 to 595. Drive wood plug from 595 to 592. Fill with clay from 592 to 582, and fill with red clay to surface. Erect a marker described in Rule 18, 1931, Regulations.

Description of monument: Made out of 10" casing and cement.

DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 16, ARTICLE 4, CHAPTER 22 OF THE CODE)

The work of plugging and filling said well was completed on the 24th day of March, 1934.

Further deponents saith not.

Leroy Cassidy
Leroy Cassidy