



dw JBA

I, the undersigned, being duly sworn, depose and say that the foregoing is correct and true to the best of my knowledge and belief, and of the facts and circumstances known to me and the undersigned at the time of the same in and for the County of Loudoun, Virginia.

Acknowledged before me this 9th day of June, 1964, at Loudoun County, Virginia.

PLUGGING AND FILLING WELL
(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)
WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

COAL OPERATOR OR OWNER	T. C. Zinn
ADDRESS	405 1/2 Market Street, Parkersburg, W. Va
COAL OPERATOR OR OWNER	November 7th 19 35
ADDRESS	Freeman's Creek District
COAL OPERATOR OR OWNER	Lewis County
ADDRESS	Well No. 376 Hona Gas Co. J. L. Osbourn, et al Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA, }
 COUNTY OF Wood } ss:

H. E. Adams and Lellis Snyder
 being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by T. C. Zinn, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 16th day of June, 19 35, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Filled with red clay from bottom of well 2095' to 2011', pulled 6-5/8 casing and continued to fill with red clay to 1935'- 20' above Big Injun Sand.
 Drove wood plug from 1935' to 1932' cemented from 1932' to 1972' sealing Big Injun Sand.
 Set a permanent bridge at 1740'- 30' below second Salt Sand, filled with Red clay from 1740' to 1232'- 20' above first salt sand.
 Drove wood plug from 1232' to 1279', cemented from 1279' to 1269' sealing the salt sand.
 None Manner in which coal was plugged:
 Set a permanent bridge at 1065'-30' below Gas sand, filled with Red Clay from 1065' to 943'- 3' below 3-1/4 casing.
 Drove wood plug from 943' to 940', pulled 3-1/4 casing and continued to fill with red clay to 310'-20' above the Little Lunkard.
 Drove wood plug from 310' to 307'.
 Set a permanent bridge at 206', filled with clay from 206' to 197'.
 Drove wood plug from 179' to 176', filled with clay from 176' to surface.
 Erected a marker according to Rule 18.1931 regulations
 Description of monument:
 Cement and 6-5/8 casing

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE)

and that the work of plugging and filling said well was completed on the 1st day of July, 19 35

And further depone that not



H. E. Adams
Lellis Snyder