

LATITUDE 39°00'00"



LONGITUDE 80°37'30"

T5 OGIS topo location

7.5' loc 120 S 15' loc _____
 0.78 W (calc.) _____

Company _____

Farm _____

Quad GILMER 7 1/2

County LEWIS

District COURT HOUSE

WELL LOCATION MAP

File No. 041-91A

91A

Court House District, Lewis County, W. Va.
 South Penn Oil Co., Chamber of Commerce Bldg., Pittsburgh, Pa.
 On 86 acres, surface owned by John H. Linger, RFD No. 1, Camden,
 W. Va., and mineral rights by Bernard Bohan, Roanoke, W. Va.
 Elevation, 1127' L.
 16' conductor; 10" casing, 165' (pulled); 8 $\frac{1}{2}$ " , 1030' (pulled);
 6-5/8" , 2160'.
 Coal was encountered at 446'.
 Abandonment reported to Dept. of Mines Oct. 24, 1935.
 Well was shot March, 1902, with 30 qts.
 Oil well.

	Top.	Bottom.
Pittsburgh Coal	446	
Big Lime	2130	- 2220
Big Injun Sand (gas, 2270')	2220	- 2430
Gordon Stray Sand (gas-oil, 2806')	2803	- 2815
Gordon Sand, to bottom	2826	- 2831

AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 8, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

Jan 9/18

Bernard Bohan <small>COAL OPERATOR OR OWNER</small> Roanoke, W. Va. <small>ADDRESS</small>	SOUTH PENN OIL COMPANY Chamber of Commerce Bldg. Pittsburgh, Pa. <small>COMPLETE ADDRESS</small>
<small>COAL OPERATOR OR OWNER</small> <small>ADDRESS</small>	May 20, 19 36 <small>WELL AND LOCATION</small> Court House District Lewis County Well No. 2 B. Bohan Farm
<small>LEASE OR PROPERTY OWNER</small> <small>ADDRESS</small>	

AFFIDAVIT TO BE MADE IN TRIPLICATE, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR, AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA, }
 County of Harrison } ss:

J. F. Black ~~John~~
 being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by South Penn Oil Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 6th day of April, 19 36, and that the well was plugged and filled in the following manner:

Manner in which well was plugged:
 Total Depth 2832'. Filled with non-porous material to 2783', - 20' above Gordon Sand. Set wood plug 2783' - 2770', sealing Gordon and Stray Sands. Set bridge 2460'. Filled with non-porous material to 2200' - 20' above Big Injun Sand. Set wood plug 2200' - 2197'. Set cement plug 2197' - 2187', - sealing Big Injun Sand. Pulled 6-5/8" casing, 1160' 7". Set bridge 1520'. Filled with non-porous material to 1326'. Set wood plug 1326' - 1323'. Set cement plug 1323' - 1313'. Set bridge 486'. Set 2" vent pipe 486' to surface. Set Morn-ling Gloy Packer 476'. 10' perforated anchor below packer. Cemented vent pipe 476' to 422'. Filled with non-porous material to surface.

Description of monument: Erected monument, -2" pipe 8' above ground 2" Tee 2-1/2" Ell: pointing downward. 2' cement cone around vent pipe 2' above ground.
 All work done in a workmanlike manner.

DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE.