



| | | | |
|-----------------|------------------------|------------|------|
| Company | Snyder Bros + Zinn | | |
| Address | Beckley, West Virginia | | |
| Name | John T. Cawthon | | |
| Tract | 2 | Acres | 0.54 |
| Well (Form) No. | 1 | Serial No. | |
| Station | (Quiet Level) | | 554 |

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MA
 FILE NO. LEW-117A

PLUGGING AND FILLING WELL
(REQUIRE BY SECTION 8, ARTICLE 4, CHAPTER 22 OF THE CODE)
WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

COAL OPERATOR OR OWNER: Lyder Brothers and Zinn NAME OF WELL OPERATOR
 ADDRESS: Martinsburg, W. Va COMPLETE ADDRESS
 COAL OPERATOR OR OWNER: _____ WELL AND LOCATION
 ADDRESS: Freemans District District
 COAL OPERATOR OR OWNER: _____ Lewis County
 ADDRESS: Well No. 1 Well No. _____
John R. Cowthon Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA, }
 COUNTY OF Wood } ss:

Dallas Snyder and Cloyd Owens
 being first duly sworn according to us depose and say that they are experienced in the work of plugging
 and filling oil and gas wells and were employed by Lyder Brothers and Zinn, well operator,
 and participated in the work of plugging and filling the above well, that said work was commenced on the
28th day of October, 1936, and that the well was plugged and filled in
 the following manner:

Manner in which sand was plugged: filled with red clay from 2458' to 2430'
 20' above fifth sand, drove wood plug 2430' to 2427', cemented 2427' to 2417'
 cealing hole above fifth sand, continued to fill with red clay from 2417' to
 2150' - 20' above 30' sand, rod plug 2150' to 2147', cemented 2147' to 2137'
 cealing the 30' sand, set a permanent bridge at 1930' - 30' below here rit cemented
 on top of bridge, filled with red clay from 1930' to 1738' - 15' below 6 5/8 casing
 wood plug 1738' to 1735', cemented 1735' to 1725', cealing hole, pulled 6-5/8 casing
 casing and filled with red clay to 1620' - 20' above Big Injun, wood plug 1620' to
 1617', cemented 1617' to 1607' cealing hole above Big Injun sand, set a permanent
 bridge ~~at 1315' - 30' below second set sand~~ which coal was plugged: none
 at 1315' - 30' below second set sand, cemented on top of bridge, filled with red
 clay from 1315' to 1064' - 10' below 8-1/4 casing, wood plug 1064' to 1061' pulled
 8-1/4 casing and filled with red clay to 932' - 20' feet above second set sand,
 wood plug 932' to 929', cemented 929' to 919' cealing second set sand above
 continued to fill with red clay from 919' to 218' - 15' below casing, wood plug
 218' to 215' cemented 215' to 205', cealing hole, filled with red clay to
 surface.

88
 Description of monument: Painted marker described in Rule 18

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE.)

and that the work of plugging and filling said well was completed on the 19th day of November

1936
 And further depositions said:

Cloyd Owens
Dallas Snyder