





Company Israel H. Beren  
 Address Marietta, Ohio  
 Farm L.M. Reed  
 Tract Acres 73.1 Lease No.             
 Well (Farm) No. 1 Serial No.             
 Elevation (Spirit Level) 1197  
 Quadrangle Vadis  
 County Lewis District Freemans Cr.  
 Engineer C.C. Fittro, C.E.  
 Engineer's Registration No. 818  
 File No. XYZ Drawing No. 91  
 Date Oct. 26, 1937 Scale 1"=30 P.

STATE OF WEST VIRGINIA  
 Department of Mines  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 File No. LEV-128A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

— Denotes one inch spaces on border line of original tracing.

229

WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. CEW-128-A

Oil or Gas Well Oil  
(Kind)

Company.....	Israel H. Beren	Casing and Tubing	Used in Drilling	Left in Well	Packers
Address.....	Marietta, Ohio	Size			
Farm.....	L. M. Reed	16.....			Kind of Packer.....
Location (waters).....	Straight Run	13.....			Size of.....
Well No.....		10.....	246	246	Depth set.....
District.....	L. M. Reed	8 1/4.....	1238	1238	Perf. top.....
The surface of tract is owned in fee by.....	Hurst, W. Va.	6 5/8.....	2150	2150	Perf. bottom.....
Mineral rights are owned by.....	W. C. Black	5 3/16.....			Perf. top.....
Drilling commenced.....	No record	2.....		2538	Perf. bottom.....
Drilling completed.....	No record	Liners Used.....			
Date shot.....	No record				
Open Flow /10ths Water in.....					
Open Flow /10ths Merc. in.....					
Volume.....		CASING CEMENTED.....	SIZE.....	No. FT.....	Date.....
Rock Pressure.....	No record				
Oil.....		COAL WAS ENCOUNTERED AT.....	689	FEET.....	72
Fresh water.....		.....	FEET.....	INCHES.....	FEET.....
Salt water.....		.....	FEET.....	INCHES.....	FEET.....

Formation	Color	Hard or Soft	Top	Bottom	Oil Gas or Water	Depth Found	Remarks
Dunkard Sand			1211	1251			
Salt Sand			1561	1586			
Maxen Sand			1831	1881			
Big Lime			2141	2191			
Big Injun			2191	2301			
Gantz Sand			2533	2538			
Total Depth				2555			



NOV 28 1937

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION**

*Jew 128A*

W. F. Black <small>COAL OPERATOR OF OWNER</small> Clarkburg, W. Va. <small>ADDRESS</small>	Israel H. Beren <small>NAME OF WELL OPERATOR</small> Box 73, Marietta, Ohio <small>COMPLETE ADDRESS</small>
<small>COAL OPERATOR OF OWNER</small>  <small>ADDRESS</small>	December 21, 1937 <small>WELL AND LOCATION</small>
I. H. Beren <small>LEASE OR PROPERTY OWNER</small> Marietta, Ohio <small>ADDRESS</small>	Freeman's Creek <small>District</small> Lewis <small>County</small> Well No. 1 W. L. Reed <small>Farm</small>

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

**AFFIDAVIT**

Ohio }  
 STATE OF ~~WEST VIRGINIA~~ } ss:  
 COUNTY OF ~~Washington~~ }

G. W. Green and  
 being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Israel H. Beren, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 21st day of November, 1937, and that the well was plugged and filled in the following manner:

Manner in which said well was plugged: Filled hole with non porous material from bottom 2555 ft. to 2513 ft. - 20 feet above Cantz Sand. Sealed hole at this point. Anchored permanent bridge at 2331 ft. - 30 ft. below Big Injun. Filled hole with non porous material from 2331 ft. to 2171 ft. - 20 ft. above Big Injun. Sealed hole at this point. Pulled 8-5/8" casing from hole. Anchored permanent bridge at 1911 ft. - 30 ft. below Maxen Sand. Filled hole with non porous material from 1911 ft. to 1811 ft. - 20 ft. above Maxen Sand. Sealed hole at this point. Anchored permanent bridge at 1616 ft. - 30 ft. below Salt Sand. Filled hole with non porous material from 1616 ft. to 1541 ft. - ~~Sealed hole at this point~~ - 20 ft. ~~manner in which coal was plugged:~~ above Salt Sand. Sealed hole at this point. Anchored permanent bridge at 1301 ft. - 30 ft. below Dunkard Sand. Pulled 8" casing from hole. Filled with non porous material from 1281 ft. to 1191 ft. - 20 ft. above Dunkard Sand. Sealed hole at this point. Anchored permanent bridge at 725 ft. - 30 ft. below Coal. Filled hole with neat cement 725 ft. to 669 ft. 20 ft. above Coal. Filled hole with non porous material from 669 ft. to 640 ft. Sealed hole at this point. Pulled 10" casing from hole. Filled hole with non porous material from 240 ft. to top.

Description of monument: Marker not yet installed. Awaiting warm weather for setting of concrete. Will be installed according to regulations.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE)

and that the work of plugging and filling said well was completed on the 21st day of November, 1937.