

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE. ONE COPY MAILED TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY, AND EXTRA COPIES IF REQUIRED, SHOULD BE MAILED TO EACH COAL OPERATOR AT THEIR RESPECTIVE ADDRESSES.

No coal operations in vicinity

Hope Natural Gas Company

COAL OPERATOR OR OWNER

NAME OF WELL OPERATOR

ADDRESS

Clarksburg, W. Va.

COMPLETE ADDRESS

COAL OPERATOR OR OWNER

AUGUST 15, 1941

WELL AND LOCATION

ADDRESS

Freemans Creek

District

Susan Snyder Heirs, Freemansburg, W. Va. Lewis

County

LEASE OR PROPERTY OWNER

Well No. 8440 (Formerly Reserve Gas Co. #744)

ADDRESS

Susan Snyder

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA

County of Lewis

James T. Dempsey

and Cecil C. Collins

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by Hope Natural Gas Co. well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

12th day of July, 1941, and that the well was plugged and filled in the following manner:

BAND OR ZONE RECORD	FILLING MATERIAL		PLUGS USED		CASING		
	FORMATION	CONTENT	FROM	TO	SIZE & KIND	CSS PULLED	CSS LEFT IN
Filled with clay from total depth (2552), to 2513. Cement plug 2513 to 2510. Filled with clay to 2306. Cement plug 2306 to 2305. Filled with clay to 1820. Pulled out 1834', 5-3/16" casing which was run to shut off water while cleaning out well. Continued filling with clay to 1770'. Attempted to pull 6-5/8" casing, was unable to start same, ripped 6-5/8" casing and pulled out 1327', leaving 443' in hole. Filled hole solid with clay from 1770', up through 6-5/8" casing that was left in hole to 1005'. Could not place plug at 1737' on account of leaving in part of 6-5/8" casing. Placed cement plug from 1005 to 1000'. Filled with clay from 1000' to 233'. Cement plug 833 to 230'. Pulled out 213' 10" casing and filled with clay to 158'. Cement from 158 to 104'. Filled hole with clay from 104' to surface of ground.							
COAL BEAMS				DESCRIPTION OF MONUMENT			
(NAME)				Concrete 5' long 6" square with			
(NAME)				3" hole through center. Extends			
(NAME)				30" below and 30" above surface			
(NAME)				of ground. Inscription HNG 8440.			

and that the work of plugging and filling said well was completed on the 15 day of August 1941