

## west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax

Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

May 09, 2016

## WELL WORK PLUGGING PERMIT Plugging

This permit, API Well Number: 47-4301697, issued to HG ENERGY, LLC, is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to all conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas inspector.

Upon completion of the plugging well work, the above named operator will reclaim the site according to the provisions of WV Code 22-6-30. The above named operator will also file, as required in WV Code 22-6-23, an affidavit on form WR-38 by two experienced persons in the operator's employment and the Oil and Gas inspector that the work authorized under this permit was performed and a description given. Failure to abide by all statutory and regulatory provisions governing all duties and operations here under may result in suspensions or revocation of this permit and in addition may result in civil and/or criminal penalities being imposed upon the operator.

This permit will expire in two (2) years from date of issue. If there are any questions, please free to contact me at (304) 926-0499 ext. 1654.

Operator's Well No: A. A. WOODRUM 5

Farm Name: HUGHES, JAMES E.

James Martii

Chief

API Well Number: 47-4301697 Permit Type: Plugging

Date Issued: 05/09/2016

## PERMIT CONDITIONS

West Virginia Code §22-6-11 allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. Failure to adhere to the specified permit conditions may result in enforcement action.

### **CONDITIONS**

- 1. All pits must be lined with a minimum of 20 mil thickness synthetic liner.
- 2. In the event of an accident or explosion causing loss of life or serious personal injury in or about the well or while working on the well, the well operator or its contractor shall give notice, stating the particulars of the accident or explosion, to the oil and gas inspector and the Chief within twenty-four (24) hours.
- 3. Well work activities shall not constitute a hazard to the safety of persons.
- 4. This well is under a consent order and must be plugged under the terms of that agreement.

WW-4B Rev. 2/01

1) Date February 11	,	2016
2)Operator's		
Well No. A A Woodrum 5		
3) API Well No. 47-043		- 1697

## STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

	OFFICE OF	OIL AND GAS
	APPLICATION FOR A PERM	AIT TO PLUG AND ABANDON
4)	Well Type: Oil X / Gas X / Liquid	l injection/ Waste disposal/
	(If "Gas, Production or Und	derground storage) Deep/ Shallow_X
- \	995'	Watershed Hayzlett Fork
5)	Location: Elevation 885'  District Duval	County Lincoln Quadrangle Garrett's Bend 7.5'
		244444
6)	Well Operator HG Energy, LLC	7)Designated Agent Diane White
	Address 5260 Dupont Road	Address 5260 Dupont Road
	Parkersburg, WV 26101	Parkersburg, WV 26101
۵۱	Oil and Gas Inspector to be notified	A) Blugging Contractor
8)	Name Jeremy James	Name To Be Determined Upon Approval of Permit
	Address PO Box 36	Address
	Clendenin, WV 25045	
	** See Attacl	ned Sheet **
		REGEIVED Office of Oil and Gas APR 1 8 2016
	fication must be given to the district of can commence.	WV Department of Environmental Protection and gas of the chief of the control of
Work	order approved by inspector	Date 3-1-16

WW-4B - Conti Rev. 2/01

1)	Date: Fe	ebruary 11	, 2016		
2)	Operator's Well	Number			
-	AA '	Woodrum	5		
3)	API Well No:	47 -	043	-	1697
•		State	County		Permit

## STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

		APPLICAT	ON FOR A PER	MIT	TO PLUG A	ND ABANDO	N			
4)	WELL TYPE:	<u></u>	x Gas	х	_Liquid Injec _Undergroun		Waste Disp ) Deep		allow _	x
5)	LOCATION:	Elevation: District:	885' Duval		_Watershed:_ _County: _	Hayzlett Fo		uadrangle	Garre	tt's Bend 7.5'
6)	WELL OPERAT	5260 Du	rgy, LLC pont Road ourg, WV 26101		494497948	7) DESIGNAT	TED AGENTAddress	Diane V 5260 Du Parkersl	ipont R	oad V 26101
8)	OIL & GAS INS Name Address	Jeremy James P. O. Box 36 Clendenin, W	3			9) PLUGGING Name Address	G CONTRACT To Be Deter		Approva	ıl of Permit
•	WORK ORDER - 2,439'	: The work or	der for the manner	of pl	lugging this w	ell is as follows	:			
Plu Loc Che	nners of pluggir g #1 - 2350' - 22 ated above the ck for free-point at g # 2 - Approx. 1	50' highest perfo top of Big Lime (	ration 1688'), If pipe is free	, part	and pull. If pip	e is not free, prefo	orate for placem	ent of plug #	12.	

Located at elevation, if pipe was not free at 1688', part and pull at elevation (885')

Located at top of Big Lime - 4 1/2" casing stub

Plug #4 - 350' - 250' Located at 8 5/8" casing shoe, below fresh water

Plug #5 - 100' - 0'

Plug #3 - 950' - 850'

Located at Surface

Recover all possible casing. If casing can not be recovered, perforate for plug placement.

Monument 6" minimum diameter metal pipe
30" above surface
10' in well below surface
Sealed with cement
API identification (1/2") height numbering

6% Gel between all plugs

RECEIVED
Office of Oil and Gas

APR 1 8 2016

WV Department of Environmental Protection

Well: A.A. Woodrum #5 Monument to extend 30" above surface. 10' 47-43-1697 API: into well. 6" min metal pipe, sealed with cement. API i.D. Elevation: 885' 5 Casing Information 200 sacks cement to surface 4 Size Depth Weight 8 5/8" 3061 20#/ft. Freepoint Cut and Pull Casing 4 1/2" 2444' 10.5#/ft. Size Approx. Depth 1688' or 885' 4 1/2 4 Hole Size 6.75" Cement Plugs NO. Bottom Top 2350 2250 1 2 1730 1630 3 950 3 850 4 350 250 5 100 0 **Bottom Hole Cement Level Calculations** # Sacks Used Cement Depth 50 2218.167 + Big Lime 1688' - 1880' **Hole Size Casing Size** Depth 2439 6.75 4.5 bbls / ft. diameter delta Conv. Factor 0.02459 25.3125 1029.4 cubic ft. per vertical ft. depth 0.138058122 Sacks per vertical ft. depth 50 Sacks Cement T.O.C. 2218' 0.226415321 Toe of Oil and Gas Yield options APR 1 8 2016 50/50 posmix 6% gel = 1.64 ///Highest Perforation 2378' Neat w/ salt flakes = 1.19 partment of Vironmental Protection 50/50 w/ 2% gel = 1.27 TD 2439'

## PENNZOIL COMPANY Well Completion Report

75% DeArman - 25% Pennzoil

Pool Name: Griffithsville Northeast	Pool No. 57 Eleva	ation_893.81' KB:@K
Producing Formation: <u>Berea</u>	Depth: From	2369' to 2392'
Date Drilled In: August 21, 1976	Pays: Oil: From From	2369' to 2392'
Original Total Depth: 2439'	Gas: From	
Plug Back Depth: 2418'	From	to
Production Initial	Present	After Fracture
011		
Gas 8-5/8"		1
Surface Csg. set @ 313' KB:XIL Gr	H-40 New:Used Wt. 20#	Collars_ST&C
Cement Reg. Neat Amount 200 Sacks		A CONTRACTOR OF THE PROPERTY O
Production Csg. set @ 2435' KB:XGL G		FO# Callana ST&C
rroduction usg. set 6 2435 KB: GL G	r. E.R.W. New:Used Wt.10	J. 50# LOTTERS STAC
Cement 50/50 Posmix Amount 50 Sacks		PM Date 8/21/76
Cement 50/50 Posmix Amount 50 Sacks Logged by: Basin Surveys	Plug Down @ 4:45 AX: Date: Augus	PM Date 8/21/76
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-C	Plug Down @ 4:45 AX:  Date: Augus	PM Date 8/21/76
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-C  Perforated by: McCullough  Perforations: 2378'-2383' - 4 holes/	Plug Down @ 4:45 AM:  Date: Augus  Caliper  Date: Au	PM Date <u>8/21/76</u> st 21, 1976
Cement 50/50 Posmix Amount 50 Sacks Logged by: Basin Surveys Logs Used: Gamma Ray-Comp. Density-C	Plug Down @ 4:45 AM:  Date: Augus Caliper  Date: Ac  Plug Down @ 4:45 AM:  Date: Ac  Plug Down @ 4:45 AM:  Date: Ac	PM Date 8/21/76 st 21, 1976 ugust 30, 1976
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-Composit	Plug Down @ 4:45 AM:  Date: Augus  Caliper  Date: Ac  Fft 20 holes  Breaking F	PM Date 8/21/76 st 21, 1976 ugust 30, 1976
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-Composit	Plug Down @ 4:45 AM:  Date: Augus  Caliper  Date: Ac  Fft 20 holes  Breaking Folvent Gel Agent L	PM Date 8/21/76 st 21, 1976  qust 30. 1976  Fluid F.R. N.E. Agent Agent FR-5 15-N
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-Composit	Plug Down @ 4:45 AM:  Date: Augus  Caliper  Date: Ac  Fft 20 holes  Breaking Folvent Gel Agent L	PM Date 8/21/76 st 21, 1976  qust 30, 1976  Fluid F.R. N.E. Agent Agent FR-5 15-N
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-Composit	Plug Down @ 4:45 AM:  Date: Augus  Caliper  Date: Ac  Oft 20 holes  Divent Gel Agent L  Crathin	PM Date 8/21/76 st 21, 1976  qust 30, 1976  Fluid F.R. N.E. oss Agent Agent  FR-5 15-N  1 2
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-Comparted by: McCullough  Perforated by: McCullough  Perforations: 2378'-2383' - 4 holes/  Treatment Data  Fluid Sand Acid Sample Sample Crude 20/40 15% HCl Pate  Amount 581 24,200 750	Plug Down @ 4:45 AM:  Date: Augus Caliper  Date: Ac  Oft 20 holes  Divent Gel Agent L  Divent Gel Agent L  Divert Gel Agent L  Divert Gel Agent L  Divert Gel Agent L  Divert Gel Agent L	PM Date 8/21/76 st 21, 1976  qust 30. 1976  Fluid F.R. N.E. Agent Agent FR-5 15-N  Transport Transport Avg. 2400
Cement         50/50 Posmix Amount         50         Sacks           Logged by:         Basin Surveys           Logs Used:         Gamma Ray-Comp. Density-Comp.	Plug Down @ 4:45 AM:  Date: Augus Caliper  Date: Au  Fft 20 holes  Olvent Gel Agent L  Crathin  55  ressure: Max. 2500 Min.  Go @ 12:03 AM:PM 5	PM Date 8/21/76 st 21, 1976  qust 30, 1976  Fluid F.R. N.E. Agent Agent FR-5 15-N 1 2 0110 Avg. 2400 6 min. SAP R1156 2016
Cement 50/50 Posmix Amount 50 Sacks  Logged by: Basin Surveys  Logs Used: Gamma Ray-Comp. Density-Composit	Plug Down @ 4:45 MX:  Date: Augus Caliper  Date: Acc  Oft 20 holes  Oft.	PM Date 8/21/76 st 21, 1976  qust 30. 1976  Fluid F.R. N.E. Agent Agent FR-5 15-N  Transport Transport Avg. 2400


### PENNZOIL COMPANY

### NEW WELL REPORT

LEASE NO	190	79-50		ACRES	WORKING DISTR	ст	South	ern Area	
A	A. Woods	rum		FARM	WELL NO.	N	s.	Map	124-W
Duva	al		DISTR	ICT OR	Lincoln	Cou		St.	Albans QUAD.
LOCATION MADE	J	July 29,		19_76	DRILLING COMM			igust 17	
DRILLING EQUIPM	ENT USED	DE S	SPUDDER ROTARY	3	DRILLING COMPL	ETED	At	igust 2]	- <b>,</b> 76
DRILLING EQUIPM FURNISHED BY	ENT FW	A Drill	ing Com	many	TOTAL 243	9	SA	NDE	Berea
ELEVATION: FLOO	DR	893.81		x =	DRILLING CONTR	ACTOR	FWA Dr	illing	Company
ELEVATION: GROU	ND	885,81			WORK ORDER NO	. 7	0-26820	)_1	
	+		Sec.	FORMAT	ON RECORD				
KIND	. TOP	воттом	STEEL * LINE MEAS.	TEST	KIND	ТОР	BOTTON	STEEL LINE MEAS.	TEST
Substructure	0	8					1		
Rock	8	215	1						
Shale	215	1004							
Salt Sand	1004	1454							*
Shale	1454	1511				1	1	1	-
Salt Sand	1511	1580						1	1
Shale	1580	1616							
Salt Sand	1616	1650				-	1	-	
Little Lime	1650	1684			-	-	-	-	
Pencil Cave	=1684	=1688	-				1	-	-
Big Lime	-21688	_1880						-	
McCrady Shale	1880					-			
Big Injun	1895	1895					-		_
Shale		1948					- 34		X
Sand	1948	7			-				+ +
Shale	2024	2082							
	2082	2349							
Coffee Shale	2349	2370			-				4 -4
Berea	2370	2392				100	-		
Shale	2392	2439							
Potal Depth		2439							
									-
Logged by Basi	n Surve	ys, Inc.	8-21-	76 to 3439	*	-	:/-	1.00	
P.B.D.		0.50							
*D*U*		2418							
							F = 111	12.7.7.1	
.V.									
							A 11		
		-							
								100	ET 25 ES 13 / ES 25
		-						180	ECEIVED
		7.4C H	7.5					Office	of Oil and Ga
						- 1			The same of the sa
	*		- 1					A	DD 1 0 2010
				-				. A	PR 1 8 2016
>			34						
					2		•	WATE	Department of
							· Jen		
							127	MONE	<del>name! Preta</del> ct
			Í				-		
	- 1				II .				

## NEW WELL REPORT - CONTINUED

INITIAL TORPEDO RECORD	II.		PUT IN		DING	RECOR			
Date of Shot	SIZE	TRANC	FER NO.				PULLED		
	8-5/8	- nans	EA NO.	306	INCH	TRANSFE	R NO.	FEET	INCH
Name of Torpedo Co.	4-1/2	-							
No. of Quarts	4-1/2	_		2444	.43				
ength of Shell						-			
Diameter of Shell			- 1					- 1	-
ength of Anchor									
Top of Shot									
Sottom of Shot							-		-
Feet of Fluid in Hole When Shot							_		
Results:		-	_		-				-
					_				
	-				_				
									1
	H 1				1				
6.94			٠						
INITIAL PRODUCTION FIRST 24 HOURS	1		PA	CKER	REC	ORD.			
	KINI	)	1	SIZE	DE	PTH SET	D	ATE SET	
Open Flow /10ths Water inInch	Steel Sh		8	3-5/8"		313 RKT	8-	18-76	
/10ths Merc. inInch	Guide Sh	loe		-1/2"	$\overline{}$	435 RK		21-76	
VolumeCu. Ft.								-10	_
Rock Pressure The	1			_	+			_	-
Oilbbls., First 24 hrs.	1		-	_	1				
24 hrs.			11		1				
ACIDIZATION OR FRACTURING RECORD		1			207.5	1754			
THE TOTAL RECORD				CA	SING	CEMENT	ED		
DATE WELL ACIDIZED.			5/on	2	72 0	vin a		,	
DATE WELL FRACTURED		-	-2/0"	SIZE	13 1	KB 8	-TS-3	6	DATE
NAME OF COMPANY		1		200 5	ve N	eat Cem	ant 2	d cc	20.2
List below materials used in Acidizing or Fracturing, i.e., Sand, Crue	de Oil, Gasoline.								
Water, Kerosene, Mothballs, Acid, etc., giving-gallons, barrels and-	oounds.)	4	-1/2"	2	1.35R	CB :- 8	_27_7	6	
				SIZE	7//	F		0	DATE
				· FOrmale	- FO	150-D-		7-00	
			1112.0	-50-sk	s -50	B = 8 /50 Poz	mix 2	ZECC -	1002
		BA	AGS USE	-50-sk	S-50 Gal	/50 Poz	mix 2	ZECC -	1002
		BA	AGS USE	w/500	Gal.	- Mud F	lush	_	-
581 Bbls, Crude Oil		B/	AGS USE	W/500	Gal	Fr.	lush	_	DATE
2 4,200 Lbs. 20/40 Sand		B/	AGS USE	w/500	Gal	Fr.	lush	_	-
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HC1		B/	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sand		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HC1	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HC1	· .	BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HC1		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HC1		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HC1		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  Breakdown Pressure Pumping Pressure Max. 2500 Min. 2300		BA	AGS USER	W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sænd 750 Gal. 15% HCl  Breakdown Pressure Pumping Pressure  Max. 2500 Min. 2300		BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  GREAKDOWN PRESSURE 1500  PUMPING PRESSURE Max. 2500 Min. 2300  AVERAGE PUMPING RATE/MINUTE 30.5 BPM		BA	AGS USEE	5 W/500	Gal	Fr.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE 1500  PUMPING PRESSURE Max. 2500 Min. 2300  AVERAGE PUMPING RATE/MINUTE 30.5 BPM  PUMPING TIME		BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  GREAKDOWN PRESSURE 1500  PUMPING PRESSURE Mex. 2500 Min. 2300  AVERAGE PUMPING RATE/MINUTE 30.5 BPM	. Cu. Fr.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE Max. 2500 Min. 2300  PUMPING PRESSURE Max. 2500 Min. 2300  EVERAGE PUMPING RATE/MINUTE 30.5 BPM  PUMPING TIME  RESULT AFTER   GAS.  TREATMENT   GAS.  OIL	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE Max. 2500 Min. 2300  PUMPING PRESSURE Max. 2500 Min. 2300  EVERAGE PUMPING RATE/MINUTE 30.5 BPM  PUMPING TIME  RESULT AFTER   GAS.  TREATMENT   GAS.  OIL		BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE 1500  PUMPING PRESSURE Max. 2500 Min. 2300  EVERAGE PUMPING RATE/MINUTE 30.5 BPM  PUMPING TIME  RESULT AFTER   GAS.  TREATMENT   OIL  ROCK PRESSURE AFTER TREATMENT	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  Verage Pumping Rate/Minute 30.5 BPM  UMPING TIME  ESULT AFTER   GAS.  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  UVERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  RESULT AFTER   GAS.  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  VERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  ESULT AFTER   GAS.  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT.  MARKS:	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  VERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  ESULT AFTER   GAS  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT.  MARKS:	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  VERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  ESULT AFTER   GAS.  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT.  MARKS:	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  REAKDOWN PRESSURE 1500  UMPING PRESSURE Max. 2500 Min. 2300  VERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  ESULT AFTER   GAS.  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT.  MARKS:	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  VERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  ESULT AFTER   GAS  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT.  MARKS:	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  GREAKDOWN PRESSURE Max. 2500 Min. 2300  LUMPING PRESSURE Max. 2500 Min. 2300  LUMPING TIME  RESULT AFTER   GAS.  TREATMENT   OIL  LOCK PRESSURE AFTER TREATMENT.  EMARKS:	BSLS.	BA	AGS USEE	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE  Max. 2500 Min. 2300  EVERAGE PUMPING RATE/MINUTE 30.5 BPM  PUMPING TIME  RESULT AFTER   GAS  TREATMENT   OIL  ROCK PRESSURE AFTER TREATMENT  EMARKS:	BSLS.	BA	AGS USET	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  BREAKDOWN PRESSURE  Max. 2500 Min. 2300  EVERAGE PUMPING RATE/MINUTE 30.5 BPM  EVERAGE PUMPING TIME  RESULT AFTER   GAS  TREATMENT   OIL  ROCK PRESSURE AFTER TREATMENT  EMARKS:	BSLS.	BA BA	AGS USET	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE  Max. 2500 Min. 2300  WARPING PRESSURE  WERAGE PUMPING RATE/MINUTE 30.5 BPM  WARPING TIME  RESULT AFTER 1 GAS  TREATMENT 011  BOCK PRESSURE AFTER TREATMENT  EMARKS:	BSLS.	BA BA	AGS USET	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HC1  BREAKDOWN PRESSURE Wax. 2500 Min. 2300  WUMPING PRESSURE WERAGE PUMPING RATE/MINUTE 30.5 BPM  PUMPING TIME RESULT AFTER 1 GAS TREATMENT 011  ROCK PRESSURE AFTER TREATMENT  EMARKS:	BSLS.	BA BA	AGS USET	5 W/500	Gal	FT.	lush		DATE
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  GREAKDOWN PRESSURE Max. 2500 Min. 2300  LUMPING PRESSURE Max. 2500 Min. 2300  LUMPING TIME  RESULT AFTER   GAS.  TREATMENT   OIL  LOCK PRESSURE AFTER TREATMENT.  EMARKS:	BSLS.	BA BA	AGS USET	5 W/500	Gal	Mid F FT.  HOWN BY	TEMPER 1	11/EF	DATE OG
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  REAKDOWN PRESSURE Max. 2500 Min. 2300  UMPING PRESSURE Max. 2500 Min. 2300  UVERAGE PUMPING RATE/MINUTE 30.5 BPM  UMPING TIME  RESULT AFTER 1 GAS.  TREATMENT 011  OCK PRESSURE AFTER TREATMENT.  EMARKS:	Bels,	BA BA	AGS USET	OF CEMI	Gal	All WAY F	TEMPER 1	ATURE L	DATE O
2 4,200 Lbs. 20/40 Sand 750 Gal. 15% HCl  REAKDOWN PRESSURE Mex. 2500 Min. 2300  UMPING PRESSURE Mex. 2500 Min. 2300  UMPING TIME  ESULT AFTER   GAS.  TREATMENT   OIL  OCK PRESSURE AFTER TREATMENT.  MARKS:	BSLS.	BA BA	AGS USET	OF CEMI	Gal	Mid F FT.  HOWN BY	TEMPER 1	ATURE L	DATE O



WW-4A Revised 6-07

1)	Date:	February 11, 20	16		
	Operator's Woodrum 5	Well Number	C.		
3)	API Well N	0:47 -	043	1697	

# STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS NOTICE OF APPLICATION TO PLUG AND ABANDON A WELL

(a) Name	James E. Hughes	Name	NA
Address	2062 Garrett's Bend Road	Address	
	Sod, WV 25564		
(b) Name		(b) Coal Ox	wner(s) with Declaration
Address		Name	NA
		Address	
(c) Name		Name	\(\frac{1}{2} \)
Address		Address	
6) Inspector	Jeremy James	(c) Coal Le	ssee with Declaration
Address	P. O. Box 36	Name	NA
	Clendenin, WV 25045	Address	
Telephone	304-951-2596		

#### TO THE PERSONS NAMED ABOVE: You should have received this Form and the following documents:

- (1) The application to Plug and Abandon a Well on Form WW-4B, which sets out the parties involved in the work and describes the well its and the plugging work order; and
- (2) The plat (surveyor's map) showing the well location on Form WW-6.

The reason you received these documents is that you have rights regarding the application which are summarized in the instructions on the reverses side. However, you are not required to take any action at all.

Take notice that under Chapter 22-6 of the West Virginia Code, the undersigned well operator proposes to file or has filed this Notice and Application and accompanying documents for a permit to plug and abandon a well with the Chief of the Office of Oil and Gas, West Virginia Department of Environmental Protection, with respect to the well at the location described on the attached Application and depicted on the attached Form WW-6. Copies of this Notice, the Application, and the plat have been mailed by registered or certified mail or delivered by hand to the person(s) named above (or by publication in certain circumstances) on or before the day of mailing or delivery to the Chief.

OFFICIAL SEAL Well Operator	HG Energy, LLC
NOTARY PUBLIC BY:	Diane White
STATE OF WEST VIRGINIA I S:	Agent RESERVE
96 Turning Leaf Lane Address	5260 Dupont Road
Williamstown, West Virginia 26187	Parkersburg, WV 26101
My Commission Expires July 11, 2022	304-420-1119
	AFR 1 8 2016
	WVD
	ay of February, 2016 WV Department of EnvironNotary Public rotection
Diane White	- WHON Notary Rublic
Commission Expires July 11, 2022	rotection

Oil and Gas Privacy Notice

The Office of Oil and Gas processes your personal information, such as name, address and phone number, as a part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of business or as needed to comply with statutory or regulatory requirements, including Freedom of Information Act requests. Our office will appropriately secure your personal information. If you have any questions about our use of your personal information, please contact DEP's Chief Privacy Officer at depprivacyoffier@wv.gov.

WW-9 (2/15)

API Number 4	7 - 043	_ 1697
Opera	tor's Well N	O. A A Woodrum 5

#### STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

FLUIDS/ CUTTINGS DI	ISPOSAL & RECLAMATION PLAN
Operator Name HG Energy, LLC	OP Code 494497948
Watershed (HUC 10) Hayzlett Fork	Quadrangle Garrett's Bend 7.5'
Do you anticipate using more than 5,000 bbls of water to co	
If so, please describe anticipated pit waste: Fluids	s encountered while plugging subject well
Will a synthetic liner be used in the pit? Yes	
Proposed Disposal Method For Treated Pit Wastes:	* 4 * *
Land Application No La	nel Application
Underground Injection ( UIC Per	
Reuse (at API Number	
Off Site Disposal (Supply form V	WW-9 for disposal location)
Other (Explain	
Will closed loop system be used? If so, describe: NA	
Drilling medium anticipated for this well (vertical and horiz	ontal)? Air, freshwater, oil based, etc. NA
-If oil based, what type? Synthetic, petroleum, etc.	NA
Additives to be used in drilling medium? NA	
Drill cuttings disposal method? Leave in pit, landfill, remov	ved offsite, etc. NA
-If left in pit and plan to solidify what medium will	be used? (cement, lime, sawdust) NA
-Landfill or offsite name/permit number?	
Permittee shall provide written notice to the Office of Oil an West Virginia solid waste facility. The notice shall be provid where it was properly disposed.	nd Gas of any load of drill cuttings or associated waste rejected at any ded within 24 hours of rejection and the permittee shall also disclose
on August 1, 2005, by the Office of Oil and Gas of the West provisions of the permit are enforceable by law. Violation law or regulation can lead to enforcement action.  I certify under penalty of law that I have person application form and all attachments thereto and that, but	
Company Official Signature Diane White	Office of Other
Company Official (Typed Name) Diane White	Office of Oil and Gas
Company Official Title Agent	APR 1 8 2016
Company Official Title 1950	
	WV Department of
Subscribed and sworn before me this 11th day of	February, 2016 NVIrong 1-Die 20 16 rotection
Diane White	Notary Public
My commission expires July 11, 2022	

Form WW-9

OIII W W-9		Operator's W	ell No. A A Wood		
HG Energy	, LLC				
Proposed Revegetation Trea	atment: Acres Disturbed 0.9 acr	res Prevegetation pF	Η		
Lime	3 Tons/acre or to correct to ph	6.5			
	0-20-20 or equivalent ■				
Fertilizer amount	500 <sub>][</sub>	os/acre			
Mulch_ Straw	2 <sub>Tons</sub> /	acre			
	<u>See</u>	d Mixtures			
Т	emporary	Perma	Permanent		
Seed Type	lbs/acre	Seed Type	lbs/acre		
Tall Fescue	40	Tall Fescue	40		
Ladino Clover	5	Ladino Clover	5		
Plan Approved by:	Control Will Be In Place	e At All Times			
Comments:					
Title: inspect	006	Date: 4 RECEIVED	<u> </u>		
Field Reviewed?	) Yes (				
		APK I 8 2010			

WV Department of Environmental Protection

## Westbrook, Joshua P

From: Diane White <dwhite@hgenergyllc.com>

Sent: Friday, May 06, 2016 9:49 AM

To: Westbrook, Joshua P

Subject: Pit Fluids

#### Josh,

As per our discussion, HG does not intend to treat pit fluids for the following new well drill sites and plugging sites. HG will contract hauling the pit fluids to an authorized disposal site.

New Drill Sites:

CB Ferrell 218

Jackson Long 220

Jackson Long 129

Jackson Long 130

AW Edgell 127

IB Butcher 128

Wells to be plugged:

Stowers Heirs 6

Samuel Bowman 2

AA Woodrum 5

Woodrum Daniels 2

SW Nunn 1

SW Nunn 2

Please let me know if I should provide more information.

Thanks,

Diane

Diane C. White




HG Energy, LLC 5260 Dupont Road Parkersburg, WV 26101

304-420-1119 (O)

304-482-0108 (C)

304-863-3172 (F)

dwhite@hgenergyllc.com



WW-7 5-02

## West Virginia Department of Environmental Protection Office of Oil & Gas

## WELL LOCATION FORM: GPS

	47- 043	- 1697		WELL NO:	5
FARM NAME:	A.A.	Woodrum No.5			
RESPONSIBLE PAI	RTY NAME:	H.G. En	ergy, LLC		
COUNTY:	Line	oln		DISTRICT:	Duval
QUADRANGLE:		Garrett's Bend 7.5	5'		
SURFACE OWNER		James E. Hughes			
ROYALTY OWNER	₹:	H.G. Energy, LLC	et al.		
UTM GPS NORTHI	NG:	4,236,350	(NAD 83)		
UTM GPS EASTING	3:	422,040	(NAD 83)	GPS ELEVATION:	270 m. (885
preparing a new wel Oil & Gas will not a	Il location pla accept GPS co	ove has chosen to sub at for a plugging perm oordinates that do not	it on the above meet the foll	ve well. The Office of lowing requirements:	
preparing a new well Oil & Gas will not a  1. Date heig 2. According	Il location pla accept GPS co um: NAD 198 ht above mea uracy to Datu	nt for a plugging permoordinates that do not 83, Zone:17 North, C an sea level (MSL) - n um - 3,05 meters	it on the above meet the foll Coordinate Un	ve well. The Office of lowing requirements:	
preparing a new well Oil & Gas will not a  1. Datu heig 2. Accurate Accurat	Il location pla accept GPS co um: NAD 198 ht above mea	at for a plugging permoordinates that do not 83. Zone:17 North, Can sea level (MSL) - num - 3.05 meters  Method:  Post Processed D	it on the above meet the following the coordinate Unneters.	ve well. The Office of lowing requirements:	
preparing a new well Oil & Gas will not a  1. Datu heig 2. Accu 3. Data Survey G	Il location pla accept GPS co um: NAD 198 ht above mea uracy to Datu a Collection M arade GPS	nt for a plugging permoordinates that do not 83, Zone:17 North, C an sea level (MSL) - n am - 3,05 meters Method:	it on the above meet the followed the followed in the followed	ve well. The Office of lowing requirements:	
preparing a new well Oil & Gas will not a  1. Datu heig 2. Acci 3. Data Survey G  Mapping  I the undersigned, he	Il location pla accept GPS co um: NAD 198 ht above mea uracy to Datu a Collection M arade GPS Grade GPS ereby certify the informat	at for a plugging permoordinates that do not 83, Zone:17 North, Can sea level (MSL) - norm - 3.05 meters  Method:  Post Processed D	it on the above meet the followed the followed in the followed	ve well. The Office of lowing requirements: nits: meters, Altitude X	
Date Oil & Gas will not a  1. Date heig 2. Acce 3. Data Survey G  Mapping  I the undersigned, he belief and shows all	Il location pla accept GPS comes are NAD 198 ht above mea aracy to Datu a Collection Marade GPS Grade GPS ereby certify the informat ffice of Oil ar	at for a plugging permoordinates that do not 83, Zone:17 North, Can sea level (MSL) - norm - 3.05 meters  Method:  Post Processed D	it on the above meet the followed the followed in the followed	ve well. The Office of lowing requirements: nits: meters, Altitude X	GEIVED f Oil and Gas