

LATITUDE

LONGITUDE

7'5 OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
(calc.) \_\_\_\_\_

Company Holley Oil & Development Co

Farm G.W. Byrnside 2

Quad \_\_\_\_\_

County Lincoln

District Duval

WELL LOCATION MAP

File No. 043-70023

# 5 in 1913 WVGES  
Lincoln County Report

*By 1913 CWL Rpt.*

Duval District, Lincoln County, W. Va.  
By Holley Oil and Development Co.  
Elevation, 835'.  
On Turkey Creek.

Drilling commenced June 28, 1905; completed, July 13, 1905.  
Cost per foot, \$1.00. Contractor, Chamberlin & Co.  
Conductor, 20'; 6-5/8" casing, 130' (110' left in well).  
6-5/8" packer. 3" tubing all out. One packer, 6-5/8", spoilt.  
Water well 85' deep. Dry hole? (Probably drowned out).

7

	Top.	Bottom.	Thickness.
Conductor	0	20	20
Slate	20	30	10
Red rock	30	50	20
Slate and shells	50	130	80
Slate	130	210	80
Sand	210	235	25
Slate	235	265	30
Sand	265	325	60
Slate	325	330	5
Sand	330	360	30
Slate	360	370	10
Sand	370	465	95
Slate (water, 485')	465	485	20
Sand	485	570	85
Slate	570	580	10
Sand	580	595	15
Slate	595	615	20
Sand	615	675	60
Slate	675	715	40
Sand	715	775	60
Slate	775	860	85
Sand	860	880	20
Slate	880	940	60
Limestone	940	955	15
Sand	955	988	33
Sand (gas at 988'; water, 8' below = 995'; more water, 20' below gas = 1008')	988	1017	29
Total depth of well		1017	
Depth of water well		85	
		<u>1102</u>	

The total of 1102' may be the total depth of the gas well (1017') and the water well (85'). CWL Rpt. gives depth of gas well as 1017'.  
RPT