

SB 1913 Co. Rep

Duval District, Lincoln County, W. Va.
 By Benedum & Trees, Pittsburgh, Pa.
~~At~~ Head of Laurel Fork of Horse Creek; Griffithsville district.
 Completed, March 19, 1909.
 Contractor, Kanawha Drilling & Development Co., St. Albans, W. Va.,
 F. G. Leidecker, Foreman.
 Drillers: W. H. Kirtley and A. C. Phillips.
 13" casing, 12'; 10", 140'; 8", 430'; 6-5/8", 1650'. All left in.
 Elevation, 925'. (900'; 900+10') (CWL - 925')
 On 115 acres.

	Top.	Bottom.
Loose earth	0	12
Sand	12	35
Lime	35	85
Slate	85	110
Sand	110m-	135
Slate	135	175
Sand	175	400
Slate	400	450
Sand	450	540
Slate	540	590
Sand	590	700
Slate	700	770
Sand	770	840
Slate	840	890
Sand	890	900
Slate	900	905
Sand (6 bailers salt water at 965'; 985')	905	1540
Red rock	1540	1580
Lime, shells, and slate	1580	1650
Big Lime	1650	1850
Big Injun Sand	1850	1895
Slate and shells	1895	2356
Berea Grit Sand (oil and 231 M. gas)	2356	2377
Slate (6 bbls. light yellow, very high gravity)	2377	2379
Total depth		2379

(SEE OTHER SIDE FOR
 ANOTHER RECORD OF THIS WELL)

HORSE CREEK LAND (COAL) CO. NO. 2 WELL.

	Thickness.	Depth.
Unrecorded	15	- 15
Sand	20	- 35
Lime	50	- 85
Slate	30	- 115
Sand	15	- 130
Slate	45	- 175
Sand	225	- 400
Slate	50	- 450
Sand	95	- 545
Slate	50	- 595
Sand	105	- 700
Slate	70	- 770
Sand	75	- 845
Slate	45	- 890
Sand	10	- 900
Slate	5	- 905
Sand (water at 955'; big water at 980')	635	- 1540
(Light blue)	40	- 1580
Lime and shale	70	- 1650
Big Lime	200	- 1850
Big Injun Sand	50	- 1900
Slate, lime, sand	450	- 2350
Berea Sand	20	- 2370
Slate (or shale)	10	- 2380

300,000 cu. gas, 6 bbls. oil, light yellow, very high gravity,
in Berea Sand.