

LATITUDE

LONGITUDE

7'5 OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
(calc.) \_\_\_\_\_

Company Ohio Fuel Oil Co

Farm W L Richmond 1 (156)

Quad \_\_\_\_\_

County Lincoln

District Duval

WELL LOCATION MAP

File No. 043-70172

*NOT in 1913 Co. Rept*

Duval District, Lincoln County, W. Va.

The Ohio Fuel Oil Co.

Drilling commenced Jan. 27, 1910, and completed April 5, 1910.

Contractor, Pratt Drilling Co., Charleston, W. Va.

Drillers names, F. E. Sackrider and Ray Metts.

About 400,000 cu. ft. gas; no oil at all.

Record by C.E.Krebs from record book of O.F.O.Co., Nov. 14, 1911.

	Top.	Bottom.	Thickness.
Red rock	0	- 75	75
Slate	75	- 195	120
Sand	195	- 260	65
Slate	260	- 275	15
Sand	275	- 340	65
Slate	340	- 355	15
Sand	355	- 460	105
Slate	460	- 490	30
Sand	490	- 650	160
Slate	650	- 670	20
Sand	670	- 800	130
Slate	800	- 815	15
Sand	815	- 970	155
Slate	970	- 1140	170
Salt Sand (gas sand, 1175')	1140	- 1685	545
(hole full water at 1200')			
Maxton Sand	1685	- 1705	20
Slate (cave)	1705	- 1715	10
Little Lime	1715	- 1755	40
Pencil Cave	1755	- 1760	5
Big Lime	1760	- 1945	185
Big Injun Sand (water to drill with at 1980')	1945	- 1985	40
Slate and shells	1985	- 2090	105
Black lime	2090	- 2190	100
Slate and shells	2190	- 2426	236
Berea Sand (gas)	2426	- 2451	25