

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

MILDRED H PRICHARD HEIRS (C/O PHIL PRICHARD)
Lease or Property Owner
PO BOX 108, MANNINGTON, WV 26582
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address

MANNINGTON 7.5'
Well Location
MANNINGTON
District
MARION
County
8006
Well No.
PRICHARD, PHIL ET AL
Farm

STATE INSPECTOR SUPERVISING PLUGGING Jeff Hurlbush 12-15-15

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 12th day of October, 2015 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In	
Cleaned 3 1/2" hole from Surface to 3027'. Tagged solid plug at 3027'. Cemented bottom hole from 3027' to 1830' with 75 sacks of Expandable Cement. 4 1/2" casing had existing perforations at the following depths: 2980', 2941', 2832' and 2802'. Cut 4 1/2" casing at the following depths: 1778' and 1677'. Removed 1578' of 4 1/2" casing from Surface to 1578'. Attempts to remove additional 4 1/2" casing we unsuccessful due to extreme cement bond. Cemented hole from top of bottom hole plug at 1830' to 923' with 130 sacks of Expandable Cement. Left an unknown amount of 7" casing in the hole from Surface to an unknown depth. Cleaned 6 1/4" hole from Surface to 923'. Tagged top of cement plug at 923'. Jet cut 7", 9 5/8" and 13 3/8" casing at the following depths: 583', 581', 579', 577', 575', 573', 571', 569.5', and 568'. Cleaned 6 1/4" hole through the Pittsburgh Coal seam from 571' to 578'. Left an unknown amount of 9 5/8" casing in the hole from Surface to an unknown depth. Left an unknown amount of 13 3/8" casing in the hole from Surface to an unknown depth. Left 20' of 16" conductor casing in the hole from Surface to 20'.		4 1/2"	1578'	Unknown	
			7"	0'	Unknown
			9 5/8"	0'	Unknown
			13 3/8"	0'	Unknown
			16" Conductor	0'	20'
<p>Cemented hole from 923' back to Surface as follows: From 923' to 471' with 90 sacks of Thixotropic Cement with green dye. From 471' back to the Surface with 70 sacks of Expandable Cement. Cement did circulate at the Surface.</p>					
Coal Seams	Description of Monument				
<u>Pittsburgh</u>	<u>(571' - 578')</u>	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.			


RECEIVED
Office of Oil and Gas
DEC 16 2015
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 29th day of October, 2015

And further deponents saith not.

Delbert Moore
Delbert Moore

Kevin S. Wright
Kevin S. Wright



Sworn to and subscribed before me this 16th day of November, 2015

[Signature]
Notary Public

My commission expires: 08/16/17

Permit No. 47-049-01465-P
Well No. 8006

12/18/2015