

ORIGINAL

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
ALMA FRYE
Lease or Property Owner
447 WARRIOR FORK ROAD, MANNINGTON, WV 26582
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
5349
Well No.
MINGER, HARLED G. & ALMA A
Farm

STATE INSPECTOR SUPERVISING PLUGGING William R. Hendricks 117-102

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and **KEVIN WRIGHT** being first duty sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 20th day of August, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Removed all 2 3/8" tubing from the surface to 833'. Cleaned 12 1/4" hole from surface to 271'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 271' to 845'. Tagged top of 8 5/8" casing at 845'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 845' to 1415'. Section milled 8 5/8" casing from 845' to 887.5'. Cleaned 9 7/8" hole through the Pittsburgh coal seam from 873' to 881'. Cut 8 5/8" casing at the following depths: 960', 1060', 1160' and 1260'. Left 472.5' of 8 5/8" casing in the hole from 887.5' to 1360'. Left 30' of 16" conductor pipe in the hole from the surface to 30'.		16" Conductor 8 5/8" Casing 2 3/8" Tubing	0' 0' 833'	30' 473' 0'
Cemented hole from 1415' back to surface as follows: From 1415' to 1081" with 335 sacks of Super Lite Cement. From 1081' to 773' with 90 sacks of SuperTropic Cement with white dye. From 773' to surface with 67 sacks of Super Lite Cement. A total of 402 sacks of Super Lite Cement, and 90 sacks of Super Lite SuperTropic Cement was used to fill the hole from 1415' back to surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh	(873' - 881')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

RECEIVED
Office of Oil & Gas
NOV 20 2012

WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 26th day of September, 2012

And further deponents saith not.

Delbert Moore
Delbert Moore

Kevin S. Wright
Kevin S. Wright


Sworn to and subscribed before me this

5th day of November 2012

Jacqueline L. Shriver
Notary Public

My commission expires:

March 18, 2020



Permit No. 47-049-02228-P
Well No. 5349