

AFFIDAVIT OF PLUGGING AND FILLING WELL

ORIGINAL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address

DOUGLAS L. CYPHERS  
Lease or Property Owner  
8 SMOKEY VALLEY ROAD MANNINGTON, WV 26582  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE ST. MONONGAH, WV 26554  
Complete Address

CLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District

MARION  
County  
5162  
Well No.

CYPHERS, DOUGLAS L.  
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]*

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

RUSSELL SMALLWOOD and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 1<sup>st</sup> day of May, 2013 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
<p>Cleaned 12 1/2" hole from the surface to 231'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 231' to 1249'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 744' to 752'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 1249' to 1746'. Reduced hole to 6 1/2". Cleaned 6 1/2" hole from 1746' to 2746'. Tagged solid plug at 2746'. Cement bottom hole plug from 2746' to 1000' with 345 sacks of 35/65 Poz Mix Cement. Tagged bottom hole plug at 977'. Left 15' of 16" conductor casing in the hole from the surface to 15'.</p> <p><u>Cemented hole from top of bottom hole plug at 977' back to surface as follows:</u> From 977' to 644' with 160 sacks of Thixotropic Cement w/ dye. From 644' to 251' with 115 sacks of Econofill Cement. From 251' to the surface with 100 sacks of Econofill Cement. A total of 720 sacks of cement was used to cement the hole from 2746' to surface. Cement did circulate at the surface.</p>		16" Conductor	0'	15'
Coal Seams		Description of Monument		
<u>PITTSBURGH</u>	<u>744' to 752'</u>	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7"		
(Name)		casing. Well marker will be attached to the		
(Name)		cement plug at ground level.		

RECEIVED  
Office of Oil & Gas  
JUN 24 2013  
WV Department of  
Environmental Protection

... And that the work of plugging and filling said well was completed on the 17<sup>th</sup> day of May, 2013

And further deponents saith not.

*[Signature]*  
Russell Smallwood


*[Signature]*  
Kevin S. Wright

Sworn to and subscribed before me this 20 day of June

*[Signature]*  
Notary Public

My commission expires: February 16, 2021

Permit No. 47-49-02258-P  
Well No. 5162



07/19/2013