	LATITUDE 39 35
	CNG
	LONGITUDE
	m
	800
	Ŏ
	2.74s .85w
	7'5 OGIS topo location
	5' loc 15' loc (calc.)
Company	
Farm LAURA A. BROCK 67	
	WELL LOCATION MAP
Quad GRANT TOWN	File No. 30081
County MARIDE	
District Paw Paw	



Paw Paw District, Marion County, W. Va.

By Owens-Illinois Glass Co., Gas Dept., Charleston, W. Va.

On 51 acres, surface owned by L. A. Brock Heirs, Rivesville, W. Va., and coal rights by The Consolidation Coal Co., Fairmont, W. Va. Well was completed Dec. 10, 1924. Elevation, 1015' L.
16" conductor, 16': 10" casing, 437': 82", 1090': 6-5/8", 1662':

2" tubing, 1764'. Gas anchor packer, 2 x 6-5/8, set at 1668'. Coal was encountered at 240-248 and 367-373'.

10" casing cemented in through Pittsburgh Coal from 317 to 437'.

Packer, all 2" tubing, and 926' of 84" casing were removed in 1930.

Abandonment reported to Dept. of Mines Oct. 26, 1933. Well was shot at 2218-2230 and 1719-1730'.

Salt water at 1282'. Gas well.

MAR-81-A

			*
	Top.	Bottom.	Thickness.
Slate and shells	0	- A	240
Mapletown (Sewickley) Coal	5,10	- 5/18	8
Lime and shells	248	- 367	119
Pittsburgh Coal	367	- 373	6
Shale and shells		- 703	330
Sand (gas, 708-710'; blew out)	703	- 725	55
Slate and lime shells		- 925	200
Sand	925	- 940	15
Shale	940	- 980	40
Sand	980	- 1010	30
Shale	1010	- 1020	10
Sand	1020	- 1100	80
Shale and lime shells	1100	- 1165	65
Sand		- 1232	67
Shale		- 1255	23
Third Salt Sand (hole full water,			
1282-1295')	1255	- 1430	175
Shale and shells		- 1652	222
Big Lime		- 1715	63
Big Injun Sand (gas, 1721-1731')		- 1735	50
Red rock		- 1737	2
Slate		- 1742	5
Lime, hard		- 1764	55
Total depth (1924)		1764	
DRILLED DEEPER (1930):			
Big Injun Sand, gray, hard	1764	- 1859	95
Slate, gray, soft	1859	- 1874	15
Lime, gray, hard	1874	- 1881	7
Slate and lime shells, dark, medium		- 1903	55
Sand, white, hard	1903	- 1978	75
Slate and shells, dark, medium		- 2047	69
Lime, white, hard		- 2113	68
Slate and shells, black, soft		- 2141	28
Sand, dark, hard		- 2165	24
Slate and shells, dark, medium		- 5505	37
Gantz Sand, gray, medium and hard			
(gas at 2225')	5505	- 2268	66
Slate, gray, soft		- 2269	1
50-Ft. Sand, gray, hard	2260	- 2288	19
	2209 .		19
Total depth		2288	