

Lincoln District, Marion County, W. Va.

By A. M. Snider, Weynsburg, Pa.

Abandoned under permit Mar-.....-A?

On 120 acres.

Elevation, 1488' L.

Surface owned by Henry M. and Foster G. Rexroad, Fairmont, W. Va., and minerals by Eastern Gas & Fuel Associates, Grant Town, W. Va.

Drilling commenced Oct. 27, 1910; completed Dec. 15, 1910.

Shot Jan. 3, 1921, with 15 qts., Gantz Sand; Feb. 13, 1925, with 15 qts., 5th Sand; and July 1, 1938, with 20 qts., Gantz Sand.

Salt water at 1720'.

10" casing, 1303'; 8 $\frac{1}{2}$ " , 1485'; 6 $\frac{3}{4}$ " , 1590'; 5 $\frac{1}{2}$ " , 2060'; all left in.

Coal was encountered at 763-774'.

Packers: 6 x 10, C. A., set at 1444'; 8 x 10, A., set at 1460';

6" shoe, set at 1578'; 5" shoe, set at 2046'; 2 x 5 A (pulled), set at 2201'.

Gas well. Record to Dept. of Mines stamped July 20, 1950.

Record to RCF from Mrs. Griffith June 24, 1951. Old File No. 785.

	Top.	Bottom.
Pittsburgh Coal	763	- 774
Dunkard Sand	1105	- 1320
Gas Sand (gas, 1467')	1432	-
Salt Sand	1573	- 1628
Big Injun Sand (water, 1720')////	2098	- 2233
Gantz Sand (gas, 2633')	2620	- 2666
Fifty-foot Sand	2684	- 2731
Thirty-foot Sand	2754	- 2786
Stray Sand	2957	- 2966
Gordon Sand	2973	- 2982
Fourth Sand	2993	- 3012
Fifth Sand (gas, 3139-41')	3127	- 3141
Total depth		3165



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

WELL RECORD

785

Permit No. 670-A Oil or Gas Well Oil (KIND)

Company A. M. Snider
 Address Waynesburg, Pa.
 Farm Martin L. & Hannah Yost Acres 120
 Location (waters) _____
 Well No. 1 Elev. 1488
 District Lincoln County Marion
 The surface of tract is owned in fee by Emory W. & Foster
G. Rozzroad Address Fairmont, W. Va.
 Mineral rights are owned by Eastern Gas & Fuel
Associates Address Grant Town, W. Va.
 Drilling commenced Oct. 27, 1910
 Drilling completed Dec. 15, 1910
 Date Shot See below From _____ To _____
 With _____
 Open Flow _____ /10ths Water in _____ Inch
 _____ /10ths Merc. in _____ Inch
 Volume _____ Cu. Ft.
 Rock Pressure _____ lbs. _____ hrs.
 Oil _____ bbls., 1st 24 hrs.
 Fresh water _____ feet _____ feet
 Salt water 1720 feet _____ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			<u>See below.</u>
10	<u>1303</u>	<u>1303</u>	Size of
8 1/4	<u>1485</u>	<u>1485</u>	
6 5/8	<u>1590</u>	<u>1590</u>	Depth set
5 3/16	<u>2060</u>	<u>2060</u>	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____
 COAL WAS ENCOUNTERED AT 763 FEET _____ INCHES
 _____ FEET _____ INCHES FEET _____ INCHES
 _____ FEET _____ INCHES FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Pittsburgh Coal			763	774			
Dunkard Sand			1105	1320			
Gas Sand			1432		Gas 1467		
Salt Sand			1573	1628			
Injun Sand			2098	2233	Water 1720		
Gantz Sand			2620	2666	Gas 2633		
Fifty Foot			2684	2731			
Thirty Foot			2754	2786			
Stray Sand			2957	2966			
Gordon Sand			2973	2982			
Fourth Sand			2993	3012			
Fifth Sand			3127	3141	Gas 3139-41		
Total Depth				3165			

Shooting		Packers			
Date	Qts	Sand	Size	Make	Set At
1-3-21	15	Gantz	6x10	G.A.	1444
2-13-25	15	5th	8x10	A.	1460
7-1-38	20	Gantz	6"	Shoo	1578
			5"	"	2046
			2x5	A (Pulled)	2201

