

39°32'30"

Latitude

80°25'00"

Longitude

1.38s
.36w

Topo Location

7.5' Loc. _____ 15' Loc. _____
_____ (calc.) _____

Company _____

Farm _____

15' Quad _____
(sec.)

7.5' Quad Glover Gap

District Mammington

WELL LOCATION PLAT

County 049 Permit 30742

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

Permit No. Mar-742 WELL RECORD

Oil or Gas Well _____

Company Head Supply Company
 Address 184 East Main St., Salem, W. Va.
 Farm George W. Beatty Acres 250
 Location (waters) Buffalo Creek
 Well No. 5 Elev. 988.49
 District Hamington County Marion
 The surface of tract is owned in fee by Mr. Glen Beatty
St. 2 Address Hamington, W. Va.
 Mineral Charles W. Beatty, Trustee
Sampson, Box 300, Marlinton, W. Va.

Drilling commenced _____
 Drilling completed July 15, 1904
 Date Shot From _____ To _____
 With _____

Open Flow /10ths Water in _____ Inch
 /10ths Merc. in _____ Inch
 Volume _____ Cu. Ft.
 Rock Pressure _____ lbs. _____ hrs.
 Oil _____ bbls., 1st 24 hrs.
 Fresh water _____ feet
 Salt water _____ feet

Casing and Tubing
 Size
 14
 13
 10
 8 1/4
 6
 5 3/16
 2
 2

Used in Drilling
 1348'
 1860'
 2700'

Left in Well
 1348'
 1860'
 2700'

Packers
 Kind of Packer
 Size of
 Depth set
 Perf. top
 Perf. bottom
 Perf. top
 Perf. bottom

Liners Used
 Perf. top
 Perf. bottom

CASING CEMENTED No. _____ SIZE _____ No. Ft. _____

COAL WAS ENCOUNTERED AT 651 FEET 72 INCHES
 FEET INCHES FEET INCHES
 FEET INCHES FEET INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Pittsburgh Coal			645	651			
Little Dunkard Sand			1060	1090			
Sand			1090	1115			
Big Dunkard			1135	1215			
Maxon Sand			1778	1813			
Big Lime Sand			1910	1966			
Big Injun			1966	2110			
50' Sand			2576	2616			
30' Sand			2638	2700			
Total Depth				2700'	Oil at 2674 - 2690		

1822

SEE
733 FOR
2004

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN WRITING. ONE COPY MAILED TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND A FOURTH IF REQUIRED) SHOULD BE MAILED TO EACH COAL OPERATOR AT THEIR RESPECTIVE ADDRESSES.

The Charleston National Bank, Trustee
COAL OPERATOR OR OWNER
RAAD SUPPLY COMPANY
NAME OF WELL OPERATOR
Address: Bernard G. Beatty, Engr.
184 East Main St., Salem, W. Va.
Box 368, Fairmont, W. Va.
August 30 19 51
WELL AND LOCATION
Mannington District
Mr. Glen Beatty
LEASE OR PROPERTY OWNER
Marion County
Rt. 2 - Mannington, W. Va.
Well No. 3
George W. Beatty Farm

STATE INSPECTOR SUPERVISING PLUGGING Oliver W. Lineberg

AFFIDAVIT

STATE OF WEST VIRGINIA

County of Harrison

SS:

Harvey Good and Martin L. Fluharty
being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Raad Supply Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 25th of September, 19 51, and that the well was plugged and filled in the following manner:

SAND OR ZONE RECORD	FORMATION	MATERIAL	MATERIAL		PLUGS USED	CASING	
			FROM	TO		CSG PULLED	CSG LEFT IN
30' and 50' sand	Clay		2700	2556	2" Tub.	2700'	None
	Cement		2556	2546			
Permanent bridge				2140			
Big Injun sand	Clay		2140	2036			
	Cement		2036	1916			
Cut 6-5/8" casing at 1600'							
Cut 6-5/8" casing at 1575'							
					6-5/8"	1575'	324'
Permanent bridge				1245			
Big Dunkard	Clay		1245	1158			
	Cement		1158	1148			
Perforated 8 1/2" casing at 700'; 850'; 750'; 700' and 610'.					8 1/2"	610'	528'
Put in a 2" vent pipe to the surface, with Morning Glory							
Packer in top of the pipe	Clay		610	303			
	Cement		303	293	10"	293'	None
COAL BEAMS	Clay		293	to the surface			
(NAME)					DESCRIPTION OF MONUMENT		
(NAME)					Cement-Size 33x33x10" thick with		
(NAME)					a cement post in center of 6-5/8"		
(NAME)					pipe, extended above cement base		
					3' with inscription RAAD SUPPLY		
					COMPANY, October 1951.		

and that the work of plugging and filling said well was completed on the 8th day of