



Company RICHARD JACKSON  
 Address HAMLIN, W. VA.  
 Farm CONSOLIDATION COAL Co.  
 Tract \_\_\_\_\_ Acres 47 1/2 Lease No. 599  
 \_\_\_\_\_ 1 \_\_\_\_\_ No. 117

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**

Latitude

Longitude



**Topo Location**

7.5' Loc. \_\_\_\_\_ 15' Loc. \_\_\_\_\_  
 \_\_\_\_\_ (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm \_\_\_\_\_

15' Quad \_\_\_\_\_  
(sec.)

7.5' Quad Grant Town

District Paw Paw

**WELL LOCATION PLAT**

County 049 Permit 30759

CONSOLIDATION COAL CO. NO. 1 (117) WELL.

759A  
 Pumpaw District, Marion County, W. Va.  
 By Wilhelm & Jackson, Hamlin, W. Va.  
 Abandoned under permit Mar-.....-A?  
 On 47 acres, on Little Pumpaw Creek.  
 Elevation, 1035' L.  
 Surface and minerals owned by Consolidation Coal Co., Fairmont, W. Va.  
 Drilling commenced Nov. 29, 1927; completed Jan. 28, 1928.  
 Volume, 182,000 cu. ft.  
 Rock pressure, 250 lbs. in 24 hrs.  
 Fresh water at 90', 258', 372', and 1302' (?)  
 10" casing, 434', 8 1/2", 1371' (pulled); 6 1/2", 1701'; 2" tubing, 2557'.  
 Reeter anchor packer, 6 1/2" x 3 x 16, set at 1730-35'.  
 Perf. top, 2231'; bot., 2235'; top, 2541'; bot., 2545'.  
 Casing cemented: 10", 113', 12-13-27.  
 Water, 90', 2 bailers per hour. Water, 245', 3 bailers per hour.  
     Water, 258', 6 bailers per hour. Water, 372', hole full.  
     Water, 1302', 8 bailers per hour.  
 Gas, 1736-1741', 50 M. Gas, 2230-2235', 203 M. Gas, 2300-2303', 40 M. (?)  
 Gas well. Record to Dept. of Mines not dated or stamped.  
 Record to RGT from Mrs. Griffith July 9, 1952. O. F. No. 837.

	Top.	Bottom.
Clay, rock, slate	0	210
Sand	210	255
Mapletown (Sewickley) Coal	255	261
Slate, lime, and sand	261	355
Slate	355	371
Pittsburgh Coal	371	379
Slate and lime	379	590
Sand	590	625
Slate and red rock	625	670
Slate and sand	670	806
Lime	806	829
Slate and shells	829	890
Sand and slate	890	965
Slate and shells	965	1000
Sand and slate	1000	1125
Coal	1125	1129
Slate, shells, and lime	1129	1280
Salt Sand	1280	1440
Slate, shells, and red rock	1440	1500
Lime shells	1500	1575
Red rock, slate, and lime	1575	1625
Slate and red rock	1625	1644
Little Lime	1644	1654
Pencil Cave	1654	1660
Big Lime	1660	1729
Big Injun Sand	1729	1746
Red rock and lime	1746	1757
Big Injun Sand	1757	1853
Slate, shells, lime, and sand	1853	2230
Gantz Sand	2230	2270
Fifty-foot Sand	2270	2325
Shells	2325	2345
Thirty-foot Sand	2345	2387
Red rock	2387	2392
Sand and shells	2392	2453
Next line did not print		
Total depth	2557'	(?) write for c/n



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

837

WELL RECORD

Permit No. MAR-759-A

Oil or Gas Well \_\_\_\_\_  
(KIND)

Company Wilhelm & Jackson  
 Address Henlin, W. Va.  
 Farm The Consolidation Coal Co. Acres 47  
 Location (waters) Little Paw Paw Creek  
 Well No. 1, Serial 117 Elev. 1035'  
 District Paw Paw County Marion  
 The surface of tract is owned in fee by The Consolidation Coal Company Address Fairmont, W. Va.  
 Mineral rights are owned by Same Address \_\_\_\_\_  
 Drilling commenced November 29, 1927  
 Drilling completed January 23, 1928  
 Date Shot From \_\_\_\_\_ To \_\_\_\_\_  
 With \_\_\_\_\_  
 Open Flow /10ths Water in \_\_\_\_\_ Inch  
 /10ths Merc. in \_\_\_\_\_ Inch  
 Volume 182,000 Cu. Ft.  
 Rock Pressure 250 lbs. 24 hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water 90' 253' 372' feet 1302' feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			Water Anchor
10			Size of
8 1/4	1371'	1371'	6-5/8"x3"x26"
6 5/8	1701'	1701'	Depth set 1730'-35'
5 3/16			
3	2557'	2557'	Perf. top 2231'
2			Perf. bottom 2235'
Liners Used			Perf. top 2541'
			Perf. bottom 2545'

CASING CEMENTED 10" SIZE 123 No. Ft. 12/13/27 Date

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Clay, rock, slate			0	210	Water 90' -	2 bailers pr. hr.	
Sand			210	255	Water 245' -	3 bailers per hr.	
Waplestown Coal			255	261	Water 253' -	6 bailers per hr.	
Slate, lime and sand			261	355			
Slate			355	371			
Pittsburgh Coal			371	379	Water 372' -	hole full	
Slate and lime			379	590			
Sand			590	625			
Slate and red rock			625	670			
Slate and sand			670	806			
Lime			806	829			
Slate & shells			829	890			
Sand and slate			890	965			
Slate and shells			965	1000			
Sand and slate			1000	1125			
Coal			1125	1129			
Slate, shells - lime			1129	1280			
Salt Sand			1280	1440	Water 1302' -	8 bailers per hr.	
Slate, shells and red Rock			1440	1500			
Lime Shells			1500	1575			
Red Rock slate and lime			1575	1625			
Slate and red rock			1625	1644			
Little Lime			1644	1654			
Pencil Cave			1654	1660			
Big Lime			1660	1729			
Big Injun			1729	1746	Gas 1736'-1741' -	50 cu. ft.	
Red Rock & Lime			1746	1757			
Big Injun			1757	1853			
Slate, shells, lime & sand			1853	2230			
ant. Sand			2230	2270	Gas 2230'-2235' -	203 cu. ft.	
Fifty-Foot Sand			2270	2325	Gas 2300'-2303' -	40 cu. ft.	
Shells			2325	2345			
Thirty-Foot Sand			2345	2387			
Red Rock			2387	2392			
Sand & shells			2392	2453			