

Latitude 39° 40'

Longitude 80° 05'

M. E. & PINKEY EDDY  
60  $\frac{5}{8}$  AC.

M. LEBLOND  
30 AC.

M. J. TOOTHMAN  
16 AC.

S. C. GRUBB HRS.  
75 AC.

W. W. WALKER  
84 AC.

MARGARET A. TENNANT  
162 AC.

M. E. ROBINSON  
73 AC.

CAROLINE NEPTUNE  
30 AC.

J. McCRAY  
29 AC.

MAY 15 1961

New Location...   
Drill Deeper...   
Abandonment...

Map Sh. 16; N-10, E-25; F.B. 1135, P. 35-36

Company HOPE NATURAL GAS CO  
 Address CLARKSBURG, W. VA.  
 Farm W. W. WALKER  
 Tract \_\_\_\_\_ Acres 84 Lease No. 14495  
 Well (Farm) No. \_\_\_\_\_ Serial No. 1218  
 Elevation (Spirit Level) 1316'  
 Quadrangle BLACKSVILLE  
 County MARION District PAW PAW  
 Engineer Guy H. Bradley  
 Engineer's Registration No. 2425  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date 10-31-60 Scale 1"=40'

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION  
CHARLESTON

WELL LOCATION MAP  
FILE NO. MAR-901-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
- Denotes one inch spaces on border line of original tracing.

K&E 150 IMPERIAL TRACING CLOTH T.M. W.W. WALKER No. 1218 HOPE N.G. Co. MAR-901-A 3945



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

934

Quadrangle BLACKSVILLE

Permit No. WV 901-A

WELL RECORD

Oil or Gas Well Gas

Company Hope Natural Gas Company  
Address Clarksburg, W. Va.  
Farm W. W. Walker Acres 84  
Location (waters) \_\_\_\_\_  
Well No. 1218 Elev. 1316'  
District Paw Paw County Marton  
The surface of tract is owned in fee by \_\_\_\_\_  
Address \_\_\_\_\_  
Mineral rights are owned by \_\_\_\_\_  
Address \_\_\_\_\_

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer <u>8x10 B.H. set 1598</u>
18			Size of <u>6x8 B.H. 1868</u>
10	<u>1017'6"</u>	<u>1017'6"</u>	<u>5-3/16 Shoe-2785</u>
8 1/4	<u>1598'</u>	<u>1598'</u>	Depth set <u>10" shoe</u>
6 1/2	<u>1868'1"</u>	<u>1868'1"</u>	<u>2x5 B. set 2924'10"</u>
5 3/16	<u>2800'</u>	<u>2800'</u>	Perf. top _____
3			Perf. bottom _____
2	<u>3059'</u>	<u>3059'</u>	Perf. top _____
Liners Used			Perf. bottom _____
<u>2" Perf.</u>	<u>12'2"</u>	<u>12'2"</u>	

Drilling commenced \_\_\_\_\_  
Drilling completed \_\_\_\_\_  
Date Shot 5-10-21 From \_\_\_\_\_ To \_\_\_\_\_  
With 20 qts. in 5th. sand  
Open Flow /10ths Water in \_\_\_\_\_ Inch  
/10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED No record  
WELL FRACTURED No record

CASING CEMENTED	SIZE	No. Ft.	Date
COAL WAS ENCOUNTERED AT		FEET	INCHES
		FEET	INCHES
		FEET	INCHES

RESULT AFTER TREATMENT \_\_\_\_\_  
ROCK PRESSURE AFTER TREATMENT \_\_\_\_\_  
Fresh Water \_\_\_\_\_ Feet Salt Water \_\_\_\_\_ Feet

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Pitts. Coal			634	640			
Salt sand			1460	1699	Water	1580-8-1593	
Maxon sand			1800	1825			
Injun sand			1948	2084	Gas	2073	
Gantz sand			2425	2435			
50 ft. sand			2509	2543			
30 ft. sand			2565	2570			
Stray sand			2780	2794			
Gordon sand			2841	2860			
4th. sand			2920	2939			
5th. sand			3008	3042	Gas	3012-7; 3022-4	
Total Depth				2356			
Deeper				3024			
Deeper				3142			
Filled up to				3049			



April 26, 1961  
*Jack Pauley*  
H. N. G. Co.

AUG 2 1961