

LATITUDE 39 35

45S  
06W

LONGITUDE 80 22 30

7'5 OGIS topo location

7.5' loc .45S 15' loc \_\_\_\_\_  
                  .06W (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm ALFRED KENDALL 10

Quad GLOVER GAP

County MARION

District MANNINGTON

WELL LOCATION MAP

File No. 70122

Farmington District, Marion County, W. Va.

By.....

A. &amp; H. Drilling Co., Contractor.

Elevation.....

10" casing, 200' (pulled); 8 1/2", 1508' (pulled); 6 1/2", 2380'; 5", 3050';  
2" tubing, 3165'.

Nov. 1, 1918, Drilled deeper.

Bottom of 30-Ft. Sand, 3157'.

Nov. 1, 1918, Shot with 10 gts.

Pulled and plugged Oct. 1, 1924.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil &amp; Gas Co.

|  | Top. | Bottom. |
|--|------|---------|
| Pittsburgh Coal                        | 1130 | - ....  |
| Little Burkard Sand                    | 1528 | - 1548  |
| Big Burkard Sand                       | 1598 | - 1670  |
| Gas Sand                               | 1810 | - 1875  |
| First Salt Sand                        | 1958 | - 2000  |
| Second Salt Sand                       | 2044 | - 2099  |
| Little Line                            | 2330 | - 2346  |
| Big Line                               | 2352 | - 2438  |
| Big Injun Sand                         | 2438 | - 2586  |
| Fifty-foot Sand                        | 3038 | - 3103  |
| Thirty-foot Sand (oil, 3130 and 3165') | 3135 | - ....  |
| Total depth (first drilling)           |      | 3155    |
| DRAINED Nov. 1, 1918:                  |      |         |
| Bottom of Thirty-foot Sand             | .... | - 3157  |
| Campbell Run Sand (oil, 3290')         | 3258 | - ....  |
| Total depth (second drilling)          |      | 3290    |