

LATITUDE 39 35

.90S
.06W

LONGITUDE 80 22 30

7'5" OGIS topo location

7.5' loc .90S 15' loc _____
 .06W (calc.) _____

Company _____

Farm ON KOEN 2

Quad GLOVER GAP

County MARION

District MANNINGTON

WELL LOCATION MAP

File No. 70128

Hamington District, Marion County, W. Va.

By Eastern Petroleum Co.

On 112½ acres.

Elevation.....

Drilling commenced Oct. 9, 1921; completed Dec. 20, 1921.

10" casing, 194' (pulled); 8½", 1464' (pulled); 6", 2220'; 2" tubing, 2937'

Tubing record, 1¼" jts. of 2" tubing. 18' of anchor, with 40 - ½" holes.

Top of packer, 2895'. Bottom of packer, 2898'. Size, top of packer, 3½".

Bottom of tubing, 2916'. Tubing tallied 2937'. Size of packer, 6".

Block pressure, 30 min., 360 lbs.; 1 hr., 390 lbs.

Jan. 1925, well shot and cleaned.

Feb. 10, 1925, pulled and plugged hole. Not enough gas for a test.

Well plugged back to 2916'.

Shot Dec. 24, 1921, with 15 qts.; top of shot, 2903½'; bottom, 2913½'.

6" casing, 1450' pulled, 758' left in (when abandoned).

Abandoned Feb. 19, 1925. (Feb. 27)

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

	Top.	Bottom.
Conductor	0	15
Native coal	839	844
Pittsburgh Coal	939	945
Big Buckard Sand	1424	1474
First Salt Sand	1741	1763
Second Salt Sand	1805	1846
(water, 1898', 6 double sections bailers per hour)		
Little Line	2165	2180
Pencil Cove	2180	2185
Big Line	2185	2265
Big Injun Sand	2265	2435
Fifty-foot Sand (gas, 2900'; gas, 2908', 14/10 Water through 2")	2895	2934
Thirty-foot Sand	2993	3011
Gordon Stray Sand	3106	3144
Gordon Sand	3150	3160
Fourth Sand	3175	3187
Fifth Sand (gas, 3237-3248')	3212	3223
Total depth		3252