

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOL PENNSYLVANIA COAL CO., LLC.
Coal Operator or Owner
1525 PLEASANT GROVE RD. CLAYSVILLE, PA 15323
1000 CONSOL ENERGY DRIVE CANONSBURG, PA 15317
Address
CONSOL PENNSYLVANIA COAL CO., LLC.
Coal Operator or Owner
1525 PLEASANT GROVE RD. CLAYSVILLE, PA 15323
1000 CONSOL ENERGY DRIVE CANONSBURG, PA 15317
Address
RIGGGLE, RALPH CURTIS
Lease or Property Owner
RD 4, BOX 247 CAMERON, WV 26033
Address

CONSOL PENNSYLVANIA COAL CO., LLC.
Name of Well Operator
1525 PLEASANT GROVE RD. CLAYSVILLE, PA 15323
Complete Address
MAJORSVILLE, WV-PA 7.5'
Well Location
WEBSTER
District
MARSHALL
County
5006
Well No.
RIGGGLE, RALPH CURTIS
Farm

STATE INSPECTOR SUPERVISING PLUGGING _____

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

ROBERT STEEL and **KEVIN WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consol Pennsylvania Coal Company, LLC. Well Operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 13th day of June, 2011 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Removed 7" casing from the surface to 756'. Left 1082' of 7" casing in the hole from 765' to 1847'. Cut remaining 7" casing at 1746', 1646', 1546', 1446', and 1346'. Perforated 7" casing with 6 shots each at the following depths; 1300', 1200', 1100', 1000', 900' and 800'. Removed 8 5/8" casing from surface to 56'. Left 1305' of 8 5/8" casing from 56' to 1361'. Perforated remaining 8 5/8" casing with 6 shots each at the following depths 1300', 1200', 1100', 1000', 900', and 800'. Cemented bottom hole from 1942' to 800' with 155 sacks of Expandable Cement and 35 sacks of Thixotropic Cement with green dye. Cut 8 5/8" casing at 458', 235', 94', and 71'. Sand cut 8 5/8" and 10 3/4" casing thru Pittsburgh Coal 709' to 715'. Sand cuts were made at the following depths; 717', 715', 713.5, 711', 710', 709', 707' and 657'. Cemented hole from 1942' to surface as follows: From 1942' to 915' with Expandable Cement. From 915' to 609' with 95 sacks of Thixotropic Cement with green dye. From 609' to surface with Expandable Cement. A total of 400 sacks of cement were used to fill the hole from 1942' to surface. Cement did circulate at the surface.	10 3/4" Casing 8 5/8" Casing 7" Casing	0' 56' 765'	746' 1305' 1082'	
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	(709' - 715')	2x2 flat plate w/ company name, well number, permit number and date cemented stated on flat plate. Well marker will be buried 36" beneath the surface.		

RECEIVED
Oil and Gas
SEP 26 2011
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 1st day of July, 2011

And further deponents saith not.

Douglas Dinger
CPCC - PROJECT ENGINEER

Robert Steel
Robert Steel
Kevin S. Wright
Kevin S. Wright 09/30/2011

Sworn to and subscribed before me this 12th day of September, 2011

My commission expires:

June 1, 2015

NOTARIAL SEAL
JACQUELINE L SHRIVER
Notary Public
DUNKARD TWP., GREENE COUNTY
My Commission Expires Jun 1, 2015

Jacqueline L Shriver
Notary Public

Permit No. 47-051-00338-P
Well No. 5006