STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

51-006469

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041

Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS

Coal Operator or Owner 6126 ENERGY DRIVE MOUNDSVILLE, WV 26041 Address

CHARLES ALBERT WITSBERGER!

Lease or Property Owner 250 DRY RIDGE ROAD CAMERON, WV 26033

Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS

Name of Well Operator

6126 ENERGY DRIVE MOUNDSVILLE, WV 26041

Complete Address MAJORSVILLE. WV 7.5'

Well Location

WEBSTER

District

MARSHALL

County

SGW-148 Well No.

CHARLES ALBERT WITSBERGER II

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MARK WILSON and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 29th day of August, 2014 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing / Tubing Size	Casing Pulled	Casing Left In
	<u> </u>	42 2/01 Coning		450
Cleaned 3 ½" hole from Surface to 1866'. Left 1984' of 4 ½" casing in the hole from Surface to 1984'. Cut remaining 4 ½" casing at the following depths: 1835', 1735', 1635', 1535', 1435', 1336', and 734'. Perforated remaining 4 ½" casing with 6 Shots at the following depths: 1592', 1496', 1396', 1196', 1097', and 997'. Cemented bottom hole plug from 1866' to 895' with 55 sacks of Expandable Cement. Left 1788' of 7" casing in the hole from Surface to 1788'. Left 1200' of 8 5/8" casing in the hole from Surface to 1200'. Left 620' of 10 ½" casing in the hole from Surface to 620'. Jet cut 4 ½", 7", 8 5/8", and 10 ½" casings at the following depths: 901', 851', 800', 750', 701', 700', 698', 696', 694', 692', 690', 688', 592', and 542'. Jet cut 4 ½", 7", 8 5/8", and 10 ½" casings through the Pittsburgh Coal seam from 690' to 695'. Left 154' of 13 3/8" conductor casing in the hole from Surface to 154'.		13 3/8" Casing	0,	154'
		10 %" Casing	O,	620'
		8 5/8" Casing	O,	1200'
		7" Casing	O,	1788'
		4 1/2" Casing	0,	1984'
		Offic	Receiv e of Oi	ed & Gas
Cemented hole from top of bottom hole plug at 895' to surface as follows:		(CT 07 2	014
From 895' to 590' with 35 sacks of Thixotropic Cement with green dye. From 590' to the surface with 50 sacks of Expandable Cement. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh Coal	690' to 695'	77" of 7" casing w/ company name, well number,		
(Name)		permit number and date cemented stated on 7*		
(Name)		casing .Well marker attached to the cement		
(Name)		plug at ground level.		

... and that the work of plugging and filling said well was completed on the 15th day of September, 2014

And further deponents saith not.

Sworn to and subscribed before me this 6

day of October 2014

My commission expires: 1/4/23



Official Seal

Ty Public, State Of West Virginia Well No. 47-051-00846-P

Well No. SGW-148

World American Drivers LLC

To Gurn Spring Rd

Morgantown W 26505

Morgantown W 26505

10/10/2014