



Company COLUMBIAN CARBON CO.  
 Address BOX 873 CHARLESTON WVA.  
 Farm MINGO LAND CO.  
 Tract \_\_\_\_\_ Acres 5575.07 Lease No. C.3085  
 Well (Farm) No. 1 Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 1272.0 1200'  
 Quadrangl. GILBERT-8-5-282 W-452  
 County MINGO District STAFFORD  
 Engineer C. Q. Branham  
 Engineer's Registration No. 683  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date 5/12/47 1" = 2640

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. MIA-134

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

3-0-27  
 Dec 1947

*Study of surface map of Mingo Co. West Virginia*

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Min 134  
Gilbert Quad.  
Company  
Address  
Farm  
Location  
Well No.  
District  
Surface

Columbian Carbon Company  
Box 878, Charleston 23, W.Va.  
Mingo Land Company A 5575.07  
Turkey Creek  
1 GW 954 Elev. 1272. ' G  
Stafford Mingo County  
Mingo Land Company,  
206 1st Htg. Nat'l Bank  
Huntington, W.Va.

Dry Hole  
CASING & TUBING

16" 20'6" Pld.  
13 3/8 48# 476'9 Pld.  
8 1/2 24# 2023'1 30'6  
7" 23# 3176'4 Pld.  
Midget B.H. Packer  
Size 8 5/8"  
Depth 2015' SLM

Mineral Same  
Commenced 5-3-47  
Completed 2-20-48  
Date shot 12-10-47  
Depth 3671-SLM to 3686'  
SLM 235# gelatin

Coal at 28' 12"  
1' 20' 72"

Volume Dry Hole  
Fresh Water 29' H.F.

Sandy Top Soil	0	5	Corniferous Lime	5599 DLM	
Sand Rock	5	28		5604' SLM	5682
Coal	28	29	Sand (5620' DLM-5625 SLM)	5682	5687
Sand	29	51	Lime	5687	5725
Slate & Shells	51	164	Total Depth		5725
Sand	164	196			
Slate & Shells	196	240	Dry Hole - plugged and abandoned 3-1-48		
Sand	240	293			
Slate & Shells	293	361	Gas 2807' show		
Sand	361	506	Gas 2917' show		
Slate & Shells	506	561	Gas 3657' show		
Sand	561	672	Gas 5480' show		
Slate & Shells	672	714			
Sand	714	730	Cement Record:		
Slate & Shells	730	855	5-28-47 13 3/8" casing, ran 12 bags		
Sand	855	998	aquegel and 1 bale fibertex. No cir-		
Slate & Shells	998	1020	culatation, or returns.		
Hard Sand	1020	1240			
Slate & Shells	1240	1312	9-5-48 8 5/8" casing, ran 28 bags		
Sand	1312	1515	aquegel and 1 bale fibertex. No		
Slate	1515	1520	circulation or returns.		
Coal	1520	1520			
Lime Shells	1526	1556	11-18-47 7" casing, ran w/jacks.		
Sand	1556	1653			
Slate & Shells	1658	1665	G.C.Co. Crew		
Red Rock	1665	1695			
Slate & Shells	1695	1735			
Red Rock	1735	1771			
Lime Shells	1771	1784			
Slate & Shells	1784	1834			
Sand	1834	1868			
Slate & Shells	1868	2010 DLM			
2015' SLM-2017 DLM		2008 SLM			
Sand	2008	2112			
Slate & Shells	2112	2143			
Red Rock	2143	2147			
Sand	2147	2157			
Slate & Shells	2157	2190			
Sand	2190	2198			
Slate & Shells	2198	2248			
Sand	2248	2389			
Red Rock	2389	2415			
Slate & Shells	2415	2650			
Big Lime	2650	3053			
Big Injun Sand	3053	3113			
Lime	3113	3185			
Slate & Shells	3185	3609			
Black Shale	3609	3632 DLM			
Berea Grit	3632 DLM	3638' SLM			
3738' DIM-3744' SLM	3638 SLM	3670 SLM			
Slate & Shells	3670 SLM	5480			
Black Shale	5480	5599 DLM			
		5604 SLM			

3632  
3113  
577

5604 5682  
1272 1272  
-4332 -4410