

FORM WR-38 (Affidavit of Plugging)

September 08, 1988

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND CAS WELLS DIVISION



DIVISION OF OIL & GAS TO DEPARTMENT OF ENERGY

Permit No. 47-061-0836-P

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Consolidation Coal Company		Consolidation Coal Company		
Coal Operator or Owner P. O. Box 1314, Morgantown, WV 26507-1314		Name of Well Operator P.O. Box 1314, Morgantown, WV 26507-1314		
Address		Complete Address		
Consolidation Coal Company		Ju	ne 05,	19 87
Coal Operator or Owner		WE:	LL AND LOCATION	
P. O. Box 1314, Morgantown, WV 26507-1314				District
Address				1
Glayds Yost			Monongalia	County
Lease or Property Owner Route 2, Box 335C, Fayetteville		WELL NO. Con		
Address		WELL NO.		7
		Gladys Yost		Farm
STATE INSPECTOR SUPERVISING PI	LUGGING Don Elli	s, Fairmont,	WV 26554	
	AFFIDAV	ır '		
				•
STATE OF WEST VIRGINIA, County of Harrison	ss:			
Calvin C. Lofton		and George	R Core	
being first duly sworn accord				nood in the
work of plugging and filling	oil and gas well:	s and were em	ployed by Conso	nceu in the lidation
'Coal Company , well o	perator, and par	ticipated in	the work of pluggi	ng and fill-
ing the above well, that said	work was commend	ced on the	18th day of May	ng und 1111
$19 \frac{87}{}$, and that the well was	as plugged and f	illed in the	following manner:	
Sand or Zone Record	Filling Mate	rial	Plugs Used	Coolne
		LIAI	_	Casing
Formation			Size & Kind	CSG CSG PULLED LEFT IN
Pulled cable tool jars of	ut of hole at 52	5 feet and		
a string of wood. Cleaned 9 cleaned 7 7/8 hole from 497 f	//8 Inch hole to	497 feet,		
protection string as follows:	· · · · · · · · · · · · · · · · · · ·			
tubing followed by 1,193.33 f	eet of 4½ inch c	asing. Latch		
down plug at 1,163.02 feet.	Float valve at l	.193.33 feet	19 01	TIPS VI
Circulated cement to surface	as follows: Pum	ped 700 sacks	12	1.131
of poz mix followed by 180 sa	cks of expanding	cement.	1011	41 63
Displaced cement to 1,163.02	feet with water	. Let set,	I-I VUN	10
bailed dry.				19/h
Total Depth: 1,510.04 fe	et.		E	<i> </i>
			N. A	
			That is	6/87
Coal Seams			Description of	Monument
(Name) Pittsburgh	1,000 feet to	1 009 feet	5 feet of 4½ inch	
(Name)	1,000 1000 1000	1,000 1001	with plaque stat	
(Name)			Consol #3885	
(Name)			47-061-0836-P	* []
and that the work of plu	gging and filling	g said well w		e 27th day
of <u>May</u> , 19			D 4	
And further deponents sa	ith not.	H	R House	
Sworn to and subscribed befor	e me this OS	, , , , , , ,		
Sworn to and subscribed before me this 05 day of June , 19 87				
		J. K	· Couratt	1
		V	Notary Public	JUL 6 198
My commission expires:				20F () 138