

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26582
Address

CONSOLIDATION COAL COMPANY
Name of Well Operator
1 BRIDGE ST. MONONGAH, WV 26582
Complete Address
JAKES RUN
Well Location
CLAY
District
MONONGALIA
County
J W WRIGHT #2
Well No.
W WRIGHT
Farm

DOWNEY HAROLD FOX ESTATE
Lease or Property Owner
104E GENESSEE ST. PITTSBURGH PA 15223-1114
Address

STATE INSPECTOR SUPERVISING PLUGGING

[Signature] *oil & Gas Inspector*
AFFIDAVIT ~~of Plugging and Filling~~

No cement plug across Elevation

STATE OF WEST VIRGINIA,
County of **MONONGALIA** ss:

ALEX WILSON and DENNIS YOST being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 24TH day of October, 2013 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
	<p>Pulled 1900' of wooden sucker rods. Pulled 1900' of 2 3/8" tubing. Pulled 714' of 5 1/2" casing. Made perforations in 5 1/2" with 3 shots at each of the following depths; 1800', 1700', 1600', 1500', 1400', 1300', 1200', 1100', 1000', 900', and 800'. Pulled 300' of 7". Made cuts in 7" at each of the following depths; 700', 600', 590', 580', 500', and 400'.</p> <p>Cemented hole from 1900' back to surface as follows;</p> <p>Cemented plug from 1900' to 1800' with 20 sacks of portland cement. From 1800' to 714' with Aqualgel plug (drilling mud). From 714' to 450' with 35 sacks of expandable cement. From 450' to 300' with Aqualgel plug (drilling mud). From 300' to surface with 115 sacks of portland cement. Cement did circulate.</p>	<p>Wooden Rods 2 3/8" 5 1/2" 7"</p>	<p>1900' 1900' 714' 300'</p>	<p>Unknown Unknown Unknown Unknown</p>
Coal Seams		Description of Monument		
Pittsburgh	596' - 586'	2' x 2' x 1/4" flat plate with Consolidation coal company, API # 47-6100856, Well # J W Wright #2, and date plugged of 12-14-13, buried at plow depth of 3'		
(Name)				
(Name)				
(Name)				

... And that the work of plugging and filling said well was completed on the 14th day of December, 2013

And further deponents saith not.

Alex B. Wilson

Received 06/06/2014
Office of Oil & Gas
JUN 05 2014