

STATE OF WEST VIRGINIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
OFFICE OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Husk, Ralph Operator Well No.: F2- 567

LOCATION: Elevation: 1,114' Quadrangle: Blacksville
District: Clay County: Monongalia
Latitude: 2,839 Feet South of 39 Deg. 42 Min. 30 Sec.
Longitude: 3,103 Feet West of 80 Deg. 12 Min. 30 Sec.

Well Type: OIL GAS

Company: Eastern Associated Coal LLC Coal Operator: Eastern Associated Coal LLC
1044 Miracle Run Road or Owner 1044 Miracle Run Road
Fairview, WV 26570 Fairview, WV 26570

Agent: Matthew L. Bonnell Coal Operator or Owner _____

Permit Issued Date: December 05, 2014

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of Monongalia ss:

X Eric Dale Chisler and X Chris Thomas being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the above named well operator, and participated in the work of plugging and filling the above well, and Gayne Knitowski, Oil and Gas Inspector representing the Director, say that said work was commenced on the 5th day of January, 2015, and that the well was plugged and filled in the following manner:

TYPE	FROM	TO	PIPE REMOVED	LEFT
Drilled with a 12 1/4" cone bit down to 600'. Drilled with a 9 3/4" mill down to 713'. Drilled with an 8" mill down to 768'. Drilled with a 7 7/8" mill down to 825'. Drilled with a 7 5/8" bit down to 842'. Drilled with a 6 1/2" mill down to 1121'. Drilled with an 6 1/4 tricone bit down to 1,170'.				
Ran logs with Century Wireline Services. Based on the logs the Pittsburgh coal seam is 759'-766'. The well deviated 4.4' at the coal seam. Based on the logs, there was no casing in the Pittsburgh coal seam.				
There is a bottom hole cement plug from 1,170 up to 990'. Then they set an expanding cement plug from 990' to 630'. Then from 630' to surface it was filled with cement.				
There were 540 sacks of Portland and 160 sacks of expanding cement used to plug the well.				

Description of monument: 4 1/2" Pipe with metal plate, API #, and date plugged and that the work of plugging and filling said well was completed on the 13th day of February 2015.

And further deponents saith not. X Eric Dale Chisler
X Chris Thomas

Sworn and subscribe before me this 13th day of Feb.

My commission expires: April 29, 2019
J Ann Moore
Notary Public

Oil and Gas Inspector: Gayne J Knitowski 2/18/2015

