

STATE OF WEST VIRGINIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION  
OFFICE OF OIL AND GAS  
AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Fisher, Aaron Operator Well No.: F2- 564

LOCATION: Elevation: 1,147' Quadrangle: Blacksville  
District: Clay County: Monongalia  
Latitude: 3,729 Feet South of 39 Deg. 42 Min. 30 Sec.  
Longitude: 3,508 Feet West of 80 Deg. 12 Min. 30 Sec.

Well Type: OIL X GAS \_\_\_\_\_

Company: Eastern Associated Coal LLC Coal Operator: Eastern Associated Coal LLC  
1044 Miracle Run Road or Owner 1044 Miracle Run Road  
Fairview, WV 26570 Fairview, WV 26570

Agent: - Matthew L. Bonnell Coal Operator \_\_\_\_\_  
or Owner \_\_\_\_\_

Permit Issued Date: January 30, 2015

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of Monongalia ss:

x Eric Dale Chisler and x Gary C Thomas being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by the above named well operator, and participated in the work of plugging and filling the above well, and Gayne Knitowski, Oil and Gas Inspector representing the Director, say that said work was commenced on the 25th day of February, 2015, and that the well was plugged and filled in the following manner:

TYPE	FROM	TO	PIPE REMOVED	LEFT
	Drilled with a 12 1/4" cone bit down to 695'. Drilled with a 9 5/8" cone bit down to 1,200', Drilled with a 6 1/4" cone bit down to 1,500'.			
	Ran logs with Century Wireline Services. Based on the logs the Pittsburgh coal seam is 797'-804'. The coal seam deviated 4.1' at the coal seam. There was 10" casing from 695' down to 1,170', and 8" casing from 1,200' down to 1,500'. The 8" casing was cut at 1,350' and 1,500'. An attempt was made to pull the 8" casing. The Jars went off two times. Then they were not able to set the 8" spear. Then they attempted to pull the 10" casing. First they cut the 10" casing at 760', 860', 960' and 1,060'. The jars went off once. Then the 10" spear would not set again. Both casings shot by Timco logging at the coal seam and every 50 above and below.			
	There is a bottom hole cement plug from 1,500' up to 1,020'. Then they set an expanding cement plug from 1,020' to 690'. Then from 690' to surface it was filled with cement.			
	There were 640 sacks of Portland and 160 sacks of expanding cement used to plug the well.			

Description of monument: 4 1/2" Pipe with metal plate, API #, and date plugged and that the work of plugging and filling said well was completed on the 12<sup>th</sup> day of March 2015.

And further deponents saith not. x Eric Dale Chisler

x Gary C Thomas

Sworn and subscribe before me this 12<sup>th</sup> day of March

My commission expires: April 29, 2019

Jo Ann Moore  
Notary Public



OFFICIAL SEAL  
STATE OF WEST VIRGINIA  
NOTARY PUBLIC  
Jo Ann Moore  
788 Thomas Run Road  
Blacksville, WV 26521  
My Commission Exp. April 29, 2019

Oil and Gas Inspector: Gayne J Knitowski 3/13/2015