

LATITUDE 39° 45' 00"

LONGITUDE 80° 51' 08"

LONGITUDE

7.5'

7.5 OGIS topo location

7.5' loc 2.77S
0.82W

15' loc 2.77S
(calc.) 0.82W

Company _____

Farm _____

Quad Wadestown

County Monongahela

District Battelle

WELL LOCATION MAP

File No. 061 - 46A

Battelle District, Monongalia County, W. Va.

By South Penn Oil Co., P. O. Drawer 1255, Pittsburgh, Pa.

On 67 acres, surface and mineral rights owned by Mrs. Martha Taylor, 422 Grand St., Morgantown, W. Va.

Elevation, 1150' L.

10" casing, 1150'; 8", 2035'; 6-5/8", 1872'; 5-3/16", 2101'.

Coal was encountered at 755-762'.

1/2" x 1/2" liner.

Abandonment reported to Dept. of Mines May 7, 1932.

Well was shot April 18, 1907, with 20 qts.

Oil well.

	Top.	Bottom.
Pittsburgh Coal	755	- 762
Big Injun Sand	2130	- 2295
50Ft. Sand	2765	- 2815
Campbell's Run Sand	3033	- 3053
Gordon Sand (1st pay, oil, 3100')	3083	
Total depth		3113

MON-46-A

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

PRELIMINARY DATA SHEET NO. 1

File No. _____ Well No. 8
COAL FIRM OIL COMPANY Company of F. S. POWER 1888, Pittsburgh, Pa.
 on date A. J. 1924 Date

containing 87 acres Location _____
Stonelle located in Monongalia County, West Virginia

The surface of the above tract is owned in fee by Mrs. Martha Taylor
428 Canal St., Morgantown, W. Va. address, and the mineral rights are owned by
Mrs. Martha Taylor of 428 Canal St., Morgantown, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under
 permit No. _____ issued by the West Virginia Department of Mines, Oil and Gas Section,

at _____
 Elevation of surface casing of well 1100' Right
 _____ barometric

The number of feet of the different sized casings used in the well

Size	Material	Length	Weight	Notes
1100	Steel	20'	also, 2200	also, Wood conductor
8000	Steel	42"	also, 2200	also, 2 1/2" / 100' steel cap
1270	Steel	3-4/8"	also, 2200	also, steel cap
		gauge of		also, set of
		gauge of		also, set of
		size casing perforated at	feet to	feet
		size casing perforated at	feet to	feet
Coal was encountered at	<u>750</u>	feet; thickness	<u>65</u>	feet; and at
bit; thickness		feet; and at	feet; thickness	feet
Spuds were used as follows:	also details	<u>42" X 4"</u>		

Drilled by May 9, 1924

May 9, 1924

Approved COAL FIRM OIL COMPANY

Shaner

SEVEN FIVE OIL COMPANY, _____ Company
 P. O. BOX 1888, _____
 Pittsburgh, Pa. _____ Address

COMPLETION DATA SHEET
 No. 2
 FORMATION RECORD

Well No. U- A. J. Ritz Boire Pass.

Zone	Color	Character	Oil Cut or Water	Top	Bottom	Thickness	Total Depth	Remarks
Pittsburgh	Coal			708	708			
Big Injun				8120	2925			
Fifty Feet				2705	2815			
Cow Run				2425	2425			
Garden				2025				
Garden				8120				let pay
Total Depth							8115	

Oil well completed on (4/12-1928, -22-426) - Date well worked on _____

Oil flow rate at _____ gals per hour
 Daily flow rate at _____

Producing _____
 Oil rate _____

Day 7, 1928. _____

SEVEN FIVE OIL COMPANY,
 Approved by *J. H. H. H.* SUPERINTENDENT

NOTE: All bottom formations must be noted as indicated above and all intervals cut off and gas marks must be recorded when they appear. This report should be made to the owner of the well and the owner's name and address should be given.

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

The Dunbar Valley Bank,
Blacksville, W. Va.

SOUTH PINE OIL COMPANY
F. S. Dwyer 1000, Pittsburgh, Pa.
AUGUST 16, 1932
Well and Location
Bathalia District
Monongalia County
Well No. 8
L. J. Eddy Dwyer

AFFIDAVIT

STATE OF WEST VIRGINIA
County of Monongalia)
F. S. Dwyer

being that duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by South Pine Oil Company and participated in the work of plugging and filling the above well, that said work was commenced on the 1st day of August, 1932, and that the well was plugged and filled in the following manner:

From 0' to 100' was plugged with 2 1/2" cement. From 100' to 150' was plugged with 2 1/2" cement. From 150' to 200' was plugged with 2 1/2" cement. From 200' to 250' was plugged with 2 1/2" cement. From 250' to 300' was plugged with 2 1/2" cement. From 300' to 350' was plugged with 2 1/2" cement. From 350' to 400' was plugged with 2 1/2" cement. From 400' to 450' was plugged with 2 1/2" cement. From 450' to 500' was plugged with 2 1/2" cement. From 500' to 550' was plugged with 2 1/2" cement. From 550' to 600' was plugged with 2 1/2" cement. From 600' to 650' was plugged with 2 1/2" cement. From 650' to 700' was plugged with 2 1/2" cement. From 700' to 750' was plugged with 2 1/2" cement. From 750' to 800' was plugged with 2 1/2" cement. From 800' to 850' was plugged with 2 1/2" cement. From 850' to 900' was plugged with 2 1/2" cement. From 900' to 950' was plugged with 2 1/2" cement. From 950' to 1000' was plugged with 2 1/2" cement.

Description of cement:

and that the work of plugging and filling said well was completed on the 17th day of August, 1932.

And further depose that on

Done in and subscribed before me this 17th day of August, 1932.

My Commission expires
Jan. 1, 1933

L. J. Eddy
Notary Public