



- LEGEND
- Center
 - 1/4 Acre
 - 5 Acre Block
 - 1/2 Acre
 - 1/4 Acre
 - 1/2 Acre
 - 1/4 Acre
 - 1/2 Acre
 - 1/4 Acre
 - 1/2 Acre

ENGINEERS CERTIFICATE

I, the undersigned, hereby certify that the above Survey and plans are the representation to the best of my knowledge and belief, prepared by me or by an assistant of the Surveyors of West Virginia.



Witness my hand and the Surveyors hand and seal this 25th day of February, 1908.

Clay District, Monongalia County, W. Va.

By Hope Construction & Refining Co., 445 W. Main St.,
Clarksburg, W. Va.

On 10 acres, surface owned by Wm. Shuman, Blacksville, W. Va.,
and mineral rights by W. J. Eddy Heirs, Mathew Eddy,
Fairview, W. Va.

Elevation, 1195' L.

8 $\frac{1}{2}$ " casing, 1703'; 6-5/8", 2131'.

Coal was encountered at 532-535, 795-800, and 895-902'.

Abandonment reported to Dept. of Mines Sept. 26, 1934.

Well was not shot.

Salt water at 1806-1855'.

Producing hole; now exhausted.

	Top.	Bottom.	Thickness.
Coal	532	- 535	3
Coal	795	- 800	5
Pittsburgh Coal	895	- 902	7
Big Dunkard Sand	1335	- 1475	140
Gas Sand	1635	- 1661	26
First Salt Sand	1690	- 1718	28
Second Salt Sand (water, 1806-1855')	1730	- 1895	165
Little Lime	2074	- 2086	12
Pencil Cave	2107	- 2112	5
Big Lime	2112	- 2179	67
Big Injun Sand (oil, 2258'; gas, 2270')	2179		
Fourth Sand (oil, 3145-3147')	3130	- 3191	
Total depth			3191
Formerly filled and plugged to present T.D.			2275

MON-90-A

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. _____ Well No. 506

Bege Construction & Refining Company Company of 448 West Main St.

Glenburg, W. Va. on the W. J. Bedy Farm

containing 10 acres. Location _____

Clay District, in Minnehaha County, West Virginia

The surface of the above tract is owned in fee by Wm. Shuman

of Blacksburg, W. Va. address, and the mineral rights are owned by

W. J. Bedy, Walter G. Mather Bedy, of Fairview, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No. _____ issued by the West Virginia Department of Mines, Oil and Gas Division

Elevation of surface at top of well, 1195 feet

The number of feet of the different sized casings used in the well.

_____ feet _____ dia. Wood casing.

1000 feet 8 1/2 dia. reg. 5151 feet 6 1/2 dia. reg.

_____ feet _____ dia. reg. _____ feet _____ dia. reg.

_____ feet _____ dia. reg. _____ feet _____ dia. reg.

_____ pair of _____ dia. set at _____

_____ pair of _____ dia. set at _____

_____ in casing perforated at _____ feet to _____ feet.

_____ in casing perforated at _____ feet to _____ feet.

Coal was encountered at 500 feet, thickness 20 inches, and at 700

feet, thickness 20 inches; and at 800 feet, thickness 20 inches.

Lines were used as follows: (Give details) _____

September 22th, 1934. Date.

Approved Bege Construction & Refining Co., Owner.

By _____



Asst. General Supt.

OCT 1 - 1934

copy 1/2c

Hope Construction & Refining Company

COMPLETION DATA SHEET

Glarksburg, E. Va. Address

No. 2

Well No. 279

FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Coal				588	588	8"		
Coal				798	800	8"		
Pittsburgh Coal				895	902	7"		
Big Buckner Sand				1385	1475	140"		
Gas Sand				1685	1681	28"		
First Salt Sand				1690	1718	28"		
Second Salt Sand		Water--	1698-1885	1730	1885	165"		1783' - 8 1/2" 2131' - 6 3/8"
Little Lim				2074	2086	12"		
Fossil Cove				2107	2112	8"		
Big Lime				2112	2179	67"		
Big Injun Sand		Oil-- Gas--	2220 2270	2179	Present	2270		
Fourth Sand		Oil--	2140-2157	2120	2161	Original	2161	
Formerly filled and plugged to 2270 present total depth.								

Well was not shot at _____ feet; well was shot at _____ feet.

First fresh water at _____ feet; fresh water at _____ 1898-1925 feet.

Well was _____ producing _____ lbs. _____ Now exhausted.

September 22th, 1924.

Approved _____

NOTE: All bottom formations must be noted as indicated above and all bar-codes and oil and gas flows must be recorded when their proper geological names to the district as well as any local names commonly used in the district for each rock.

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

<u>No. coal operations in this section.</u>	<u>Hope Construction & Refining Company</u>
<small>COAL OPERATOR OR OWNER</small>	<small>NAME OF WELL OPERATOR</small>
_____	<u>Clarksburg, West Virginia.</u>
<small>ADDRESS</small>	<small>COMPLETE ADDRESS</small>
_____	<u>November 28th, 1934.</u>
<small>COAL OPERATOR OR OWNER</small>	<small>WELL AND LOCATION</small>
_____	<u>Clay</u> District
<small>ADDRESS</small>	<small>COUNTY</small>
_____	<u>Minnehaha</u> County
<small>COAL OPERATOR OR OWNER</small>	<small>WELL NO.</small>
_____	<u>279</u>
<small>ADDRESS</small>	<small>NAME</small>
_____	<u>W. J. Eddy</u> Firm

AFFIDAVIT TO BE MADE BY OPERATOR, AND COPY TO BE MAILED BY OPERATOR SHALL BE FOR DEPARTMENT, AND COPY TO BE AFFIDAVIT BY THE WELL OPERATOR AND THE TRUSTEES AND OTHER OFFICERS OF COMPANY, TO BE AS Laid TO EACH WELL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA, }
COUNTY OF Minnehaha } ss:

John E. Shisler and William E. Tuttle
being first duly sworn according to law depose and say that they are experienced in the work of plugging
and filling oil and gas wells and were employed by Hope Construction & Refining Co., well operator,
and participated in the work of plugging and filling the above well, that said work was commenced on the
28th day of November, 1934, and that the well was plugged and filled in
the following manner:

Manner in which said well was plugged: Filled hole from total depth (2100') to 2000' with Clay
and put in cement plug, tubular to pull 2-4/8" Casp. Cut down at 2000' and pulled out,
filled hole with Clay to 2000' then filled hole with Clay to 1950' and drove 2-4/8"
N & F. Wood Ring and Cement Plug, tubular to pull 2-4/8" Casp. Filled hole up in side of
2-4/8" Casp. to 1150' cut 2-4/8" Casp. at 1150' and pulled out, drove 2" N & F. Wood
ring at 1150' and Cement Plug at this depth, filled with Clay to 1100' bridged hole at
200' tubular to pull 2" Casp. rigged down from 200' to 250' then plug, haul and filled with
cement.

Manner in which said well was plugged:

Cemented 2 1/2" Casing from 200' to 250' then 2" Casp. after
rigging came from 200' to 250' Filled hole with Cement to 700' Filled with Clay 200'
Cut 2" Casp. at 200' while pulling out, cemented 2 1/2" Casing from 200' to 250' and filled
hole with Clay to top of Cement.

Description of monument: Erected Cement Monument Size 6" x 6" x 60"-65" of which
extends above the ground with the following inscription,
(Hope Construction & Ref. Co. 279, 2 1/2")

AND WHEREAS SAID OPERATOR HAS BEEN AND IS SATISFIED WITH THE REPRESENTATION OF OFFICERS OF SAID COMPANY AS TO THE WORK
AND THAT THE WORK OF PLUGGING AND FILLING SAID WELL WAS COMPLETED ON THE 28th day of November, 1934
1934

And further deponents with out.

Sworn to and subscribed before me this 20 day of December, 1934

My Commission expires:

July 15, 1935

John E. Shisler
William E. Tuttle
W. J. Eddy 1934
W. J. Eddy
Notary Public