

LATITUDE

39° 37' 30"

75'

80° 17' 30"

LONGITUDE

7'5 OGIS topo location

7.5' loc	<u>0.285</u>	15' loc	<u>3.165</u>
	<u>1.520</u>	(calc.)	<u>3.740</u>

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad Mannington (Mannington EC)

County Monongahela

District Battelle

WELL LOCATION MAP

File No. 061-97A

PLAN OF THE PROPOSED ABANDONMENT OF WELL NO. 1270 OF  
 THE MANUFACTURERS LIGHT & HEAT CO. OF PITTSBURGH, PA.  
 ON THE ALBERT STAMM FARM CONSISTING OF 24 ACRES  
 LOCATED IN SHERIDAN TOWNSHIP, WASHINGTON COUNTY, PA.  
 OF 1932-33



ENGINEER'S CERTIFICATE

I, THE UNDERSIGNED, ENGINEER, HEREBY CERTIFY THAT THE PLAN OF THE ABANDONMENT OF WELL NO. 1270 OF THE MANUFACTURERS LIGHT & HEAT CO. OF PITTSBURGH, PA. ON THE ALBERT STAMM FARM CONSISTING OF 24 ACRES LOCATED IN SHERIDAN TOWNSHIP, WASHINGTON COUNTY, PA. OF 1932-33 IS A TRUE AND CORRECT COPY OF THE ORIGINAL PLAN OF SAID WELL.

W. J. [Signature]  
 ENGINEER

Battelle District, Monongalia County, W. Va.

By The Manufacturers Light & Heat Co., 500 Union Trust Bldg.,  
Pittsburgh, Pa.

On 64 acres, surface owned by F. M. Kfan, Wadestown, W. Va., and  
mineral rights by ML&H Co., Pgh., Pa.

Drilled prior to June 1, 1929.

Elevation, 1380' L.

13" conductor, 16'; 10" casing, 416'; 8½", 1635'; 6-5/8", 2420';  
5-3/16", 3337' 7".

Packer, 5-3/16".

Coal was encountered at 765-770, 1033-1040, and 1138-1145'.

Abandonment reported to Dept. of Mines Nov. 16, 1934.

	Top.	Bottom.	Thickness.
Bluff Sand	705	- 765	60
Fairview (Waynesburg) Coal	765	- 770	5
Mapletown (Sawickley) Coal	1033	- 1040	7
Pittsburgh Coal	1138	- 1145	7
Murphy Sand	1240	- 1280	40
Red rock	1300	- 1305	5
Red rock	1440	- 1460	20
Little Dunkard Sand	1495	- 1515	20
Big Dunkard Sand	1685	- 1710	25
Gas Sand	1815	- 1900	85
1st Salt Sand	1920	- 1960	40
2nd Salt Sand	2080	- 2140	60
Maxton Sand	2270	- 2290	20
Red rock	2290	- 2310	20
Little Lime	2335	- 2365	30
Pencil Cave	2365	- 2370	5
Big Lime	2370	- 2425	55
Big Injun Sand	2425	- 2580	155
Squaw Sand	2590	- 2615	25
50-Ft. Sand (show of gas, 3049')	3035	- 3083	48
30-Ft. Sand	3088	- 3128	40
Red rock	3164	- 3172	8
Sand	3172	- 3200	28
Gordon Stray Sand	3295	- 3320	25
Gordon Sand	3327	- 3340	13
4th Sand (show gas, 3389-3392' and 3402-3405')	3371	- 3408	37
Slate, to bottom	3465	- 3468	3

# WEST VIRGINIA DEPARTMENT OF MINES

## OIL AND GAS DIVISION

### PRELIMINARY DATA SHEET NO. 1

File No. \_\_\_\_\_ Well No. 3-3200

The Manufacturers Light & Heat Company, of 800 Union Trust Building,

Pittsburgh, Pa., as the Albert Efew, et al, Firm

containing 6 1/2 acres. Location \_\_\_\_\_

Buttelle District, in Monongalia County, West Virginia

The surface of the above tract is owned in fee by F. H. Efew

of Wadestown, W. Va., address, and the mineral rights are owned by

The Manufacturers Light & Heat Co., of Pittsburgh, Pa.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No. \_\_\_\_\_ prior to June 1, 1929 issued by the West Virginia Department of Mines, Oil and Gas Division

\_\_\_\_\_

Elevation of surface at top of well, 1300 feet Depth \_\_\_\_\_

The number of feet of the different sized casings used in the well.

\_\_\_\_\_ feet 15 x 16 \_\_\_\_\_ also, Wood casing.

136' feet 10" also, cas. 1635 feet 8 1/4" steel cas.

2220 feet 6 5/8" also, cas. 3337.7" feet 5 3/16" steel cas.

\_\_\_\_\_ feet \_\_\_\_\_ also, cas. \_\_\_\_\_ feet \_\_\_\_\_ steel cas.

\_\_\_\_\_ number of 5 3/16" \_\_\_\_\_ also, cas. at \_\_\_\_\_

\_\_\_\_\_ number of \_\_\_\_\_ also, cas. at \_\_\_\_\_

\_\_\_\_\_ in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet

\_\_\_\_\_ in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet

Coal was encountered at 765 feet; thickness 60 inches, and at 1635

feet; thickness 6 1/2 inches; and at 1338 feet; thickness 6 1/2 inches.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

November 16th, 1924.

Approved: THE MANUFACTURERS LIGHT & HEAT CO., Owner.

By E. A. Clark Land Dept.

11/17/24

11/17

800 Union Trust Bldg., Pittsburgh, Pa. Address

No. 2

FORMATION RECORDED

Well No. 3-2800

Albert Rfaw, et al., farm

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Chart Depth	Remarks
Bluff Sand				705	765	2	60	
Fairview Coal				765	770		5	
Mapleton Coal				1055	1060		5	
Pittsburgh Coal				1138	1145		7	
Murry Sand				1260	1280		20	
Red Hook				1300	1305		5	
Red Hook				1460	1460		20	
Red Hook				1495	1535		20	
Little Dunbar				1605	1730		25	
Big Dunbar				1815	1880		65	
Gas Sand				1880	1940		60	
1st Salt Sand				2080	2110		30	
2nd Salt Sand				2070	2090		20	
Mason Sand				2080	2350		270	
Red Hook				2355	2360		5	
Little Lane				2360	2370		10	
Fossil Cove				2370	2405		35	
Big Lane				2600	2600		20	
Big Injun Sand				2600	2615		15	
Sugar Sand				2615	2620		5	
20-Foot Sand				2620	2630		10	
20-Foot Sand				2630	2635		5	
Red Hook				2635	2640		5	
Sand				2640	2650		10	
Gordon Street				2650	2655		5	
Gordon Sand				2655	2660		5	
4th Sand				2660	2665		5	
Sink				2665	2665		0	
Total depth								

Well was not shut at \_\_\_\_\_ feet, well was shut at \_\_\_\_\_ feet

First fresh water at \_\_\_\_\_ feet, first fresh water at \_\_\_\_\_ feet

Well was producing \_\_\_\_\_ bbls  
day-

THE MANUFACTURERS LIGHT &amp; HEAT COMPANY.

November 14, 1920

Approved

E. A. Clark

Local Engineer

NOTE: All bottom formations must be noted as indicated above and all bar-reads and all cut and gas reads must be recorded under their proper geological names in the column as well as any local names commonly used in the district for such rocks.

