


LATITUDE 39°42'30"

450



LONGITUDE

7'5 OGIS topo location

7.5' loc	$\frac{0.535}{0.26W}$	15' loc	$\frac{3.415}{2.50W}$
		(calc.)	

Company _____

Farm _____

Quad Blacksville (Blacksville NW)

County Monongahela

District Clay

WELL LOCATION MAP

File No. 061-132A

Plot showing the location of Well No. 2 of the
 receiver of the Moore-Paul Oil Company of Morgantown, West
 Virginia, to be abandoned on the 2.2 Acres farm of 20-2-4 acres
 located in Clay District, Boone County, West Virginia.



WITNESSES & DECLARATION.

I, the undersigned having verified that this map is correct
 and shows all the information to the best of my knowledge and
 belief required by the law and give evidence of the Mining Laws
 of West Virginia.

[Handwritten signature]

Witnessed before me a Notary Public, on and for
 Boone County, West Virginia, this 11th day of
 May, 1930.
 My Commission Expires

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. 202107 Well No. 2

By Wm. S. Glasscock Jr.,
Special Inspectors of Marathon Oil Company of Wilmington, V. W.

at the E. S. Sprank well
(formerly Mr. Myers)
containing 20 1/4 acres. Location 1 mile south of Blacksville V. W.

Clay District, Monroe County, West Virginia

The surface of the above tract is owned in fee by E. S. Sprank
of Blacksville V. W. Pittsburgh, Pa.

Sealed Co. (formerly Clay District Seal Co.) of Pittsburgh, Pa.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit
No. before permits were issued by the West Virginia Department of Mines, Oil and Gas Division

March 1921

Depth of surface at top of well 1150 feet

The number of feet of the different sized casings used in the well:

Size	Depth	Material	Weight
16"	feet	of conductor	feet
4 1/2"	feet	to 1/2"	feet
10 1/2"	feet	to 5/8"	feet
20 1/2"	feet	to 1 1/8"	feet
30 1/2"	feet	2" tubing	feet
	feet	of	feet
	feet	of	feet
	feet	of	feet

Pittsburgh coal in casing perforated at feet to feet

Sealed Co. coal in casing perforated at feet to feet

Sealed Co. coal in casing perforated at feet to feet

Notes were used as follows: (Give details) None

September 29, 1921

Wm. S. Glasscock and
Special Inspectors of

Subt. J. Henson and
 Wm. B. Glascock Jr.,
 Special Receivers of
 Moore-Tex Oil Company

BOOK #2

OIL OR GAS WELL See Well

Company: Morgantown, W. Va.
 Address: R. E. Brock
 (Formerly Sub. Meyers)
 COMPLETION DATA SHEET
 No. 2
 FORMATION RECORD

WELL NO. 2

Name	Color	Character	Oil Gas or Water	Top	Bottom	Thickness	Feet Thick	Remarks
Swickley coal	.	.	.	705	711	6	711	6' 7" - 6' 11"
Pittsburgh coal	.	.	.	800	808	8	808	
Murphy sand	.	.	.	890	920	30		
Little Duckard sand	.	.	.	1130	1460	130		
First Salt sand	.	.	.	1970	1807	237		18' 11" - 19' 7"
Little Lino	.	.	.	2002	2006	4		
Fencil Cove	.	.	.	2006	2032	6		
Big Lino	.	.	.	2032	2083	51		
Big Injun sand	.	.	.	2083	2313	230		22' 4" - 23' 0"
Hayard sand	.	.	.	3205	3232	7		
GAS at	.	.	gas	3206	3220			3' 14" - 3' 28"
total depth.....							3220	

Well was set at 3224-3230

Fresh water at

original production was gas

Subt. J. Henson and
 Wm. B. Glascock Jr.,
 Special Receivers of
 Moore-Tex Oil Company

September 26, 1935

Approved

Form 60

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

PREPARED BY GEORGE S. ARNOLD & COMPANY AS OF THE DATE

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION**

132-

Coalwood Co., Inc.
(Formerly Clay District (L) Co.)

Geo. S. Arnold and
Company, Inc.,
1000 11th Street, N. W.,
Washington, D. C.

Union Industrial Lumber Co.,
Martinsburg, W. Va.

P. O. Box 872, Charleston, W. Va.

Oil District of West Virginia

WELL AND LOCATION

Clay

CLAY STATE

S. S. Beck

MINER, DISTRICT

Stonewall, W. Va.

Well No. 2

S. S. Beck
Testimony of Mr. [Name]

AFFIDAVIT

STATE OF WEST VIRGINIA
County of Marshall

I, S. S. Beck do hereby certify that the above named well was plugged and filled in accordance with the provisions of the laws of this State, and that the well was plugged and filled in the following manner:

There is a well and was plugged:

hole was filled with clay from the bottom 20' to top.
Bottom 20' was filled from 20' to 20'
hole was cemented from 20' to 20'

A concrete collar was set at 20'
This was filled with concrete to the top.
The concrete was set at 20'.
The hole was filled with concrete to the top.
The concrete was set from 20' to 20'

Description of operation:
A concrete collar was set. This extends 10 inches above the
ground surface and has a collar at the top of 6" x 6".

and that the well was plugged and filled and well was completed on the 15th day of October, 1935



[Handwritten signature]

S. S. Beck