

LATITUDE 39° 42' 30"

150

80° 12' 30"

LONGITUDE

7'5 OGIS topo location

7.5' loc	<u>0.315</u>	15' loc	<u>3.195</u>
	<u>0.68w</u>	(calc.)	<u>2.90w</u>

2385 on Eggenmans

Company _____

Farm _____

Quad Blacksills (Blsville NW)

County Monongahela

District Clay

WELL LOCATION MAP

File No. 061-135A

Plan showing the location of Hall No. 26 of John L. Deagan et al., of Morgantown, West Virginia, to be abandoned on the both E Stephens farm of 141.4 acres, located in Clay District, Boone County, West Virginia.



WITNESSES' CERTIFICATE

We, the undersigned hereby certify that this map is correct and shows all the information to the best of my knowledge and belief required by the act and the section of the Mining Law of West Virginia.

E. P. Dealey
 E. P. Dealey

Subscribed before me a Notary Public, in and for Boone County, West Virginia, this 11th day of May, 1940.
 My commission expires July 1, 1940.

Cabell H. Mearns

110

11

11

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

The No. 44 Phillips Shelby 1717
 is in the Phillips Shelby 1717

161.6 ft. Clay

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well


The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well

The Clay is 2 inches thick at the top of the well



Dec 16 1905
42 Phillips

Dr. J. H. Williams
 Charleston, S. C.

Company
 Address

COMPLETION DATA SHEET
 NO. 2
 FORMATION RECORD

Time	Rate	Pressure	Temp	Gas	Water	Oil	ML
10:00	100	100	100	100	100	100	100
10:15	100	100	100	100	100	100	100
10:30	100	100	100	100	100	100	100
10:45	100	100	100	100	100	100	100
11:00	100	100	100	100	100	100	100
11:15	100	100	100	100	100	100	100
11:30	100	100	100	100	100	100	100
11:45	100	100	100	100	100	100	100
12:00	100	100	100	100	100	100	100

Well No. _____ Date _____

Well Name _____

Dr. J. H. Williams
 Charleston, S. C.

842 Phillips

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

No. 32
H. L. Phillips of Blacksville W. Va.
 on the North East
 corner of Sec. 6 Town Map
 The location of the well is stated as follows: Blacksville W. Va.
North East
 The oil and gas payables are held under lease by the above named company, and this well is drilled under permit
 No. 1353 issued by the West Virginia Department of Mines, Oil and Gas Division

Direction of surface at top of well: 1353

The number of feet of the different strata encountered in the well:

Feet	Stratum	Feet	Stratum	Feet	Stratum
957	10"	3188	5 3/4"		
1785	8 1/4"	5252	3"		
2072	6 5/8"				

Feet of _____
 Feet of _____
 In casing perforated at _____ feet to _____ feet
 In casing perforated at _____ feet to _____ feet

Casing was cemented at _____ feet, thickness _____ inches, and at _____ feet, thickness _____ inches, and at _____ feet, thickness _____ inches.

Other data were used as follows: (Give details)

Mar. 23 1935
G. L. Phillips

G. L. Phillips

Company

COMPLETION DATA SHEET

NO. 2

Madisonville, Mo.

Address

FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Permeability	Remarks
Sand				500	510	10		
Sand				551	560	9		
Fgh .col				551	572	21		
Little upward				1200	1200	0		
Sls 1200-00				1400	1400	0		
Sls 1400				1500	1500	0		
First Sls			10000 2700	1700	1700	0		
Second Sls			10000 2400	1700	1700	0		
Sand and				2000	2100	10		
Little Sls				2100	2100	0		
Small Sls				2100	2100	0		
Sls 1000			1000 1000	2200	2200	0		
Sls 1000				2200	2200	0		
Sand and				2200	2200	0		
Sand and				2200	2200	0		
Sls 2000				2200	2200	0		
Third Sls				2200	2200	0		
Fourth Sls			1000 2000	2200	2200	0		
Fifth Sls			1000 2000	2200	2200	0		

Oil well completion at _____ feet, well was shut in _____ feet

Gas well completion at _____ feet, well was shut in _____ feet

Well was completed on _____
 Nov. 23, 1935 G. L. Phillips

PROPOSED MANNER OF PLUGGING AND FILLING WELL

(Approved by State and Department)

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

WORK ORDER

*3 1/2" casing finished 4/25
Plug in top of 3 1/2" casing
3 1/2" - 4 1/2" casing
Cement outside 4 1/2" casing
Casing through lead
and above 3 1/2" casing*

This is to be plugged and filled as follows:

WELL NO. 2 21-1121 - 7 1/2" SURFACE OF STEEL

Fill 2" tubing set at 2222'

Fill with red clay from 2222' to 2217' - 20' above the Fourth Lead

Drill cement sand plug from 2217' to 2214'

Seal from 2214' to 2209', using steel cement sealing the lead.

WELL 2-4-12" casing set at 2182'

Set a "STANDARD" BEARING OF 2200', using cement

Fill with clay from 2200' to 2217' - 20' above the 3 1/2" casing.

Drill cement sand plug from 2200' to 2200'

Seal from 2200' to 2200'

Set a "STANDARD" BEARING OF 2182' using cement

Fill with clay from 2182' to 2177' - 20' below the 3-1/2" casing

Set steel plug from 2177' to 2172'

WELL 2-4-1/2" casing set at 2172'

Continue filling with clay from 2172' to 2167' - 20' below 3-1/2" casing

Set steel plug from 2167' to 2162'

WELL 2-4-1/2" casing set at 2162'

Continue filling with clay from 2162' to 2157' - 20' above the Fifth Lead.

Set steel plug from 2157' to 2152'

Seal from 2152' to 2147' sealing the Fifth Lead.

Set a "STANDARD" BEARING OF 2147' - 20' below the 3 1/2" casing

Fill 2" tubing set to about 2147' - above the First Lead Lead.

Seal from 2147' to 2142' - through the 7 1/2" string lead

Fill with clay from 2142' to 2137' - 20' below the 3 1/2" casing

Seal from 2137' to 2132' through the casing

Fill with clay from 2132' to 2127' - 20' below the First Lead Lead

Seal from 2127' to 2122' through the casing

Fill balance of casing lead

Fill to the surface with clay

To be approved by State
and County or Division
and a Plugging Order.

Send a copy of this to be described in Rule 14, 1911 Regulations.

Comments:

The "well order" is submitted for your approval and enforcement and unless notified of your disapproval or non-compliance, the undersigned will proceed with the plugging and filling of well with the above described manner as far as stated in the name of Division to plug and abandon the well with its regular use of the State.

Very truly yours,

J. L. Phillips
Oil Engineer

It is declared here that the said work is not done, or not properly done, or not done at all, or that the same is not done in accordance with the provisions of the laws of this State, or that the same is not done in accordance with the laws of this State, or that the same is not done in accordance with the laws of this State, or that the same is not done in accordance with the laws of this State.

at _____, W. Va.

DEPARTMENT OF MINES
Oil and Gas Division

NOTICE OF INTENTION TO PLUG AND ABANDON WELL

Form No. 1 (Revised 1-1-64)

WEST VIRGINIA DEPARTMENT OF MINES

MSL 420 640 010000

To The Department of Mines,
Charleston, W. Va.

Wetmore

J. P. Phillips
Sept. 26 1919
500.00 .05

Wetmore
Wetmore
Wetmore

The undersigned well owner is desirous to close the above described well because the

well is plugged and abandoned and will be the property of the State of West Virginia as provided in the

This notice is given you to advise that your representative may be present at the plugging

This notice is being mailed by registered mail to each of you at the above addresses at the above date

J. P. Phillips

